



CITY OF  
**West Linn**

**PLANNING MANAGER DECISION**

DATE: October 3, 2024

FILE NO.: WAP-24-01

REQUEST: Approval of a Water Resource Area (WRA) permit utilizing the alternative review process at 5494 Linn Lane for the purpose of demolishing the existing home to be replaced with a new single-family dwelling.

PLANNER: Chris Myer, Associate Planner

---

Planning Manager DSW

---

**TABLE OF CONTENTS**

STAFF ANALYSIS AND DECISION

GENERAL INFORMATION .....	2
EXECUTIVE SUMMARY .....	3
PUBLIC COMMENTS.....	4
DECISION AND CONDITIONS OF APPROVAL.....	5
ADDENDUM: APPROVAL CRITERIA AND FINDINGS.....	7

EXHIBITS

PD-1 APPLICANT SUBMITTAL.....	38
PD-2 COMPLETENESS LETTER .....	122
PD-3 PUBLIC COMMENTS .....	124
PD-4 AGENCY COMMENTS .....	129
PD-5 AFFIDAVIT AND NOTICE PACKET.....	130

## GENERAL INFORMATION

<b>OWNER:</b>	Robert Easton 21520 Lupine Ct. West Linn, OR 97068
<b>Applicant:</b>	Kevin Janssen 614 SE 52 <sup>nd</sup> Ave West Linn, OR 97068
<b>CONSULTANT:</b>	Kim Cartwright Schott & Associates PO Bo 589 Aurora, OR 97002
<b>SITE LOCATION:</b>	5494 Linn Lane
<b>SITE SIZE:</b>	29,3157 Square Feet
<b>LEGAL DESCRIPTION:</b>	Tract 2 of Lot Line Adjustment PS-26020 (1994) Tax lot 21E25BD00500
<b>COMP PLAN DESIGNATION:</b>	Low Density Residential
<b>ZONING:</b>	R-10, Residential
<b>APPROVAL CRITERIA:</b>	Community Development Code (CDC) Chapter 11: Residential; Chapter 32: Water Resource Area Protection; Chapter 48: Access, Egress, and Circulation; Chapter 96: Street Improvement Construction; and Chapter 99: Procedures for Decision-Making: Quasi-Judicial.
<b>120-DAY RULE:</b>	The application became complete on July 29, 2024. The 120-day period therefore ends on November 5, 2024.
<b>PUBLIC NOTICE:</b>	Notice was mailed to property owners within 500 feet of the subject property and to the affected neighborhood association on July 31, 2024. A sign was placed on the property on July 30, 2024. The notice was also posted on the City's website on July 29, 2024. Therefore, public notice requirements of CDC Chapter 99 have been met.

## EXECUTIVE SUMMARY

The applicant is requesting approval of a Water Resource Area (WRA) permit utilizing the alternative review procedures of CDC 32.070 to demolish an existing single-family dwelling and replacing it with a new and larger single-family dwelling at 5494 Linn Lane (Clackamas County Tax Lot 21E25BD00500). The site is documented as containing a stream identified on the adopted West Linn Water Resource Area Map.

In compliance with the requirements of CDC Chapter 32 (Water Resource Area Protect), the applicant submitted an environmental analysis of the site prepared by Schott & Associates (Exhibit PD-1). The report was unable to identify a stream within the project area, but did identify two wetlands associated with a drainage swale near the roadway. Wetland 1 is located to the left of the existing driveway when viewed from the roadway, extends off-site to the south, and is approximately 0.006 acres in size. Wetland 2 is located to the right of the existing driveway and is approximately 0.04 acres in size. Below is a map of the Water Resources and Water Resource Area as documented by the consultant:




Figure 2: Existing Conditions

Per Clackamas County assessment records, the existing home was constructed in 1960 and is approximately 1,487 square feet in size. The proposed home will be approximately 6,385 square feet in size and will have a low profile to comply with a view easement held by an

adjoining neighbor. The existing driveway will be widened from 9.5 feet to 15 feet and new retaining walls constructed to support the driveway.

### **Public Comments:**

Staff received one comment from the Department of State Land (Exhibit PD-3) and two comments from the nearby residents (see Exhibit PD-4) prior to the close of the comment period. The comments are summarized below with responses from staff.

#### **Matthew Unitis, Oregon Department of State Lands (August 28, 2024)**

- “A state permit will not be required for the proposed project because, based on the submitted site plan, the project avoids impacts to jurisdictional wetlands, waterways, or other waters.”
- “Wetlands as depicted in WD-2023-0462 appear to be avoided. Therefore, no state permit is needed.”

Staff Response: Staff notes the Department of State Lands (DSL) determination, and Condition 1 requires conformance with the submitted plans during construction implementation. If the plan changes substantially, coordination with DSL will occur.

#### **Steve and Lorna Lathram, letter dated August 20, 2024.**

- *“The terrain in our area is on the side of a hill with significant sloping and run off.”*
- *“We are very concerned about our existing hillside and the causally cascading impacts any reshaping may bring.”*
- *“We are confident that you will not allow for any unnecessary disturbance of our property or quality of life.”*

Staff Response: Mr. and Mrs. Lathram own the property two houses uphill to the south. The applicant has prepared a preliminary stormwater management report by White Pelican Consulting (Exhibit PD-1), and development on the property will be subject to City stormwater standards as part of normal building permit review, which will filter and control additional runoff generated by the increase in impervious surfaces. The applicant has provided a geotechnical engineering report and slope stability evaluation prepared by Hardman Geotechnical Services Inc and dated March 3, 2023. The report evaluated the potential for geological risk related to construction on the site, and concluded that the proposed development is geotechnically feasible, provided the recommendations of the report are implemented in the design and construction phases of the project. Condition of Approval #4 will ensure the recommendation of the geological report is implemented during the design and construction phases.

#### **Jim Jensen email dated August 9, 2024.**

- *“The applicant states in his response to the letter from the City that the required Construction Management Plan is contained in Sheet A Plot Plan. This Plan does not address the items required in CDC 32.050 paragraph 1 concerning TDAs nor appropriate erosion control measures in paragraph 2.”*

- *“The proposed site is at the north end of Linn Lane, a dead-end, very narrow (1.5 lanes) street. Construction vehicles will cause much disruption of local traffic, especially if construction vehicles are allowed to park on the street. There is no mention on the plan of where construction vehicles will park. In addition, the street asphalt is already severely cracked in multiple places. Heavy construction vehicles will place a severe strain on the already degraded condition. What is the mitigation for this effect.”*
- *“The site is extremely steep with little area for storage of construction materials and, especially, where dirt disrupted from grading and construction will be stored without impacting the WRA.”*

Staff Response: Mr. Jensen resides approximately mid-block between the project site and Rosemont Road. Erosion control measures are typically reviewed for compliance at the time of site development and building permits, and will be reviewed and inspected for conformance with city standards as part of normal building permit review and inspection. Condition #3 requires submission of a construction management plan meeting all of the requirements of CDC 32.050(G), though staff notes that the purpose of the plan is to protect the water resource area during construction and not to regulate construction vehicle parking generally or the mitigation of heavy truck traffic on public rights of way. Traffic and parking enforcement is the purview of the West Linn Police Department.

## DECISION

The Planning Manager (designee) approves this application (WAP-24-01), based on: 1) the findings submitted by the applicant, which are incorporated by this reference, 2) supplementary staff findings included in the Addendum below, and 3) the addition of conditions of approval below. With these findings, the applicable approval criteria are met. The conditions are as follows:

1. **Site Plan, Elevations, and Narrative.** With the exception of modifications required by these conditions, the project shall conform to the submitted plans, elevations, and narrative submitted in Exhibit PD-1.
2. **Engineering Standards.** All public improvements and facilities associated with the approved site design, including but not limited to street improvements, driveway approaches, curb cuts, utilities, grading, onsite and offsite stormwater, street lighting, easements, easement locations, and connections for future extension of utilities are subject to conformance with the City Municipal Code and Community Development Code. The City may partner with the applicant to fund additional improvements as part of the project.
3. **Construction Management Plan.** Prior to issuance of building permits, the applicant shall submit a revised construction management plan that meets the content criteria of CDC 32.050(G), and an accompanying letter by the project biologist approving the proposed management plan.
4. **Geotechnical Design.** The geotechnical report prepared by Hardman Geotechnical Services Inc. shall be submitted with the building permit application and its recommendations for review by the building official. The recommendations of the report shall be implemented during design and construction.
5. **Street Improvements.** Prior to issuance of building permits, the applicant shall construct half-street improvements or pay a fee-in-lieu. A fee-in-lieu of street improvements is calculated using the fee schedule in place at the time of building permit issuance. The fee is calculated at \$405 per linear foot of property frontage. Based on County records, the subject property has 81.67 linear feet of property frontage therefore  $\$405 \times 81.67 = \$33,076$  as a fee-in-lieu amount.
6. **WRA Delineation During Construction.** The Applicant shall install an anchored chain link fence 15 feet from top of stream bank prior to grading or development and shall remain for the duration of the project.
7. **Restoration of Temporarily Disturbed Areas (TDA).** The Applicant shall restore all TDAs to pre-construction condition of grade and soil permeability and re-vegetate them with native plantings in line with the re-vegetation requirements of CDC 32.100.

8. **Re-Vegetation Inspection.** Before requesting Final Planning inspection, the Applicant shall provide a signed letter from the parties responsible for plantings on site that indicates all plantings conform to the planting plan within Exhibit PD-1.
9. **Access Plan.** The location of the proposed structure shall conform to the site plan approved by Tualatin Valley Fire & Rescue in Exhibit PD-1.
10. **Maintenance of Plantings.** The Applicant shall ensure a minimum survival rate of 80% of trees and shrubs planted by the third year after the date at which all mitigation plantings were completed and submit a report at that time from the parties responsible for plantings that demonstrates the survival of plantings. The Applicant shall be responsible for monitoring and maintaining all plantings with the following practices:
  - a. Plants that die must be replaced in kind.
  - b. New plantings shall be mulched to a minimum of three inches in depth and 18 inches in diameter.
  - c. Plantings shall be watered one inch per week between June 15<sup>th</sup> to October 15<sup>th</sup> for the three years following planting.
  - d. Non-native and/or noxious vegetation shall be controlled or removed
  - e. Bare root trees shall be planted between December 1<sup>st</sup> and February 28<sup>th</sup>, and potted plants shall be planted between October 15<sup>th</sup> and April 30<sup>th</sup>.
  - f. Plant sleeves or fencing shall be used to protect trees and shrubs against wildlife browsing and damaging plants.
11. **List of Responsible Parties.** The Applicant shall provide a list of all parties responsible for work on site before issuance of the building permit. Any changes to the involved parties shall be communicated to the Planning and Building Departments via email.

The provisions of the Community Development Code Chapter 99 have been met.

Chris Myers  
Chris Myers, Associate Planner

October 3, 2024  
Date

Appeals to this decision must be filed with the West Linn Planning Department within 14 days of mailing date. Cost is \$400. An appeal to City Council of a decision by the Planning Director shall be heard on the record. The appeal must be filed by an individual who has established standing by submitting comments prior to the decision date. Approval will lapse 3 years from effective approval date if the final plat is not recorded.

Mailed this 3rd day of October 2024.

Therefore, the 14-day appeal period ends at 5 p.m., on October 17, 2025.

**ADDENDUM  
APPROVAL CRITERIA AND FINDINGS  
WAP-24-01**

This decision adopts the findings for approval contained within the applicant’s submittal, with the following exceptions and additions:

*11.030 PERMITTED USES*

*The following are uses permitted outright in this zoning district:*

- 1. Single-family attached or detached residential unit.*

*(...)*

**Staff Finding 1: This application proposes the replacement of a single-family detached residential structure on the site with a new single-family detached residential structure. The criteria is met.**

*11.070 DIMENSIONAL REQUIREMENTS, USES PERMITTED OUTRIGHT AND USES PERMITTED UNDER PRESCRIBED CONDITIONS*

*Except as may be otherwise provided by the provisions of this code, the following are the requirements for uses within this zone:*

<b>STANDARD</b>	<b>REQUIREMENT</b>	<b>ADDITIONAL NOTES</b>
<i>Minimum lot size Average minimum lot or parcel size for a townhouse project</i>	<i>10,000 sf 1,500 sf</i>	<i>For a single-family attached or detached unit</i>
<i>Minimum lot width at front lot line</i>	<i>35 ft</i>	<i>Does not apply to townhouses or cottage clusters</i>
<i>Average minimum lot width</i>	<i>50 ft</i>	<i>Does not apply to townhouses or cottage clusters</i>
<i>Minimum yard dimensions or minimum building setbacks</i>		<i>Except as specified in CDC <a href="#">25.070(C)(1)</a> through (4) for the Willamette Historic District. Front, rear, and side yard setbacks in a cottage cluster project are 10 ft. There are no additional setbacks for individual structures on individual lots, but minimum distance between structures shall follow applicable building code requirements.</i>
<i>Front yard</i>	<i>20 ft</i>	<i>Except for steeply sloped lots where the provisions of CDC <a href="#">41.010</a> shall apply</i>
<i>Interior side yard</i>	<i>7.5 ft</i>	<i>Townhouse common walls that are attached may have a 0-ft side setback.</i>
<i>Street side yard</i>	<i>15 ft</i>	
<i>Rear yard</i>	<i>20 ft</i>	
<i>Maximum building height</i>	<i>35 ft</i>	<i>Except for steeply sloped lots in which case the provisions of Chapter <a href="#">41</a> CDC shall apply.</i>
<i>Maximum lot coverage</i>	<i>35%</i>	<i>Maximum lot coverage does not apply to cottage clusters. However, the maximum building footprint for a cottage cluster is less than 900 sf per dwelling unit. • This does not include detached garages, carports, or accessory structures.</i>



STANDARD	REQUIREMENT	ADDITIONAL NOTES
		<ul style="list-style-type: none"> <li>• A developer may deduct up to 200 sf for an attached garage or carport.</li> </ul>
Minimum accessway width to a lot which does not abut a street or a flag lot	15 ft	
Maximum floor area ratio	0.45	Maximum FAR does not apply to cottage clusters.
Duplex, triplex, and quadplex	0.60	Type I and II lands shall not be counted toward lot area when determining allowable floor area ratio, except that a minimum floor area ratio of 0.30 shall be allowed regardless of the classification of lands within the property. That 30 percent shall be based upon the entire property, including Type I and II lands. Existing residences in excess of this standard may be replaced to their prior dimensions when damaged without the requirement that the homeowner obtain a non-conforming structures permit under Chapter 66 CDC.

[...]

**Staff Finding 2:** The subject property is a lot of record in the R-10 Residential zone. As shown on Sheet “A” of Exhibit PD-1, the applicant proposes a new structure in compliance with dimensional standards of the R-10 zone with a front yard setback of 70 feet, a rear setback of 54 feet, and side yard setbacks of 16.75 and 18.5 feet. FAR and lot coverage will be below the maximum permitted at approximately 22% and 23% respectively. Per the elevations presented on Sheets 1 and 2, the height will be approximately 39 feet, which is permitted per CDC 41.020 (Height Exceptions) due to the greater than 10-foot differential in grade between the highest and lowest grades of the structure, and will be verified at the time of normal building permit review. The criteria are met.

## **CHAPTER 32: WATER RESOURCE AREA PROTECTION**

### **32.020 APPLICABILITY**

A. This chapter applies to all development, activity or uses within WRAs identified on the WRA Map. It also applies to all verified, unmapped WRAs. The WRA Map shall be amended to include the previously unmapped WRAs.

B. The burden is on the property owner to demonstrate that the requirements of this chapter are met, or are not applicable to the land, development activity, or other proposed use or alteration of land. The Planning Director may make a determination of applicability based on the WRA Map, field visits, and any other relevant maps, site plans and information, as to:

1. The existence of a WRA;
2. The exact location of the WRA; and/or
3. Whether the proposed development, activity or use is within the WRA boundary.

In cases where the location of the WRA is unclear or disputed, the Planning Director may require a survey, delineation, or sworn statement prepared by a natural resource professional/wetland biologist or specialist that no WRA exists on the site. Any required survey, delineation, or statement shall be prepared at the applicant’s sole expense.

**Staff Finding 3:** The project site is documented as containing a stream identified on the adopted West Linn Water Resource Area Map, therefore the provisions of chapter 32 apply.

**The applicant has presented documentation demonstrating compliance with these standards which are contained in Exhibit PD-1. The criteria are met.**

**32.030 PROHIBITED USES**

*Alteration, development, or use of real property designated as, and within, a WRA is strictly prohibited except as specifically allowed or exempted in this chapter.*

*Table 32-1: Summary of Where Development and Activities May Occur in Areas Subject to This Chapter*

<b>Type of Development or Activity</b>	<b>In Water Resource</b>	<b>Water Resource Area</b>
<i>New house, principal structure(s)</i>	<i>No</i>	<i>No, except by hardship, CDC 32.100. Geotechnical study may reduce WRA width per Table 32-2 (footnote 4).</i>
<i>Additions to existing house, principal structure(s) and replacement in kind (replacement in kind does not count against the 500 sq. ft. limit so long as it remains within the existing footprint)</i>	<i>No</i>	<i>Yes, so long as it gets no closer to the WRA than building footprint that existed January 1, 2006. Max. 500 sq. ft. of addition(s) to side or 500 sq. ft. to side of building footprint furthest from WRA. No limit on vertical additions within existing footprint. (CDC 32.040(C)). Geotechnical study may reduce the WRA width per Table 32-2 (footnote 4).</i>
<i>New cantilevered decks (over 30 inches), balconies, roof overhangs and pop outs towards the WRA from existing house or principal structure(s)</i>	<i>No</i>	<i>Yes, but only 5 ft. into the WRA. Foundation or supports of structure cannot extend vertically to grade in the WRA. Geotechnical study may reduce the WRA width per Table 32-2 (footnote 4).</i>
<i>Decks within 30 inches of grade, at grade patios</i>	<i>No</i>	<i>Yes, but only to within 50 ft. of the water resource or 10 ft. behind the top of slope (ravine), whichever is greater.<sup>1</sup> Geotechnical study may reduce the WRA width per Table 32-2 (footnote 4).</i>
<i>New accessory structure under 120 sq. ft. and 10 ft. tall</i>	<i>No</i>	<i>Yes, but only if it is a minimum of 50 ft. from the water resource or 10 ft. behind the top of slope (ravine), whichever is greater.<sup>1</sup></i>

<b>Type of Development or Activity</b>	<b>In Water Resource</b>	<b>Water Resource Area</b>
<i>Repair and maintenance to existing accessory structures</i>	<i>No</i>	<i>Yes, but no increase in footprint or height.</i>
<i>Storm water treatment and detention (e.g., rain gardens, storm outfall/energy dissipaters)</i>	<i>No</i>	<i>Yes, private and public facilities including outfall and energy dissipaters are permitted if no reasonable alternatives exist.</i>
<i>Driveways/streets/bridges and parking lots</i>	<i>No, unless a WRA crossing is the only available route. No parking lots.</i>	<i>No, unless a WRA crossing is the only available route, or it is part of a hardship application. Parking lots only allowed in hardship cases the maximum distance from water resource.</i>
<i>New fence(s)</i>	<i>No markers or posts in a water resource.</i>	<i>Yes, but only to within 50 ft. of the water resource or behind the top of slope (ravine), whichever is greater.<sup>1</sup> In remainder of a WRA, only City approved property markers or posts every 25 ft. to delineate property.</i>
<i>Demolition of structure and/or removal of impervious surfaces in the WRA</i>	<i>Yes, restoration and re-vegetation required.</i>	<i>Yes, restoration and re-vegetation required.</i>
<i>Exterior lighting</i>	<i>No</i>	<i>No, except on existing buildings, additions or hardship cases, but light must be directed away from the WRA and less than 12 ft. high.</i>
<i>Public passive recreation facilities</i>	<i>No, except for bridges and utility crossings.</i>	<i>Yes, but only soft or permeable surface trails, bridges and elevated paths, interpretive facilities and signage. Hard surface ADA trails are allowed in WRA above top of slope associated with well-defined ravine WRAs.</i>
<i>Public active recreation facilities</i>	<i>No, except for bridges and utility crossings.</i>	<i>Yes, but natural surface playing fields and playground areas only in WRA above top of slope associated with well-defined ravine WRAs.</i>

<b>Type of Development or Activity</b>	<b>In Water Resource</b>	<b>Water Resource Area</b>
<i>Grading, fill (see also TDAs)</i>	<i>No, except for bridges and utility crossings.</i>	<i>Yes, after a WRA permit is obtained. Restoration and re-vegetation required.</i>
<i>Temporarily disturbed areas (TDAs) (e.g., buried utilities)</i>	<i>No, except as allowed by WRA permit.</i>	<i>Yes, restoration and re-vegetation required.</i>
<i>Removal of existing vegetation or planting new vegetation</i>	<i>No, except invasive plants and hazard trees per CDC 32.040(A)(2) or per CDC 32.100.</i>	<i>Yes, if it is replaced by native vegetation. Exemption CDC 32.040(A)(3) applies.</i>
<i>Realigning water resources</i>	<i>Yes, after “alternate review” process</i>	<i>Not applicable</i>

<sup>1</sup> *Development to within 50 feet of the water resource applies to Table 32-2 WRA types (A), (C), (D), and (H). Development behind top of slope (ravine) applies to WRA type (B).*

**Staff Finding 4:** The application is for the construction of a new single-family home on the subject property. A property owner may apply for a reduction in the width of the Water Resource Area (WRA), as shown in table 32-1, with the appropriate Geotechnical study. The applicant has provided the Geotechnical study to reduce the WRA buffer (See Exhibit PD-1). The criteria are met.

**32.050 APPLICATION**

- A. An application requesting approval for a use or activity regulated by this chapter shall be initiated by the property owner, or the owner’s authorized agent, and shall include an application form and the appropriate deposit or fee as indicated on the master fee schedule.*
- B. A pre-application conference shall be a prerequisite to the filing of the application.*

**Staff Finding 5:** The applicant has provided the appropriate payment. A pre-application conference PA-23-12 was held on July 22, 2023. The criteria are met.

- C. The applicant shall submit maps and diagrams at 11 by 17 inches and a written narrative addressing the approval criteria and requirements of this chapter, and any additional copies required by the Planning Director.*
- D. Where review of soil maps, Department of Geology and Mineral Industries (DOGAMI) maps, or on-site inspection by the City Engineer reveals evidence of slope failures or that WRA slopes are potentially unstable or prone to failure, geotechnical studies may be required to demonstrate that the proposed development will not cause, or contribute to, slope failure or increased erosion or sedimentation in the WRA or adversely impact surface or modify*

*groundwater flow or hydrologic conditions. These geotechnical studies shall include all necessary measures to avoid or correct the potential hazard.*

**Staff Finding 6: The applicant has provided all required maps and diagrams. A geotechnical study that includes all necessary measures and addresses all Community Development Code requirements set forth in chapter 32 of the CDC (See Exhibit PD-1). The criteria are met.**

*E. Applications proposing that streets or utilities cross water resources, or any other development that modifies the water resource, shall present evidence in the form of adopted utility master plans or transportation master plans, or findings from a registered Oregon civil engineer, certified engineering geologist or similarly qualified professional to demonstrate that the development or improvements are consistent with accepted engineering practices.*

*F. Site plan. The applicant shall submit a site plan which contains the following information, as applicable:*

- 1. The name, address, and telephone number of the applicant, the scale (lineal) of the plan, and a north arrow.*
- 2. Property lines, rights-of-way, easements, etc.*
- 3. A storm detention and treatment plan and narrative statement pursuant to CDC 92.010(E).*
- 4. Tables and maps identifying acreage, location and type of development constraints due to site characteristics such as slope, drainage and geologic hazards. For Type I, II, and III lands (refer to definitions in Chapter 02 CDC), the applicant must provide a geologic report, with text, figures and attachments as needed to meet the industry standard of practice, prepared by a certified engineering geologist and/or a geotechnical professional engineer, that includes:
  - a. Site characteristics, geologic descriptions and a summary of the site investigation conducted;*
  - b. Assessment of engineering geological conditions and factors;*
  - c. Review of the City of West Linn's Natural Hazard Mitigation Plan and applicability to the site; and*
  - d. Conclusions and recommendations focused on geologic constraints for the proposed land use or development activity, limitations and potential risks of development, recommendations for mitigation approaches and additional work needed at future development stages including further testing and monitoring.**
- 5. Boundaries of the WRA, specifically delineating the water resource, and any riparian corridor boundary. If the proposal includes development of a wetland, a wetlands delineation prepared by a professional wetland specialist will be required. The wetland delineation may be required to be accepted or waived through the Department of State Lands (DSL) delineation review process.*
- 6. Location of existing and proposed development, including all existing and proposed structures, accessory structures, any areas of fill or excavation, water resource crossings, alterations to vegetation, or other alterations to the site's natural state.*
- 7. Identify the location and square footage of previously disturbed areas, areas that are to be temporarily disturbed, and area to be permanently disturbed or developed.*
- 8. When an application proposes development within the WRA, an inventory of vegetation within the WRA, sufficient to categorize the existing condition of the WRA, including:*

- a. *The type and general quality of ground cover, including the identification of dominant species and any occurrence of non-native, invasive species;*
- b. *Square footage of ground cover; and*
- c. *Square footage of tree canopy as measured either through aerial photographs or by determining the tree drip lines. Where only a portion of a WRA is to be disturbed, the tree inventory need only apply to the impacted area. The remaining treed area shall be depicted by outlining the canopy cover.*
9. *Locations of all significant trees as defined by the City Arborist.*
10. *Identify adopted transportation, utility and other plan documents applicable to this proposal.*
11. *For cases processed under CDC 32.110 (hardship), provide the maximum disturbed area (MDA) calculations.*

**Staff Finding 7: The applicant has provided all required maps and diagrams. And a geotechnical study that includes all necessary measures and addresses all Community Development Code requirements set forth in chapter 32 of the CDC (See Exhibit PD-1). The criteria are met.**

G. *Construction management plan.* *The applicant shall submit a construction management plan which includes the following:*

1. *The location of proposed TDAs (site ingress/egress for construction equipment, areas for storage of material, construction activity areas, grading and trenching, etc.) that will subsequently be restored to original grade and replanted with native vegetation, shall be identified, mapped and enclosed with fencing per subsection (G)(3) of this section.*
2. *Appropriate erosion control measures consistent with Clackamas County Erosion Prevention and Sediment Control Planning and Design Manual, rev. 2008, and a tentative schedule of work.*
3. *The WRA shall be protected, prior to construction, with an anchored chain link fence (or equivalent approved by the City) at its perimeter that shall remain undisturbed, except as specifically authorized by the approval authority. Additional fencing to delineate approved TDAs may be required. Fencing shall be mapped and identified in the construction management plan and maintained until construction is complete.*

**Staff Finding 8: A construction management plan (CMP) has been provided as part of the application (See PD-1, Page 10). The CMP contains erosion control measures which includes silt fencing and chain link cyclone fencing around the wetlands on-site. The CMP will be confirmed during the building permit process to ensure all appropriate measures are taken during the construction process including but not limited to proper erosion control measures. The criteria are met.**

- H. *Mitigation plan prepared in accordance with the requirements in CDC 32.090.*
- I. *Re-vegetation plan prepared in accordance with the requirements in CDC 32.100.*
- J. *The Planning Director may modify the submittal requirements per CDC 99.035.*
- K. *The following additional requirements apply to applications being submitted under the alternative review process pursuant to CDC 32.070 and 32.080.*

1. *Identify the affected WRA and describe the functions it performs (see Table 32-4).*
2. *Provide a scaled map that delineates the proposed WRA boundaries determined to be sufficient to sustain the functions occurring at the site and a narrative that justifies the proposal, consistent with CDC 32.080.*
3. *Identify the recommended WRA boundary at the site with colored tape, survey markers or other easily identified means for field inspection by staff.*
4. *Consultant required for alternate review process.*
  - a. *The narrative and analysis required by CDC 32.070 and 32.080 shall be prepared and signed by a qualified natural resource professional, such as a wildlife biologist, botanist, or hydrologist. The Planning Director shall determine the scope of work and specific products required from the consultant. The Planning Director may require a mitigation plan pursuant to CDC 32.090 and/or a re-vegetation plan pursuant to CDC 32.100.*
  - b. *The Planning Director may waive the consultant requirement for simple or minor projects if they determine that it is not necessary in order to satisfy the requirements of this chapter.*

**Staff Finding 9: The application contains a mitigation plan and scaled maps. The WRA boundary will be appropriately identified and taped during the construction process. A narrative was provided by a qualified natural resource professional, Kim Cartwright of Schott and Associates. The criteria are met.**

#### *32.060 APPROVAL CRITERIA (STANDARD PROCESS)*

*No application for development on property containing a WRA shall be approved unless the approval authority finds that the proposed development is consistent with the following approval criteria, or can satisfy the criteria by conditions of approval:*

##### *A. WRA protection/minimizing impacts.*

1. *Development shall be conducted in a manner that will avoid or, if avoidance is not possible, minimize adverse impact on WRAs.*
2. *Mitigation and re-vegetation of disturbed WRAs shall be completed per CDC 32.090 and 32.100, respectively.*

##### *B. Storm water and storm water facilities.*

1. *Proposed developments shall be designed to maintain the existing WRAs and utilize them as the primary method of storm water conveyance through the project site unless:*
  - a. *The surface water management plan calls for alternate configurations (culverts, piping, etc.); or*
  - b. *Under CDC 32.070, the applicant demonstrates that the relocation of the water resource will not adversely impact the function of the WRA including, but not limited to, circumstances where the WRA is poorly defined or not clearly channelized.*

*Re-vegetation, enhancement and/or mitigation of the re-aligned water resource shall be required as applicable.*

2. *Public and private storm water detention, storm water treatment facilities and storm water outfall or energy dissipaters (e.g., rip rap) may encroach into the WRA if:*
  - a. *Accepted engineering practice requires it;*
  - b. *Encroachment on significant trees shall be avoided when possible, and any tree loss shall be consistent with the City's Tree Technical Manual and mitigated per CDC 32.090;*

- c. *There shall be no direct outfall into the water resource, and any resulting outfall shall not have an erosive effect on the WRA or diminish the stability of slopes; and*
- d. *There are no reasonable alternatives available.*

*A geotechnical report may be required to make the determination regarding slope stability.*

*3. Roadside storm water conveyance swales and ditches may be extended within rights-of-way located in a WRA. When possible, they shall be located along the side of the road furthest from the water resource. If the conveyance facility must be located along the side of the road closest to the water resource, it shall be located as close to the road/sidewalk as possible and include habitat friendly design features (treatment train, rain gardens, etc.).*

*4. Storm water detention and/or treatment facilities in the WRA shall be designed without permanent perimeter fencing and shall be landscaped with native vegetation.*

*5. Access to public storm water detention and/or treatment facilities shall be provided for maintenance purposes. Maintenance driveways shall be constructed to minimum width and use water permeable paving materials. Significant trees, including roots, shall not be disturbed to the degree possible. The encroachment and any tree loss shall be mitigated per CDC 32.090. There shall also be no adverse impacts upon the hydrologic conditions of the site.*

*6. Storm detention and treatment and geologic hazards. Per the submittals required by CDC 32.050(F)(3) and 92.010(E), all proposed storm detention and treatment facilities must comply with the standards for the improvement of public and private drainage systems located in the West Linn Public Works Design Standards, there will be no adverse off-site impacts caused by the development (including impacts from increased intensity of runoff downstream or constrictions causing ponding upstream), and the applicant must provide sufficient factual data to support the conclusions of the submitted plan.*

*C. Repealed by Ord. 1647.*

*D. WRA width. Except for the exemptions in CDC 32.040, applications that are using the alternate review process of CDC 32.070, or as authorized by the approval authority consistent with the provisions of this chapter, all development is prohibited in the WRA as established in Table 32-2 below:*

**Table 32-2. Required Width of WRA**

<b>Protected WRA Resource (see Chapter 2 CDC, Definitions)</b>	<b>Slope Adjacent to Protected Water Resource<sup>1, 3</sup></b>	<b>Starting Point for Measurements from Water Resource<sup>1, 3</sup></b>	<b>Width of WRA on Each Side of the Water Resource</b>
A. Water Resource	0% - 25%	OHW or delineated edge of wetland	65 feet
B. Water Resource (Ravine)	over 25% to a distinct top of slope <sup>2</sup>	OHW or delineated edge of wetland	From water resource to top of slope <sup>2</sup> (30-foot minimum), plus an additional 50 feet <sup>4</sup>
C. Water Resource	Over 25% for more than 30 feet, and no	OHW or delineated edge of wetland	200 feet



<b>Protected WRA Resource (see Chapter 2 CDC, Definitions)</b>	<b>Slope Adjacent to Protected Water Resource<sup>1, 3</sup></b>	<b>Starting Point for Measurements from Water Resource<sup>1, 3</sup></b>	<b>Width of WRA on Each Side of the Water Resource</b>
	<i>distinct top of slope for at least 150 feet</i>		
<i>D. Riparian Corridor</i>	<i>Any</i>	<i>OHW</i>	<i>100 feet</i>
<i>E. Formerly Closed Drainage Channel Reopened</i>	<i>Any</i>	<i>OHW</i>	<i>15 feet</i>
<i>F. Ephemeral Stream</i>	<i>Any</i>	<i>Stream thread or centerline</i>	<i>15 feet with treatment or vegetation (see CDC 32.050(G)(1))</i>
<i>G. Fish Bearing Streams per Oregon Department of Fish and Wildlife (ODFW) or 2003-2004 Survey</i>	<i>Applies to all that stream section where fish were inventoried and upstream to the first known barrier to fish passage.</i>	<i>OHW or delineated edge of wetland</i>	<i>100 feet when no greater than 25% slope. See B or C above for steeper slopes</i>
<i>H. Re-aligned Water Resource</i>	<i>See A, B, C, D, F, or G, above</i>	<i>OHW or delineated edge of wetland</i>	<i>See A, B, C, D, F, or G, above</i>

<sup>1</sup> The slope is the average slope in the first 50 feet as measured from bankfull stage or OHW.

<sup>2</sup> Where the protected water resource is confined by a ravine or gully, the top of slope is the location (30-foot minimum) where the slope breaks to less than 15 percent for at least 50 feet.

<sup>3</sup> At least three slope measurements along the water resource, at no more than 100-foot increments, shall be made for each property for which development is proposed. Depending upon topography, the width of the protected corridor may vary.

<sup>4</sup> The 50-foot distance may be reduced to 25 feet if a geotechnical study by a licensed engineer or similar accredited professional demonstrates that the slope is stable and not prone to erosion.

**Table 32-3**

### Determining the starting point for the measurement of the WRA




Figure 32-2

**Determining the appropriate slope and measuring the WRA width:**




Figure 32-3




Figure 32-4

**WELL DEFINED RAVINE. SLOPES OVER 25%.  
DISTINCT OR IDENTIFIABLE TOP OF SLOPE.**




Figure 32-5

**STEEP DRAINAGEWAY OVER 25% SLOPE WITH NO DISTINCT TOP OF SLOPE IN THE FIRST 150 FEET FROM THE WATER RESOURCE**





Figure 32-6



E. Per the submittals required by CDC 32.050(F)(4), the applicant must demonstrate that the proposed methods of rendering known or potential hazard sites safe for development, including proposed geotechnical remediation, are feasible and adequate to prevent landslides or other damage to property and safety. The review authority may impose conditions, including limits on type or intensity of land use, which it determines are necessary to mitigate known risks of landslides or property damage.

F. Roads, driveways and utilities.

1. New roads, driveways, or utilities shall avoid WRAs unless the applicant demonstrates that no other practical alternative exists. In that case, road design and construction techniques shall minimize impacts and disturbance to the WRA by the following methods:

a. New roads and utilities crossing riparian habitat areas or streams shall be aligned as close to perpendicular to the channel as possible.

b. Roads and driveways traversing WRAs shall be of the minimum width possible to comply with applicable road standards and protect public safety. The footprint of grading and site clearing to accommodate the road shall be minimized.

c. Road and utility crossings shall avoid, where possible:

- 1) Salmonid spawning or rearing areas;
- 2) Stands of mature conifer trees in riparian areas;
- 3) Highly erodible soils;
- 4) Landslide prone areas;
- 5) Damage to, and fragmentation of, habitat; and
- 6) Wetlands identified on the WRA Map.

2. Crossing of fish bearing streams and riparian corridors shall use bridges or arch-bottomless culverts or the equivalent that provides comparable fish protection, to allow passage of wildlife and fish and to retain the natural stream bed.

3. New utilities spanning fish bearing stream sections, riparian corridors, and wetlands shall be located on existing roads/bridges, elevated walkways, conduit, or other existing structures or installed underground via tunneling or boring at a depth that avoids tree roots and does not alter the hydrology sustaining the water resource, unless the applicant demonstrates that it is

*not physically possible or it is cost prohibitive. Bore pits associated with the crossings shall be restored upon project completion. Dry, intermittent streams may be crossed with open cuts during a time period approved by the City and any agency with jurisdiction.*

*4. No fill or excavation is allowed within the ordinary high water mark of a water resource, unless all necessary permits are obtained from the City, U.S. Army Corps of Engineers and Oregon Department of State Lands (DSL).*

*5. Crossings of fish bearing streams shall be aligned, whenever possible, to serve multiple properties and be designed to accommodate conduit for utility lines. The applicant shall, to the extent legally permissible, work with the City to provide for a street layout and crossing location that will minimize the need for additional stream crossings in the future to serve surrounding properties.*

*G. Passive recreation. Low impact or passive outdoor recreation facilities for public use including, but not limited to, multi-use paths and trails, not exempted per CDC 32.040(B)(2), viewing platforms, historical or natural interpretive markers, and benches in the WRA, are subject to the following standards:*

*1. Trails shall be constructed using non-hazardous, water permeable materials with a maximum width of four feet or the recommended width under the applicable American Association of State Highway and Transportation Officials (AASHTO) standards for the expected type and use, whichever is greater.*

*2. Paved trails are limited to the area within 20 feet of the outer boundary of the WRA, and such trails must comply with the storm water provisions of this chapter.*

*3. All trails in the WRA shall be set back from the water resource at least 30 feet except at stream crossing points or at points where the topography forces the trail closer to the water resource.*

*4. Trails shall be designed to minimize disturbance to existing vegetation, work with natural contours, avoid the fall line on slopes where possible, avoid areas with evidence of slope failure and ensure that trail runoff does not create channels in the WRA.*

*5. Foot bridge crossings shall be kept to a minimum. When the stream bank adjacent to the foot bridge is accessible (e.g., due to limited vegetation or topography), where possible, fences or railings shall be installed from the foot bridge and extend 15 feet beyond the terminus of the foot bridge to discourage trail users and pets from accessing the stream bank, disturbing wildlife and habitat areas, and causing vegetation loss, stream bank erosion and stream turbidity. Bridges shall not be made of continuous impervious materials or be treated with toxic substances that could leach into the WRA.*

*6. Interpretive facilities (including viewpoints) shall be at least 10 feet from the top of the water resource's bankfull flow/OHW or delineated wetland edge and constructed with a fence between users and the resource. Interpretive signs may be installed on footbridges.*

*H. Daylighting Piped Streams.*

*1. As part of any application, covered or piped stream sections shown on the WRA Map are encouraged to be "daylighted" or opened. Once it is daylighted, the WRA will be limited to 15 feet on either side of the stream. Within that WRA, water quality measures are required which may include a storm water treatment system (e.g., vegetated bioswales), continuous vegetative ground cover (e.g., native grasses) at least 15 feet in width that provides year round efficacy, or a combination thereof.*

2. *The re-opened stream does not have to align with the original piped route but may take a different route on the subject property so long as it makes the appropriate upstream and downstream connections and meet the standards of subsections (H)(3) and (4) of this section.*
3. *A re-aligned stream must not create WRAs on adjacent properties not owned by the applicant unless the applicant provides a notarized letter signed by the adjacent property owner(s) stating that the encroachment of the WRA is permitted.*
4. *The evaluation of proposed alignment and design of the reopened stream shall consider the following factors:*
  - a. *The ability of the reopened stream to safely carry storm drainage through the area without causing significant erosion.*
  - b. *Continuity with natural contours on adjacent properties, slope on site and drainage patterns.*
  - c. *Continuity of adjacent vegetation and habitat values.*
  - d. *The ability of the existing and proposed vegetation to filter sediment and pollutants and enhance water quality.*
  - e. *Provision of water temperature conducive to fish habitat.*
5. *Any upstream or downstream WRAs or riparian corridors shall not apply to, or overlap, the daylighted stream channel.*
6. *When a stream is daylighted the applicant shall prepare and record a legal document describing the reduced WRA required by subsections (H)(1) and (5) of this section. The document will be signed by a representative of the City and recorded at the applicant's expense to better ensure long term recognition of the reduced WRA and reduced restrictions for the daylighted stream section.*
  1. *The following habitat friendly development practices shall be incorporated into the design of any improvements or projects in the WRA to the degree possible:*
    1. *Restore disturbed soils to original or higher level of porosity to regain infiltration and storm water storage capacity.*
    2. *Apply a treatment train or series of storm water treatment measures to provide multiple opportunities for storm water treatment and reduce the possibility of system failure.*
    3. *Incorporate storm water management in road rights-of-way.*
    4. *Landscape with rain gardens to provide on-lot detention, filtering of rainwater, and groundwater recharge.*
    5. *Use multi-functional open drainage systems in lieu of conventional curb-and-gutter systems.*
    6. *Use green roofs for runoff reduction, energy savings, improved air quality, and enhanced aesthetics.*
    7. *Retain rooftop runoff in a rain barrel for later on-lot use in lawn and garden watering.*
    8. *Disconnect downspouts from roofs and direct the flow to vegetated infiltration/filtration areas such as rain gardens.*
    9. *Use pervious paving materials for driveways, parking lots, sidewalks, patios, and walkways.*
    10. *Reduce sidewalk width to a minimum four feet. Grade the sidewalk so it drains to the front yard of a residential lot or retention area instead of towards the street.*
    11. *Use shared driveways.*
    12. *Reduce width of residential streets and driveways, especially at WRA crossings.*
    13. *Reduce street length, primarily in residential areas, by encouraging clustering.*

14. *Reduce cul-de-sac radii and use pervious and/or vegetated islands in center to minimize impervious surfaces.*

15. *Use previously developed areas (PDAs) when given an option of developing PDA versus non-PDA land.*

16. *Minimize the building, hardscape and disturbance footprint.*

17. *Consider multi-story construction over a big*

**Staff Finding 10: The applicant has chosen to utilize the alternative review process (see staff finding 11). Staff adopts the applicant findings.**

***“Proposed development avoids impacts to the 65-foot WRA to the extent practicable. The access road widening is regarded as a necessity to allow appropriate emergency vehicle access and turnaround, with the associated retaining walls required to support the steep embankment which is a result of the constraining site topography. The home was placed as far west as site topography allowed (see geotechnical report included as Appendix D). Where the home does encroach into the WRA, its height above the surrounding grade will allow vegetation growth, preventing erosion or sedimentation of areas downslope. The applicant proposes to restore this area (806 sq. ft) with native forest understory groundcover plants that are well-adapted to low- light conditions. A stormwater facility will also be constructed to retain and treat stormwater runoff from the proposed project (currently, no stormwater facility is present) and prevent the discharge of untreated stormwater into the wetland. The applicant proposes mitigation of the WRA at a ratio of 1:1.4 between the wetland boundaries and the proposed project to provide the best protection of the wetland (3,022 sq. ft. of mitigation to 2,216 sq. ft. of impact). The mitigation plan meets the standards of CDC 32.090.”***

**The criteria are met.**

### **32.070 ALTERNATE REVIEW PROCESS**

*This section establishes a review and approval process that applicants can use when there is reason to believe that the width of the WRA prescribed under the standard process (CDC 32.060(D)) is larger than necessary to protect the functions of the water resource at a particular site. It allows a qualified professional to determine what water resources and associated functions (see Table 32-4 below) exist at a site and the WRA width that is needed to maintain those functions.*

**Staff Finding 11: The applicant has chosen to utilize the alternative review process and submitted supporting information prepared by Kim Cartwright of Schott & Associates, a qualified professional. As demonstrated in the findings above and below, the requirements of the alternative review process are met.**

### **32.080 APPROVAL CRITERIA (ALTERNATE REVIEW PROCESS)**

*Applications reviewed under the alternate review process shall meet the following approval criteria:*

A. *The proposed WRA shall be, at minimum, qualitatively equal, in terms of maintaining the level of functions allowed by the WRA standards of CDC 32.060(D).*



**Staff Finding 12: Staff adopts applicant findings.**

***“As described further in this report (Table 1), the existing WRA, while very wide (100-150 feet from the delineated boundary of the water resources in some areas due to the steep grade of adjacent slopes), is low functioning, serving as residential yard dominated by mown nonnative turfgrass and weedy forbs along with invasive Himalayan blackberry and Canada thistle. It also contains existing development, including an access road and portions of the parking area and home which provide no protective function to the water resources, and may even adversely impact the function of the water resources by contributing untreated stormwater runoff and pollutants. The applicant proposes to reduce the WRA to 65 ft. in width and remove the existing development (access road, parking area, and residence) from it, for a proposed WRA buffer of 0.25-acre. A 65-foot width was chosen as an appropriate width because it corresponds with the base WRA width for a wetland in the City of West Linn. Other local metropolitan Portland districts, including Clean Water Service, City of Happy Valley, and Clackamas County regulate a base wetland buffer width of 50 feet, and while the basis for these different base widths is unknown, the applicant chooses to comply with the minimum City of West Linn standard. The slopes adjacent to the wetland have been demonstrated as stable according to a geotechnical study (Appendix D) and a WRA that extends 25 ft. beyond the top of slope, covering 0.43 acre of the 0.70-acre site (61%), in its current degraded condition, is unnecessary to protect the water resource. The proposed project will result in 2,216 sq. ft. of encroachment into the proposed 65-foot WRA, including the access road widening and roof/deck overhang along the western margin of the WRA. A stormwater facility is proposed to retain and treat stormwater runoff from the development and prevent discharge of untreated runoff into the wetland. The applicant proposes to mitigate for 2,216 sq. ft. of encroachments into the 65-foot WRA via enhancement of 2,216 sq. ft. within the remaining 0.20-acre WRA currently in degraded condition. The applicant also proposes to restore the 806 sq. ft. of roof/deck overhang that encroaches into the 65-foot WRA with native forest understory groundcover plants. The mitigation plan for the WRA will improve hydrological, water quality, and habitat functions including stream flow moderation, sediment and pollution control, providing organic material sources, and wildlife habitat. Enhancing the WRA will also provide protection of the wetlands from the proposed development. Existing native vegetation along the northern site boundary (red osier dogwood thicket) will be preserved and maintained as is; the remaining WRA will be landscaped and maintained according to Section 32.040 (A). The proposed WRA shall be, at minimum, qualitatively equal in terms of maintaining the level of functions allowed by the WRA standards of CDC 32.060(D) and is anticipated to be superior with the addition of native plantings and appropriate stormwater management and treatment.”***

**The criteria are met.**

***B. If a WRA is already significantly degraded (e.g., native forest and ground cover have been removed or the site dominated by invasive plants, debris, or development), the approval authority may allow a reduced WRA in exchange for mitigation, if:***

***1. The proposed reduction in WRA width, coupled with the proposed mitigation, would result in better performance of functions than the standard WRA without such mitigation. The***

approval authority shall make this determination based on the applicant’s proposed mitigation plan and a comparative analysis of ecological functions under existing and enhanced conditions (see Table 32-4).

**Staff Finding 13: Staff adopts applicant findings.**

***“As described in this report and demonstrated below in Table 1, the existing WRA is degraded, dominated by non-native and invasive species, including turfgrasses, Himalayan blackberry and Canada thistle. Stormwater runoff from steep slopes and development above is unmitigated. The proposed WRA will be enhanced by of removal of invasive species and planting of native trees, shrubs, and groundcover along the wetland boundaries to significantly improve ecological functions. The proposed WRA will result in higher functions than the larger WRA without mitigation. Additionally, 806 sq. ft. of area beneath the proposed home and deck overhang, while technically considered an encroachment according to Table 32-1 of the CDC, will be restored with native plantings and should provide further benefit to the WRA. The height of the proposed overhang above the surrounding grade will still allow sunlight and rainfall to access the area and thus can be planted with species adapted to lower-light conditions, such as those which grow under a forest canopy. Table 1 below presents existing and enhanced WRA ecological functions per Table 32-4.”***

The criteria are met.

Table 1. Ecological Functions Comparison per Table 32-4

Ecological Functions	WRA existing conditions	WRA enhanced conditions
<i>Stream flow moderation and/or water storage</i>	<i>No dense or woody vegetation or fallen trees are present to slow velocity of stormwater. Both wetlands are moderately sloped toward the tributary to Barlow Creek north of the site, and Wetland 1 is piped into a ditch which routes surface flows directly into the</i>	<i>Planting of native woody vegetation and groundcover will slow stormwater runoff and increase infiltration and sequestration of pollutants, protecting the wetlands and moderating streamflow for the Barlow Creek tributary located</i>
	<i>tributary. Together with the very steep slopes above the wetlands, stormwater is quickly routed through the wetlands and into the tributary below with little opportunity for retention or infiltration.</i>	<i>immediately downslope of the site.</i>

<i>Sediment or pollution control</i>	<i>With steep slopes and only mown turfgrasses and weedy forbs as vegetation cover, the WRA is unable to sequester sediment or pollutants from reaching downstream.</i>	<i>Increased vegetation, including woody species, will increase the WRA's capacity and opportunity to filter nutrients and retain sediments.</i>
<i>Bank stabilization</i>	<i>Low stream flow moderation and/or water storage function (see above) can contribute to bank erosion and channel downcutting downstream.</i>	<i>Increased vegetation cover will moderate velocity of stormwater, increase retention and contribute to downstream bank stabilization.</i>
<i>Large wood recruitment for a fish bearing section of stream</i>	<i>The tributary is not a fish bearing stream, though wood recruitment potential would be improved.</i>	<i>No change.</i>
<i>Organic material sources</i>	<i>The mown turfgrass vegetation cover provides little organic matter for the wetland/drainage system.</i>	<i>Planting diverse native vegetation community including woody species will increase organic material sources throughout the WRA.</i>
<i>Shade (water temperature moderation) and microclimate</i>	<i>The water resource is not currently shaded. The WRA is vegetated by mown turfgrasses</i>	<i>Tree and shrub planting will provide shade sources adjacent to the wetland, cooling surface waters that drain into the tributary below.</i>
<i>Stream flow that sustains in-stream and adjacent habitats</i>	<i>The wetland is seasonally inundated/saturated</i>	<i>Seasonal saturation/inundation will be maintained. No hydrological impacts anticipated.</i>
<i>Other terrestrial habitat</i>	<i>Forested areas within 100-300 feet of the water resource are not contiguous. Areas immediately adjacent to the water resource have only nonnative and invasive herbaceous cover.</i>	<i>Mitigation of the WRA will augment existing forested natural area within 100-300 feet of the water resource (Sahallie Illahee Park).</i>

2. The mitigation project shall include all of the following components as applicable. It may also include other forms of enhancement (mitigation) deemed appropriate by the approval authority.

a. Removal of invasive vegetation.

- b. *Planting native, non-invasive plants (at minimum, consistent with CDC 32.100) that provide improved filtration of sediment, excess nutrients, and pollutants. The amount of enhancement (mitigation) shall meet or exceed the standards of CDC 32.090(C).*
- c. *Providing permanent improvements to the site hydrology that would improve water resource functions.*
- d. *Substantial improvements to the aquatic and/or terrestrial habitat of the WRA.*

**Staff Finding 14: Staff adopts applicant findings.**

***“The mitigation plan shall consist of removal of invasive species and planting of a diverse assemblage of native trees, shrubs, and groundcover species to improve hydrological and water quality functions including slowing runoff and filtration of sediment, excess nutrients, and pollutants. Terrestrial habitat of the onsite water resources will be improved by providing cover, nesting or burrowing sites, and food availability and type. Proposed total mitigation area, which includes both enhancement of existing degraded WRA and post-construction restoration of disturbed WRA is 3,022 sq. ft. which exceeds the standards of CDC 32.090(C).”***  
**The criteria are met.**

- C. *Identify and discuss site design and methods of development as they relate to WRA functions.*
- D. *Address the approval criteria of CDC 32.060, with the exception of CDC 32.060(D).*

*Table 32-4 Ecological Functions of WRA*

<i>Ecological Function</i>	<i>Landscape Features Potentially Providing the Function</i>
<i>Stream flow moderation and/or water storage</i>	<i>A wetland or other water body with a hydrologic connection to a stream or flood area, the presence of fallen trees and density of vegetation in the WRA that slows the flow of storm water and increases its ability to retain sediment and infiltrate storm water, and the porosity of the WRA’s surface to enable it to infiltrate storm water.</i>
<i>Sediment or pollution control</i>	<i>Vegetation within 100 feet of a WRA on gentle slopes and up to 200 feet of a WRA if the slope is greater than 25%. The presence of fallen trees and other material that slows the flow of water and increase the ability to retain sediment, absorb pollutants and infiltrate storm water; the composition and density of vegetation; slope; and soils.</i>
<i>Bank stabilization</i>	<i>Root masses, existing large rocks or anchored large wood along the stream bank.</i>
<i>Large wood recruitment for a fish bearing section of stream</i>	<i>Forest canopy within 50 to 150 feet of a fish bearing stream.</i>

<i>Ecological Function</i>	<i>Landscape Features Potentially Providing the Function</i>
<i>Organic material sources</i>	<i>Forest canopy or woody vegetation within 100 feet of a water resource; or within a flood area.</i>
<i>Shade (water temperature moderation) and microclimate</i>	<i>Forest canopy or woody vegetation within 100 feet of the water resource. Roughly 300 feet of continuous canopy for microclimate.</i>
<i>Stream flow that sustains in-stream and adjacent habitats</i>	<i>Seasonal or perennial flow.</i>
<i>Other terrestrial habitat</i>	<i>Forest canopy natural vegetation contiguous to and within 100 to 300 feet of the water resource.</i>

**Staff Finding 15: Staff adopts applicant findings.**

***“Site design utilized two-story development and incorporated the existing development footprint to maximize the available development footprint while avoiding steep, hazardous slopes to the west and minimizing impacts to the proposed reduced WRA. Impacts to the reduced WRA will include widening of the access driveway from 9-12 ft. wide to 15 ft. wide to allow emergency vehicle as well as pedestrian access (personnel will be able to walk around the vehicle on the roadway which is approximately 5-6 ft above grade where it crosses the wetland swales) and turnaround, retaining walls to support the driveway embankment and prevent slope failure, and the roof and deck overhang. The overhang areas are well above the surrounding grade (the deck will be at a height of 9.5-14 ft. above the surrounding grade, while the roof overhang will be 21- 26 ft. above grade) which will allow rain and sunlight to penetrate and support vegetation growth. This area will be restored with native forest understory plantings following construction. The WRA mitigation plan will protect the water resource from the development as well as improve hydrological, water quality, and wildlife habitat functions to both the onsite water resource and the water resource immediately downslope (tributary to Barlow Creek). The existing WRA is degraded, vegetated primarily with mown, nonnative turfgrasses and invasive species.”***

The criteria are met.

**32.090 MITIGATION PLAN**

**A.** A mitigation plan shall only be required if development is proposed within a WRA (including development of a PDA). (Exempted activities of CDC 32.040 do not require mitigation unless specifically stated. Temporarily disturbed areas, including TDAs associated with exempted activities, do not require mitigation, just grade and soil restoration and re-vegetation.) The mitigation plan shall satisfy all applicable provisions of CDC 32.100, Re-Vegetation Plan Requirements.

**B.** Mitigation shall take place in the following locations, according to the following priorities (subsections (B)(1) through (4) of this section):

1. On-site mitigation by restoring, creating or enhancing WRAs.

2. *Off-site mitigation in the same sub-watershed will be allowed, but only if the applicant has demonstrated that:*
  - a. *It is not practicable to complete mitigation on-site, for example, there is not enough area on-site; and*
  - b. *The mitigation will provide equal or superior ecological function and value.*
3. *Off-site mitigation outside the sub-watershed will be allowed, but only if the applicant has demonstrated that:*
  - a. *It is not practicable to complete mitigation on-site, for example, there is not enough area on-site; and*
  - b. *The mitigation will provide equal or superior ecological function and value.*
4. *Purchasing mitigation credits through DSL or other acceptable mitigation bank.*

**Staff Finding 16: The applicant has proposed all mitigation to be on-site. A mitigation plan has been submitted as part of the application (See PD-1, Figure 3). The criteria are met.**

C. *Amount of mitigation.*

1. *The amount of mitigation shall be based on the square footage of the permanent disturbance area by the application. For every one square foot of non-PDA disturbed area, on-site mitigation shall require one square foot of WRA to be created, enhanced or restored.*
2. *For every one square foot of PDA that is disturbed, on-site mitigation shall require one half a square foot of WRA vegetation to be created, enhanced or restored.*
3. *For any off-site mitigation, including the use of DSL mitigation credits, the requirement shall be for every one square foot of WRA that is disturbed, two square feet of WRA shall be created, enhanced or restored. The DSL mitigation credits program or mitigation bank shall require a legitimate bid on the cost of on-site mitigation multiplied by two to arrive at the appropriate dollar amount.*

**Staff Finding 17: Staff adopts applicant findings.**

***“2,216 sq. ft. of permanent impacts to the 65-foot WRA are proposed. The applicant proposes enhancement mitigation of 2,216 sq. ft. of WRA adjacent to the wetland boundaries, as well as 806 sq. ft. of restoration mitigation beneath the encroaching roof/deck overhang for a total of 3,022 sq. ft. of mitigation to protect the water resource and downstream functions.”***  
**The criteria are met.**

D. *The Planning Director may limit or define the scope of the mitigation plan and submittal requirements commensurate with the scale of the disturbance relative to the resource and pursuant to the authority of Chapter 99 CDC. The Planning Director may determine that a consultant is required to complete all or a part of the mitigation plan requirements.*

E. *A mitigation plan shall contain the following information:*

1. *A list of all responsible parties including, but not limited to, the owner, applicant, contractor, or other persons responsible for work on the development site.*
2. *A map showing where the specific adverse impacts will occur and where the mitigation activities will occur.*

3. *A re-vegetation plan for the area(s) to be mitigated that meets the standards of CDC 32.100.*
4. *An implementation schedule, including timeline for construction, mitigation, mitigation maintenance, monitoring, and reporting. All in-stream work in fish bearing streams shall be done in accordance with the Oregon Department of Fish and Wildlife.*
5. *Assurances shall be established to rectify any mitigation actions that are not successful within the first three years. This may include bonding or other surety.*

**Staff Finding 18: Staff adopts applicant findings.**

***“The applicant and owner are: Kevin Janssen 614 SE 52nd Avenue Portland, OR 97215. The applicant will provide contractor/designer and other responsible party contact information as it becomes available. Appendix B of the applicant submittal illustrates the proposed impacts to the 65-foot WRA. Figure 3 illustrates the proposed mitigation planting areas.***

***Mitigation shall occur after all approvals are met and in accordance with planting requirements outlined in 32.100. As per City of West Linn WRA protection requirements, 80% success is required for replanted areas. The mitigation planting site will be monitored and maintained for three years. If, after each year monitoring period, 80% survival has not been met, dead plants will be replaced up to the 80% success required. Monitoring reports shall be provided to document these activities. No work will be conducted in fish bearing streams and the in-stream work window is not applicable.***

***The applicant can provide any necessary assurance based on coordination with City staff. We would propose that any bonding or surety be deferred based on the results of the ongoing monitoring, maintenance, and reporting requirements.”***

**The criteria are met.**

**32.100 RE-VEGETATION PLAN REQUIREMENTS**

**A. *In order to achieve the goal of re-establishing forested canopy, native shrub and ground cover and to meet the mitigation requirements of CDC 32.090 and vegetative enhancement of CDC 32.080, tree and vegetation plantings are required according to the following standards:***

**1. *All trees, shrubs and ground cover to be planted must be native plants selected from the Portland Plant List.***

**2. *Plant size.* Replacement trees must be at least one-half inch in caliper, measured at six inches above the ground level for field grown trees or above the soil line for container grown trees (the one-half inch minimum size may be an average caliper measure, recognizing that trees are not uniformly round), unless they are oak or madrone which may be one gallon size. Shrubs must be in at least a one-gallon container or the equivalent in ball and burlap and must be at least 12 inches in height.**

**3. *Plant coverage.***

**a. *Native trees and shrubs are required to be planted at a rate of five trees and 25 shrubs per every 500 square feet of disturbance area (calculated by dividing the number of square feet of disturbance area by 500, and then multiplying that result times five trees and 25 shrubs, and rounding all fractions to the nearest whole number of trees and shrubs; for example, if there will be 330 square feet of disturbance area, then 330 divided by 500 equals 0.66, and 0.66 times five***

equals 3.3, so three trees must be planted, and 0.66 times 25 equals 16.5, so 17 shrubs must be planted). Bare ground must be planted or seeded with native grasses or herbs. Non-native sterile wheat grass may also be planted or seeded, in equal or lesser proportion to the native grasses or herbs.

b. Trees shall be planted between eight and 12 feet on center and shrubs shall be planted between four and five feet on center, or clustered in single species groups of no more than four plants, with each cluster planted between eight and 10 feet on center. When planting near existing trees, the dripline of the existing tree shall be the starting point for plant spacing measurements.

4. *Plant diversity.* Shrubs must consist of at least two different species. If 10 trees or more are planted, then no more than 50 percent of the trees may be of the same genus.

5. *Invasive vegetation.* Invasive non-native or noxious vegetation must be removed within the mitigation area prior to planting.

6. *Tree and shrub survival.* A minimum survival rate of 80 percent of the trees and shrubs planted is expected by the third anniversary of the date that the mitigation planting is completed.

7. *Monitoring and reporting.* Monitoring of the mitigation site is the ongoing responsibility of the property owner. Plants that die must be replaced in kind.

8. To enhance survival of tree replacement and plantings, the following practices are required:

a. *Mulching.* Mulch new plantings a minimum of three inches in depth and 18 inches in diameter to retain moisture and discourage weed growth.

b. *Irrigation.* Water new plantings one inch per week between June 15th to October 15th, for the three years following planting.

c. *Weed control.* Remove, or control, non-native or noxious vegetation throughout maintenance period.

d. *Planting season.* Plant bare root trees between December 1st and February 28th, and potted plants between October 15th and April 30th.

e. *Wildlife protection.* Use plant sleeves or fencing to protect trees and shrubs against wildlife browsing and resulting damage to plants.

B. When weather or other conditions prohibit planting according to schedule, the applicant shall ensure that disturbed areas are correctly protected with erosion control measures and shall provide the City with funds in the amount of 125 percent of a bid from a recognized landscaper or nursery which will cover the cost of the plant materials, installation and any follow up maintenance. Once the planting conditions are favorable the applicant shall proceed with the plantings and receive the funds back from the City upon completion, or the City will complete the plantings using those funds.

**Staff Finding 19: Staff adopts applicant findings.**

***“The mitigation planting plan will meet the mitigation requirements of CDC 32.090 and vegetative mitigation of CDC 32.080.***

**WRA Mitigation Plan**



*This WRA mitigation plan has been designed to meet the requirements of 32.100(A)1-8 as outlined above and described below. The applicant proposes enhancement mitigation of 2,216 sq. ft the remaining 65-foot WRA along the boundaries of the wetland, in areas currently degraded and not vegetated by native species (red osier dogwood thicket is present along the northern boundary of the onsite WRA). The applicant also proposes to restore the 806 sq. ft. of roof/deck overhang that encroaches into the WRA with native forest understory groundcover plants. The plan is expected to improve functions of the WRA by removing invasive species and establishing a diverse assemblage of native trees and shrubs along the boundaries of the wetland and restoring the disturbed area of WRA beneath the home with native forest understory species. The functions expected to be enhanced include hydrological functions (slowing velocity of stormwater runoff), water quality functions (retention of sediment and nutrients), organic material recruitment, and riparian wildlife habitat quality.*

**Planting Plan**

*The planting plan was developed according to 32.100 Revegetation requirements (Table 2). All plants were selected from the Portland Plant List. Plants selected for the planting area adjacent to the wetland boundaries (2,216 sq. ft.) are adapted to sun-part sun and seasonally wet-dry conditions. Plants selected for the planting area under the roof/deck overhang (806 sq. ft.) are groundcovers adapted to full shade, dry-moist conditions. The proposed quantities and sizing are according to the CDC requirements. 15 trees and 96 shrubs/woody groundcover plants will be installed in the WRA adjacent to the wetland boundaries. 30 shrubs and 68 groundcover plants will be installed in the WRA beneath the roof/deck overhang. All bare ground within the mitigation planting areas will be seeded with a native grass mix as shown below. Substitutions or additional plants are allowable, subject to price and availability, provided are included on the native Portland Plant List, meet the stated type, spacing, and total quantities listed in the table below and are suited to sun and moisture conditions. The planting plan is subject to approval by the City.*

Table 2. Planting Palette for WRA Mitigation Area (3,022 sq.ft.)

Species	Type	Minimum Size	Spacing	Quantity
<b>WRA Adjacent to Wetland Boundaries (2,216 sq. ft.)</b>				
Oregon ash <i>Fraxinus latifolia</i>	Tree	0.5" diam or 1 gal.	12'OC	6
Cascara <i>Rhamnus purshiana</i>	Tree	0.5" diam or 1 gal.	12'OC	9
Snowberry <i>Symphoricarpus albus</i>	Shrub	1 gal.	4-5'OC	24
Redosier dogwood <i>Cornus sericea</i>	Shrub	1 gal.	4-5'OC	24
Red flowering currant <i>Ribes sanguineum</i>	Shrub	1 gal.	4-5'OC	24
Kinnikinnick <i>Arctostaphylos uva-ursi</i>	Woody Ground cover	1 gal.	Clusters 10' OC	24
*Sunmark Seeds native EC mix or equivalent	Ground cover	1 lb/1,000 sq. ft.		2.4 lbs
<b>WRA Beneath Roof/Deck Overhang (806 sq. ft.)</b>				

Salal <i>Gaultheria shallon</i>	Shrub	1 gal.	4-5'OC	15
Western swordfern <i>Polystichum munitum</i>	Ground cover	1 gal.	4-5'OC	15
Fringecup <i>Tellima grandiflora</i>	Ground cover	4"	2-3'OC	34
Inside-out flower <i>Vancouveria hexandra</i>	Ground cover	4"	2-3'OC	34
*Sunmark Seeds native EC mix or equivalent	Ground cover	1 lb/1,000 sq. ft.		0.8 lb

\*Seed mix includes California brome (*Bromus carinatus*), blue wildrye (*Elymus glaucus*), spike bentgrass (*Agrostis exarata*), native red fescue (*Festuca rubra rubra*), tufted hairgrass (*champsia cespitosa*)

**Schedule and Maintenance Requirements Bare root trees shall be planted between December 1st and February 28th, and potted plants shall be planted between October 15th and April 30th, following construction of the project. Monitoring of the mitigation site is the ongoing responsibility of the property owner. Plants that die must be replaced in kind. In accordance with City requirements a minimum survival rate of 80 percent of the trees and shrubs planted is expected by the third anniversary of the date that the mitigation planting is completed.**

To enhance survival of tree replacement and plantings, in accordance with Section 32.100 the following practices are required: ☐ Mulch new plantings a minimum of three inches in depth and 18 inches in diameter to retain moisture and discourage weed growth. ☐ Irrigation for new plantings shall be provided in the amount of one inch per week between June 15th to October 15th, for the three years following planting. ☐ Non-native or noxious vegetation shall be removed or controlled throughout maintenance period. ☐ Use plant sleeves or fencing to protect trees and shrubs against wildlife browsing and resulting damage to plants. ☐ Resources for plant substitutions are as follows: o Native plants from the Portland Plant List <https://www.portland.gov/bps/documents/portland-plant-list/download> o Portland Plant List Native Plants Condensed <https://backyardhabitats.org/wp-content/uploads/2021/01/Condensed-Portland-Plant-List-Plants-by-Condition.pdf> o Gardening with Oregon Native Plants West of the Cascades <https://extension.oregonstate.edu/catalog/pub/ec-1577-gardening-oregon-native-plants-west-cascades>"  
The criteria are met.


#### 48.030 MINIMUM VEHICULAR REQUIREMENTS FOR RESIDENTIAL USES

...

B. Driveway standards. When any portion of any house is less than 150 feet from the adjacent right-of-way, driveway access to the home shall meet the following standards:

1. One single-family residence, including residences with an accessory dwelling unit as defined in CDC 02.030, shall provide a driveway with 10 feet of unobstructed horizontal clearance. Dual-track or other driveway designs that minimize the total area of impervious driveway surface are encouraged but not required.

2. Two to four single-family residential homes shall provide a driveway with 14- to 20-foot-wide paved or all-weather surface.
3. Maximum driveway grade shall be 15 percent. The 15 percent shall be measured along the centerline of the driveway only. Variations require approval of a Class II variance by the Planning Commission pursuant to Chapter 75 CDC. However, in no case shall the last 18 feet in front of the garage exceed 12 percent grade as measured along the centerline of the driveway only. Grades elsewhere along the driveway shall not apply.
4. The driveway shall include a minimum of 20 feet in length between the garage door and the back of sidewalk, or, if no sidewalk is proposed, to the paved portion of the right-of-way.



**Staff Finding 20:** As demonstrated on the proposed site plan, the replacement single-family dwelling will be located approximately 70 feet from the public right of way. The existing driveway will be expanded to a width of 15 feet, exceeding the minimum standard of 10 feet, and at a grade of approximately 0.015%. The criteria are met.

#### 96.010 CONSTRUCTION REQUIRED

- A. Street improvements for residential construction are required when:
  1. Construction of a new single-family attached or detached structure (replacement of an existing structure is exempt); or
  2. Replacement of a single-family home increases the square feet by 50 percent or greater; or
  3. Construction of a new multifamily structure; or
  4. Increase in dwelling unit density on site (accessory dwelling units are exempt).

[...]

#### 96.020 FEE-IN-LIEU

- A. An applicant may apply for a waiver of street improvements and the option to pay a fee-in-lieu (in accordance with the City's adopted fee structure) of constructing street improvements if one of the following are met:
  1. Located on a cul-de-sac with no existing curb and/or no existing sidewalk; or

2. Located on a street less than 1,320 linear feet in length and not planned as a through street; or
3. Located more than 1,320 linear feet from nearest street improvements on the same street or connecting street.

**Staff Finding 21:** The application is for the demolition of an existing single-family dwelling approximately 1,487 square feet in size, to be replaced with a new dwelling approximately 6,385 square feet in size. The proposed single-family home increases the size of the structure by greater than 50% therefore street improvements are required. The subject property is located on a cul-de-sac with no existing curb and no existing sidewalk thus the applicant shall pay a fee-in-lieu of constructing street improvements. Fee-in-lieu payments are calculated at \$375 per linear foot. The subject property has approximately 81.67 linear feet of frontage. The calculation of the fee-in-lieu is  $\$405 \times 81.67 = \$33,076$ .

#### 99.080 NOTICE

Notice shall be given in the following ways:

A. Class A Notice. Notice of proposed action or a development application pursuant to CDC 99.060 shall be given by the Director in the following manner:

1. At least 20 days prior to the scheduled hearing date notice shall be sent by mail to:
  - a. The applicant or the applicant's agent, and the property owner of record on the most recent property tax assessment roll where such property is located.
  - b. All property owners of record on the most recent property tax assessment roll where such property is located within 500 feet of the site.
  - c. Any affected governmental agency which has entered into an intergovernmental agreement with the City which includes provision for such notice; plus, where applicable, the Oregon Department of Transportation, Tri-Met, neighboring local jurisdictions, Clackamas County Department of Transportation and Development, and Metro.
  - d. The affected recognized neighborhood association or citizens advisory committee.
  - e. For a hearing on appeal or review, all parties and persons with standing described in CDC 99.140 to an appeal or petition for review.
2. At least 10 days prior to the hearing or meeting date, notice shall be given in a newspaper of general circulation in the City. An affidavit of publication shall be made part of the administrative record.
  - a. Decisions pursuant to CDC 99.060(A), Planning Director authority, are exempt from the requirements of this subsection.
3. At least 10 days prior to the hearing or meeting date, the Planning Director shall cause a sign to be placed on the property which is the subject of the decision or, if the property does not have frontage on a public street, adjacent to the

*nearest public street frontage in plain view and shall state, "This property is the subject of a land use decision," with the type of use or request indicated.*

*If the application is not located adjacent to a through street, then an additional sign shall be posted on the nearest through street.*

*4. At least 10 days but no more than 40 days prior to hearing of a proposed zone change for manufactured home parks, notice shall be given to the respective manufactured home park residents.*

*5. The Director shall cause an affidavit of mailing of notice and posting of notice to be filed and made part of the administrative record.*

*6. At the conclusion of the land use action the signs shall be removed.*

**Staff Finding 22: A Class A Notice was prepared and sent via mail to the applicant, the affected neighborhood association, agencies having jurisdiction, and all property owners within 500 ft. of the site perimeter on July 31, 2024. A sign detailing the property as being the subject of a land use decision with case details was placed on the property on July 30, 2024. An affidavit of mailing of notice and posting of notice was filed in the land use case record (see Exhibit PD-5). This decision is made under the authority of the Planning Director and is exempt from the requirement of posting in a newspaper of general circulation. The criteria are met.**

**EXHIBIT PD-1 – APPLICANT SUBMITTAL**

**EXHIBIT PD-2 – COMPLETENESS LETTER**

**EXHIBIT PD-3 – PUBLIC COMMENTS**



**EXHIBIT PD-4 – AGENCY COMMENTS**

**EXHIBIT PD-5 – AFFADAVIT AND NOTICE PACKET**

**EXHIBIT PD-1 – APPLICANT SUBMITTAL**

## DEVELOPMENT REVIEW APPLICATION

For Office Use Only		
STAFF CONTACT	PROJECT No(s).	PRE-APPLICATION No.
NON-REFUNDABLE FEE(S)	REFUNDABLE DEPOSIT(S)	TOTAL

**Type of Review** (Please check all that apply):

- |   |   |   |
|---|---|---|
| <input type="checkbox"/> Annexation (ANX)               | <input type="checkbox"/> Final Plat (FP) Related File#          | <input type="checkbox"/> Subdivision (SUB)  |
| <input type="checkbox"/> Appeal (AP)                    | <input type="checkbox"/> Flood Management Area (FMA)            | <input type="checkbox"/> Temporary Uses (MISC)                                      |
| <input type="checkbox"/> CDC Amendment (CDC)            | <input type="checkbox"/> Historic Review (HDR)                  | <input type="checkbox"/> Time Extension (EXT)                                       |
| <input type="checkbox"/> Code Interpretation (MISC)     | <input type="checkbox"/> Lot Line Adjustment (LLA)              | <input type="checkbox"/> Right of Way Vacation (VAC)                                |
| <input type="checkbox"/> Conditional Use (CUP)          | <input type="checkbox"/> Minor Partition (MIP)                  | <input type="checkbox"/> Variance (VAR)   |
| <input type="checkbox"/> Design Review (DR)             | <input type="checkbox"/> Modification of Approval (MOD)         | <input checked="" type="checkbox"/> Water Resource Area Protection/Single Lot (WAP) |
| <input type="checkbox"/> Tree Easement Vacation (MISC)  | <input type="checkbox"/> Non-Conforming Lots, Uses & Structures | <input type="checkbox"/> Water Resource Area Protection/Wetland (WAP)               |
| <input type="checkbox"/> Expediated Land Division (ELD) | <input type="checkbox"/> Planned Unit Development (PUD)         | <input type="checkbox"/> Willamette & Tualatin River Greenway (WRG)                 |
| <input type="checkbox"/> Extension of Approval (EXT)    | <input type="checkbox"/> Street Vacation                        | <input type="checkbox"/> Zone Change (ZC)   |

Pre-Application, Home Occupation, Sidewalk Use, Addressing, and Sign applications require different forms, available on the website.

Site Location/Address: <b>5494 LINN LANE</b> <b>WEST LINN, OR 97068</b>	Assessor's Map No.: <b>21E25B000500</b> Tax Lot(s): <b>500</b> Total Land Area: <b>29,318 sq.ft.</b>
---	--

**Brief Description of Proposal:** THE PROPOSED SINGLE FAMILY RESIDENCE WILL BE REPLACING AN EXISTING DWELLING OVER 60 YEARS OLD. THE NEW HOME WILL BE IN THE SAME LOCATION AS THE EXISTING ONE. MINIMAL GRADING WILL BE TAKING PLACE IN THE ERA ZONE. LANDSCAPING WILL CONSIST OF GRASSES, NATIVE PLANTING AND A VARIETY OF FLOWERING AND EVERGREEN TREES.

Applicant Name*: <b>KEVIN JANSSEN</b> Address: <b>614 SE 52ND AVE.</b> City State Zip: <b>PORTLAND, OR 97215</b>	Phone: <b>541-515-0653</b> Email: <b>khjanssen@yahoo.com</b>
--	---

Owner Name (required): <b>ROBERT EASTON</b> Address: <b>21520 LUPINE Ct.</b> City State Zip: <b>WEST LINN, OR 97068</b>	Phone: <b>503-866-8810</b> Email: <b>BOBEASTON@COMCAST.NET</b>
---	---

Consultant Name: <b>KIM CARTWRIGHT</b> Address: <b>P.O. Box 589</b> City State Zip: <b>AURORA, OR 97002</b>	Phone: <b>503-678-6028</b> Email: <b>KIM@SCHOTTANDASSOCIATES.COM</b>
---	---

1. Application fees are non-refundable (excluding deposit). Applications with deposits will be billed monthly for time and materials above the initial deposit. **\*The applicant is financially responsible for all permit costs.**
2. The owner/applicant or their representative should attend all public hearings related to the propose land use.
3. A decision may be reversed on appeal. The decision will become effective once the appeal period has expired.
4. Submit this form, application narrative, and all supporting documents as a single PDF through the Submit a Land Use Application web page: <https://westlinnoregon.gov/planning/submit-land-use-application>

The undersigned property owner authorizes the application and grants city staff the **right of entry** onto the property to review the application. Applications with deposits will be billed monthly for time and materials incurred above the initial deposit. The applicant agrees to pay additional billable charges.

[Signature]

2/11/24



# CITY OF West Linn

March 1, 2024

Kevin Janssen,  
614 SE 52<sup>nd</sup> Ave  
Portland OR 97215

Subject: WAP-24-01 Water Resource Area Permit for the replacement of an existing single-family residence at 5494 Linn Lane

Dear Mr. Janssen:

The City accepted your application for review on February 20, 2024, with supplemental materials provided on February 27, 2024. The Planning Department find that this application is **incomplete**. The following items must be addressed and included in a complete revised submittal package uploaded through the [application portal](#).

- 1. Narrative.** Please provide a narrative that specifically addresses CDC 48.030(B) & (C).
- 2. Building Height.** Please revised the building elevations to include all elevations and the total height of the structure using the methodology of CDC 41.005, and 41.020 if applicable.
- 3. Preliminary Stormwater Plan.** Please provide a storm detention and treatment plan and associated narrative per CDC 32.050.F.3.
- 4. Construction Management Plan.** Please provide a construction management plan per CDC 32.050.G.
- 5. Driveway Details.** Please revise the site plan to provide details regarding the existing and proposed driveway widths and turnaround area, any changes or extension of the existing pipe below the driveway, and any work proposed in the public right of way.
- 6. TVF&R Service Provider Permit.** Please provide a complete TVF&R Service Provider Permit, as the one submitted appears incomplete

- 7. Overhang above Public Utility Easement.** Please revise the site plan to remove the roof overhang over the public utility easement. For questions about this requirement, please contact Clark Ide in the Engineering department at [cide@westlinnoregon.gov](mailto:cide@westlinnoregon.gov) or 503-722-3437.

Pursuant to CDC 99.035, the Planning Director may require information in addition to that required by a specific chapter in the Community Development Code or may waive a specific requirement for information or a requirement to address an approval standard.


Pursuant to ORS 227.178 “If an application for a permit, limited land use decision or zone change is incomplete, the governing body or its designee shall notify the applicant in writing of exactly what information is missing within 30 days of receipt of the application and allow the applicant to submit the missing information. The application shall be deemed complete for the purpose of subsection (1) of this section upon receipt by the governing body or its designee of:

- (a) All of the missing information;
- (b) Some of the missing information and written notice from the applicant that no other information will be provided; or
- (c) Written notice from the applicant that none of the missing information will be provided.

You now have 180 days, through **August 28, 2024**, to make the application complete by providing the information outlined above. On the 181<sup>st</sup> day after first being submitted, the application will be considered void if the applicant has been notified of the missing information and has not submitted the information as requested above or a written notice responding to the above options.

Please contact me at 503-742-6058, or by email at [jfloyd@westlinnoregon.gov](mailto:jfloyd@westlinnoregon.gov) if you have any questions or comments.

Sincerely,



John Floyd  
Senior Planner

# Barclay Home Design

12112 S. New Era Road  
Oregon City, OR 97045  
503-970-4257

John Floyd  
Senior Planner  
City of West Linn  
Re: Proposed residential replacement dwelling  
5494 Linn Lane  
West Linn, OR 97068

The proposed residence will be replacing an existing dwelling over 60 years old. The new home will be in the same location as the existing one. Minimal grading will be taking place in the ERA zone. Landscaping will consist of grasses, native planting and a variety of flowering and evergreen trees. The proposed drive is at the same location as the existing one.

Written response to approval criteria included.

A stamped approved site plan from Jason Arn (Tualatin Valley Fire & Rescue) is included (Pg. D)

Vicinity map (Pg. C) included on-site plan; Grading Plan also included (Pg. B).


The site plan includes:

1. Included
2. Included
3. Included (zoning) No Neighborhood Association
4. Included. Existing dwelling setbacks for the proposed structure.
5. Included. Proposed drive-off street parking n/a.
6. N/A
7. Included all easements.
8. Existing trees and trees to be removed are shown. A landscape professional to be retained to provide a landscape plan.
9. Gas, electrical, sewer and water location to remain the same. 100 yr. floodplain n/a.
10. Site-sensitive areas shown.
11. N/A
12. N/A
13. N/A

Additional: Natural resource assessment provided by Kim Cartwright, Wetland Ecologist G.I.S. analyst

Additional: Stormwater Management Report provided by Deborah Beck, P.E., of White Pelican Consulting, LLC

Cordially,  
Michael J. Barclay



NARRATIVE FOR PA-23-20  
WATER RESOURCES AREA PERMIT

Located at 5494 Linn Lane

KEVIN JANSSEN and MICHELLE JANSSEN, APPLICANTS

INTRODUCTION

The application for a Water Resources Area Permit requires “full written responses to approval criteria in the identified CDC Chapters”, as noted in **Item 3** of “HOW TO SUBMIT AN APPLICATION”. The applicable CDC Code Sections, as identified on Pg. 1 of the SUMMARY NOTES of the PRE-APPLICATION CONFERENCE MEETING, are as follows:

- Chapter 11: Residential, R-10;
- Chapter 32: Water Resource Area Protection;
- Chapter 48: Access, Egress, and Circulation;
- Chapter 96: Street Improvement Construction;
- Chapter 99: Procedures for Decision Making: Quasit-Judicial

DISCUSSION

- CHAPTER 11: This property lies within a residential zone, R-10, and because the project is a single-family home replacing an existing single-family home, it is a permitted use per Section 11.030-6. No further discussion is needed.
- CHAPTER 32: See “*NATURAL RESOURCE ASSESSMENT -5494 Linn Lane*” prepared by Kim Cartwright of Schott and Assoc., attached herein by reference.
- CHAPTER 48: The property is located at the north end of Linn Lane, which is a dead-end public street. The new dwelling will use the same point of access onto Linn Lane as does the existing house, but with a slightly wider, paved driveway. Linn Lane is paved but has no curbs or sidewalks. Therefore, the driveway will not have a standard concrete apron but will transition directly into the existing street pavement. We believe we meet all conditions of access, egress and circulation as described in Chapter 48.
- CHAPTER 96: Section 96.010 A.2 states that “*Street improvements for residential construction are required when... Replacement of a single-family home increases the square feet by 50 percent or greater*”. However, according to Section 96.020:  

“A. An applicant may apply for a waiver of street improvements and the option to pay a fee-in-lieu (in accordance with the City’s adopted fee structure) of constructing street improvements if one of the following are met:

  1. Located on a cul-de-sac with no existing curb and/or no existing sidewalk; or
  2. Located on a street less than 1,320 linear feet in length and not planned as a through street; or



3. *Located more than 1,320 linear feet from nearest street improvements on the same street or connecting street. (Ord. 1739 § 2 (Exh. B), 2022)”*

As noted under Chapter 48 above, Linn Lane is a paved, dead-end street with no existing curb or sidewalk. It is less than 1,320 feet in length and is not planned to be extended to the north because of the topography and the existence of a City park. As such it satisfies both conditions 1 and 2 above and should be considered to be candidate for an in-lieu-of waiver for street improvements along the frontage of this parcel.

*However, we also believe that, because the Linn Lane neighborhood is a well-established neighborhood, is a short, dead-end street and will probably never be extended or improved with curbs, gutters or sidewalks, the in-lieu-of option be waived as well.*

#### SUMMARY

We believe that through the above discussions we have satisfied the approval criteria outlined in Chapters 11, 32, 48 and 96, as required by Pre-Application Conference Summary Notes. As such, we hereby request approval of the Water Resources Area Permit for this site.

Date: 07/08/2024

John Floyd  
Senior Planner  
City of West Linn

Subj: WAP-24-01 Water Resource Area Permit for the replacement of an existing single-family residence at 5494 Linn Lane, West Linn, OR 97068


Dear Mr. Floyd,

Please find, below and attached, our responses addressing the seven (7) items listed in your letter of March 1, 2024.

1. Code sections CDC 48.030(B) and (C) deal with driveway standards. Because this permit is for a single-family residence that is less than 150ft. from the adjacent street right-of-way, only (B)1 and (B)3 apply:
  - a. Sheet A, Driveway Plan, of the attached plans, shows the distance between the house and the adjacent street right-of-way to be 70ft. (i.e. less than 150ft.).
  - b. (B)1 is satisfied by also referring to Sheet A, Driveway Plan of the attached plans, which shows the driveway with a minimum width of 15ft.
  - c. (B)3 is satisfied by referring to Sheet B, Driveway Plan, of the attached plans, which shows the slope of the driveway to be 0.015%, well below the maximum allowable grade of 15%.
  - d. CDC 48.030(C) does not apply because the proposed dwelling is only 70ft. from the adjacent street right-of-way.
2. Sheets 1 and 2 of the attached Plans have been modified to show building heights on all four (4) elevation drawings in accordance with CDC 41.005. CDC 41.020 does not apply. We are not requesting any height exceptions.
3. A Preliminary Stormwater Plan, prepared by Deborah Beck of White Pelican Engineers in accordance with CDC 92.010 E, is attached as requested.
4. A Construction Management Plan has been provided as requested. See Plot Plan and Erosion Control on Sheet A of the attached plans. The Plot Plan has been modified to reflect erosion control and protection fencing for wetland and material stockpile in accordance with CDC 32.050G.
5. An enlarged plan of the driveway is shown on Sheet A, showing the existing and proposed driveway and turn-around area with dimensions.
  - a. In an email received on July 2<sup>nd</sup>, 2024, Deborah Beck of White Pelican Engineering wrote the following:  
*“Hello Mike and Kevin, Good news, the believed location of the stormwater pipe draining the wetland on the south side of the existing driveway does not appear to interfere with the proposed locations of the StormTech chambers. Drainpipe has been added to the drawings and attached are the updated drawings and report for the stormwater design at 5494 Linn Ln.”*

This message confirms that the location of the pipe under the driveway will not interfere with the proposed Stormwater Plan. Therefore, no changes are necessary to the existing pipe under the driveway.


- b. The proposed concrete driveway will blend into Linn Lane with an asphalt transition to match the street's existing surface.
6. TVF&R has reviewed and stamped the Plot Plan, indicating approval. Permit number is 2023-0013.
  7. The Plot Plans, Sheets A, B, C and D have been revised by moving the house 3ft. to the south to remove the roof overhang from the Public Utility Easement that runs along the northerly property line.



# PLOT PLAN & EROSION CONTROL

T.L. 21E25BD00500  
5434 LINN LN.  
WEST LINN, OR

SCALE: 1" = 20'




# DRIVEWAY PLAN

(EXISTING & PROPOSED)

SCALE: 1" = 10'

A RESIDENCE FOR: **THE JANSSEN FAMILY**

APPLICANT : **ROBERT EASTON**  
21520 LUPINE CT.  
WEST LINN, OR 97068  
(503) 866-8810



DISTURBANCE AREA (PERMANENT / PROPOSED) 2453 SQ. FT.

R-10 ZONE	
SETBACKS:	FRONT 20'
	REAR 20'
	SIDE 7.5'
LOT AREA: 29,318 SQ. FT.	
ALLOWABLE COVERAGE:	10,261 SQ. FT. (35%)
ACTUAL COVERAGE:	6,780 SQ. FT. (23%)
ALLOWABLE FAR:	13,183 SQ. FT. (45%)
ACTUAL FAR:	6,385 SQ. FT. (22%)




FAIBD.  
(503)970-4257


12112 S NEW ERA RD  
OREGON CITY, OR 97045

General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. However, local variations may require changes. Likewise, building code requirements vary with location and change from time to time. Before starting construction, the builder must review and be responsible for all details and dimensions, and ensure that these plans meet all current requirements in your area and the current requirements of the local jurisdiction. It is suggested that a local architect and/or engineer be consulted to verify the accuracy of the drawings and the local requirements. The professional stamp is required on drawings filed for permit purposes. All applicable construction shall conform to the latest editions of either "Uniform Building Code" or the "BOCA Basic Building Code," or any other locally required code. Codes govern over drawings. Dimensions govern over scale. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

All other measurements, drawings and details not shown on this sheet are the original work product of the architect. The use of this sheet without the written permission of Barclay Home Designs Inc. is strictly prohibited by law without the written permission of Barclay Home Designs Inc. Contractors shall verify and be responsible for all dimensions and conditions on the job. This office must be notified of any variations and discrepancies of and from these drawings prior to work on the job.



JANSSEN




# GRADING PLAN

SCALE: 1" = 20'

T.L. 21E25BD00500  
5494 LINN LN.  
WEST LINN, OR


## A RESIDENCE FOR: THE JANSSEN FAMILY

APPLICANT : ROBERT EASTON  
21520 LUPINE CT.  
WEST LINN, OR 97068  
(503) 866-8810




DISTURBANCE AREA (PERMANENT / PROPOSED) 2453 SQ. FT.

R-10 ZONE	
SETBACKS:	FRONT 20'
	REAR 20'
	SIDE 75'
LOT AREA:	29,318 SQ. FT.
ALLOWABLE COVERAGE:	10,261 SQ. FT. (35%)
ACTUAL COVERAGE:	6,780 SQ. FT. (23%)
ALLOWABLE FAR:	13.15 SQ. FT. (45%)
ACTUAL FAR:	6.385 SQ. FT. (22%)



12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503)970-4257




JANSSEN

General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. However, local variations may require changes. Likewise, building code requirements vary with location and change from time to time. Before starting construction, the builder must review and be responsible for all details and dimensions, and ensure that these plans meet all current requirements in your area. It is also suggested that a local architect and/or engineer be consulted for any local requirements. For all other requirements, the contractor shall refer to the applicable building codes and the Uniform Building Code or the "BOCA Basic Building Code," or any other locally required code. Codes govern over drawings. Dimensions govern over scale. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

All other measurements, drawings, and specifications shall be taken from the original work sheet of record by and used for the construction of this building. Any use, reuse, or disclosure of any part of this work product is limited to a specified project of the purchaser and for the construction of one building. Any other reuse or disclosure of Barclay Home Designs Inc. drawings, ideas, designs, and/or arrangements, other than by Barclay Home Designs Inc. is strictly prohibited by law without the written permission of Barclay Home Designs Inc. Contractors shall verify and be responsible for all dimensions and conditions on the job. This office must be notified of any variations and discrepancies of and from these drawings prior to work on the job.





**TVF&R**  
Tualatin Valley  
Fire & Rescue  
APPROVED PLANS

APPROVAL OF PLANS IS NOT AN APPROVAL  
OF DIMENSIONS OR OVERSIGHTS.

*Jason Owen*  
Division Fire Marshal

TVF&R Permit 2023-0013

P L O T   P L A N   W /   F I R E   A P P R O V A L

T.L. 21E25BD00500  
5494 LINN LN.  
WEST LINN, OR

SCALE: 1" = 20'

A RESIDENCE FOR:    T H E   J A N S S E N   F A M I L Y

APPLICANT :    ROBERT EASTON  
21520 LUPINE CT.  
WEST LINN, OR 97068  
(503) 866-8810



General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. However, local variations may require changes. Likewise, building code requirements vary with location and change from time to time. Before starting construction, the builder must review and be responsible for all details and dimensions, and ensure that these plans meet all current requirements in your area. It is also suggested that a local architect and/or engineer be consulted to verify that the proposed construction complies with all applicable codes and regulations. All applicable construction shall conform to the latest editions of a professional stamp is required on drawings filed for permit purposes. All applicable construction shall conform to the latest editions of either "Uniform Building Code" or the "BOCA Basic Building Code," or any other locally required code. Codes govern over drawings. Dimensions govern over scale. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

All other arrangements, drawings, and plans set forth on this sheet are the original work produced or owned by, and are the property of Barclay Home Designs Inc. Use of this sheet, or any part thereof, for any other project or building is strictly prohibited by law without the written permission of Barclay Home Designs Inc. Contractors shall verify and be responsible for all dimensions and conditions on the job. This office must be notified of any variations and discrepancies of and from these drawings prior to work on the job.

**Barclay**  
HOME DESIGNS  
FALBD.



12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503)970-4257

JANSSSEN

D



FRONT ELEVATION  
SCALE: 3/16" = 1'-0"



REAR ELEVATION  
SCALE: 3/16" = 1'-0"


All ideas, arrangements, drawings, and plans set forth on this sheet are the property of Barclay Home Designs Inc. Use of this and work product is limited to a specified project of the purchaser and shall not be reproduced, copied, or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without the prior written consent of Barclay Home Designs Inc. This office and its employees shall not be held responsible for any omissions, errors, or discrepancies of and from these drawings prior to work on this job.

12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503) 970-4257




General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. It is the responsibility of the client to provide all necessary information and to verify the accuracy of the information provided. The architect is not responsible for the construction of the project or for the safety of the project. The architect is not responsible for the construction of the project or for the safety of the project. The architect is not responsible for the construction of the project or for the safety of the project.


MAN FLR  
3178 SQFT  
UPPER FLR  
1217 SQFT.









**ROOF ELEVATIONS**  
SCALE: 3/16" = 1'-0"



**ROOF PLAN**  
SCALE: 3/16" = 1'-0"




**RIGHT SIDE ELEVATION**  
SCALE: 3/16" = 1'-0"



**LEFT SIDE ELEVATION**  
SCALE: 3/16" = 1'-0"


All ideas, arrangements, drawings, and plans set forth on this sheet are the property of Barclay Home Designs Inc. Use of this and work product is limited to a specified project of the client. Any other use, reproduction, or modification without the written consent of Barclay Home Designs Inc. is strictly prohibited by law. This office and its employees shall not be held responsible for any omissions, errors, or discrepancies of and from these drawings prior to work on this job.


12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503) 970-4257



**General Notes and Disclaimers:** These drawings have been prepared to meet generally accepted professional standards. It is the responsibility of the client to provide all necessary information and to ensure that these plans meet all current requirements in your area. It is also suggested that local architect and engineer stamps be obtained for all drawings. A professional stamp is required on drawings filed for record with your local building department to see if a professional stamp is required on drawings filed for record. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

MAIN FLR  
3179 SQFT  
UPPER FLR  
1217 SQFT.






**MAIN FLOOR PLAN**  
SCALE: 3/16" = 1'-0"


All ideas, arrangements, drawings, and plans set forth on this sheet are the property of Barclay Home Designs Inc. Use of this and work product is limited to a specified project of the client. Any other use, reproduction, or distribution of this work without the express written consent of Barclay Home Designs Inc. is strictly prohibited by law. This office and its employees shall not be held responsible for any errors, omissions, or discrepancies of and from these drawings, plans, or work on this job.


12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503) 970-4257



General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. It is the responsibility of the client to ensure that all requirements in your area are met. It is also suggested that local architect and engineering requirements be checked. The client is responsible for obtaining all necessary permits and approvals. The client is responsible for checking with the local building department to see if a professional stamp is required on drawings filed for permit. Codes govern over drawings. Dimensions govern over notes. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

MAIN FLR  
3178 SQFT  
UPPER FLR  
1221 SQFT.





**UPPER FLOOR PLAN**

SCALE: 3/16" = 1'-0"


All ideas, arrangements, drawings, and plans set forth on this sheet are the property of Barclay Home Designs Inc. Use of this and work product is limited to a specified project of the client. Any other use, reproduction, or modification without the written consent of Barclay Home Designs Inc. is strictly prohibited by law. This office and its employees shall not be held responsible for any errors, omissions, or discrepancies of and from these drawings, plans, or work on this job.

12112 S NEW ERA RD  
OREGON CITY, OR 97045  
(503) 970-4257



**General Notes and Disclaimers:** These drawings have been prepared to meet generally accepted professional standards. It is the responsibility of the client to verify all details and dimensions, and to ensure that these plans meet all current requirements in your area. It is also suggested that local architect and/or engineer review and stamp these drawings. A professional stamp is required on drawings filed for record with your local building department to see if a professional stamp is required on drawings filed for record with your local building department. Codes govern over drawings. Dimensions govern over notes. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

MAIN FLR  
3178 SQFT  
UPPER FLR  
1217 SQFT.





**SCHOTT & ASSOCIATES**  
Ecologists & Wetlands Specialists

---

21018 NE Hwy 99E • P.O. Box 589 • Aurora, OR 97002 • (503) 678-6007 • FAX: (503) 678-6011

**NATURAL RESOURCE ASSESSMENT**

**5494 Linn Lane**

T2S, R1E, Section 25BD, Tax Lot 500  
West Linn, Oregon

**Prepared for**

Kevin Janssen  
614 SE 52<sup>nd</sup> Avenue  
Portland, OR 97215

**Prepared by**

Kim Cartwright  
of  
Schott & Associates, Inc.

**Date:**

November 2023

Project #: 3079

## TABLE OF CONTENTS

INTRODUCTION .....	2
SITE DESCRIPTION AND LAND USE .....	2
METHODS .....	2
RESULTS .....	3
WATER RESOURCE AREA (WRA).....	4
Protected Water Features .....	4
Wetland Buffer.....	5
PROPOSED PROJECT .....	5
APPROVAL CRITERIA .....	6
32.090 MITIGATION PLAN .....	12
WRA MITIGATION PLAN.....	15
PLANTING PLAN.....	15
SCHEDULE AND MAINTENANCE REQUIREMENTS .....	16

## LIST OF FIGURES

- Figure 1. Location Map
- Figure 2. Existing Conditions
- Figure 3. Proposed WRA and Mitigation Planting Areas

## LIST OF APPENDICES

- Appendix A. City of West Linn WRA Map
- Appendix B. Site Plan
- Appendix C. Site Survey
- Appendix D. Geotechnical Study
- Appendix E. Site Photographs
- Appendix F. Wetland Determination Forms

## **Introduction**

Schott & Associates (S&A) was contracted to conduct wetland delineation and natural resource assessment for the project site at 5494 Linn Lane, West Linn, Clackamas County, Oregon (T2S, R1E, Section 25BD, Tax Lot 500; Figure 1). This property contains a Water Resource Area (WRA) that is subject to regulation under Chapter 32 of the West Linn Community Development Code (CDC). The purpose of this report is to document existing and proposed conditions with regards to regulated natural resources and meet City approval criteria for the proposed project. The applicant participated in a pre-application meeting with the City on July 20, 2023 (File PA-23-20). An online meeting was held with the applicant, site architect, S&A, and John Floyd, Associate Planner of the City of West Linn, on August 17, 2023, to discuss the project. Additional correspondence has occurred between all parties to develop this proposal. A wetland delineation report has been prepared and was submitted to the Oregon Department of State Lands (DSL) for review on October 11, 2023 (WD#2023-0462). WRA boundaries and encroachments presented in this report are based on boundaries pending DSL approval.

All work on this project has been completed by a qualified natural resource specialist. Onsite assessment and reporting were conducted by Kim Cartwright, a wetland ecologist with over 12 years of experience in conducting natural resource assessments, including wetland and other water delineations, habitat and functional assessments, natural resource permitting, and mitigation site planning and development.

## **Site Description and Land Use**

The project site consisted of the entire 0.70-acre parcel. Residential development, including parking and turnaround areas, were in the northwestern portion of the property, accessed by an asphalt driveway from Linn Lane to the east. The site features steep convergent slopes which form a well-defined, southwest sloping swale in the eastern portion of the site. The existing home is perched on top of the slope on the west side of the property. The driveway crosses the swale and was constructed 5-6 feet above the surrounding grade to match that of the home and parking area. A culvert outlet extends from the ground upslope from the swale, just offsite to the south. A culvert placed at the bottom of the swale on the south side of the driveway conducts any surface flows east, offsite, and into a ditch on the east side of Linn Lane. The ditch flows north and into an offsite drainage in the Sahallie Illahee Park, which borders the property to the north. Onsite vegetation generally consisted of mown turfgrasses with ornamental trees and shrubs around the home. Himalayan blackberry (*Rubus armeniacus*) thickets were present in and around the swale and had been recently mown to facilitate site access for this study. A thicket of red-osier dogwood (*Cornus sericea*) grew along the northeastern site boundary.

Surrounding land use was moderate-density, single-family residential to the east, south, and west, and the forested Sahallie Illahee Park to the north. The property was zoned for single-family residential (West Linn zoning designation R-10).

## **Methods**

Assessment consisted of a site visit and review of the following existing data and information:

- Clackamas County tax map

- U.S. Fish and Wildlife Service (USFWS) National Wetland Inventory (NWI), West Linn 2005 Local Wetland Inventory (LWI), and Metro wetland and stream mapping.
- West Linn Water Resource Area (WRA) Map (Appendix A)
- Oregon Department of Forestry (ODF) and Metro stream mapping
- U.S. Department of Agriculture (USDA) Natural Resource Conservation Service (NRCS) gridded Soil Survey Geographic (gSSURGO) database for Clackamas County
- Aerial photographs for the time period between 1994 and 2021, obtained from Google Earth
- Contours derived from the Oregon Department of Geology and Mineral Industries (DOGAMI, 2014) as well as site survey completed by Love Land Surveyors (Appendix C)
- Pre-application meeting conducted with City of West Linn (File PA-23-20), online meeting, and email correspondence with John Floyd

Schott & Associates visited the site on July 10, 2023. Delineation data were collected according to methods described in the *1987 Manual* and the *Regional Supplement to the Corps of Engineers Delineation Manual: Western Mountains, Valleys, and Coast (Version 2.0)*. Five sample plots were established to document the presence and extent of wetland. Data on vegetation, hydrology, and soils was collected at the sample plot, recorded in the field, and later transferred to data forms (Appendix F). Plant indicator status was determined using the 2020 National Wetland Plant List (Corps 2020). Onsite streams, if present, were delineated via the ordinary high-water mark (OHWM) as indicated by top of bank, wrack or scour lines, or change in vegetation communities.

Wetlands and waters were classified according to the USFWS *Classification of Wetlands and Deepwater Habitats of the United States* (Cowardin et al. 1979) and the *Guidebook for Hydrogeomorphic (HGM)-based Assessment of Oregon Wetland and Riparian Sites* (DSL 2001).

Vegetation communities within the onsite WRA were assessed in the field. Vegetation was identified by species and percent cover. The wetland determination forms included in Appendix F describe vegetation cover in the WRA. As the property was bordered by a public right-of-way to the east and a public park to the north, these offsite areas were visually inspected to determine the surrounding site conditions. Required width of the Water Resource Area was determined according to Table 32-2 of the CDC, as indicated by Item B, *the width of the WRA extends from the water resource to the top of the slope (30-foot minimum), plus an additional 50 feet.*

Ground level photographs were taken to document site conditions (Appendix E).

## **Results**

According to the NRCS soil survey, Cornelius silt loam, 8-15% slopes, was mapped within all but the northwestern corner of the site; Xerochrepts and Haploxerolls, very steep, were mapped in the northwestern site corner. The Cornelius soil series is moderately well-drained, not subject to flooding or ponding, and is predominantly nonhydric (4% hydric inclusions). Xerochrepts and Haploxerolls are well drained and nonhydric. No water resources are mapped by the NWI, ODF,

or Metro. The West Linn LWI and the West Linn WRA Map show a drainage in the location of the swale. This drainage is identified as a tributary to Barlow Creek by the West Linn WRA map and as a “ditch” by the LWI. The WRA Map does not show a WRA buffer associated with the ditch. It should be noted that these sources are largely remotely sensed and are not verified through ground-truthing in most cases.

No streams were identified within the project site. Streams are generally defined as unvegetated channels with indicators of ordinary high-water mark (OHWM) including top-of-bank, wrack or scour lines, and change in vegetation communities. Instead, a headwater wetland was identified in the bottom of the swale, bisected by the access road, and partially rerouted by the pipe at the south end of the road. The water resource was entirely vegetated with no bed or banks and met wetland criteria. It is possible the wetland swale once featured stream characteristics prior to development and piping. As the swale has been hydrologically disconnected by the roadway and pipe, it was assessed as two separate wetlands.

## **Water Resource Area (WRA)**

### *Protected Water Features*

Two wetlands totaling 0.05 acre were identified onsite. The wetlands extended offsite to north and south, respectively. Wetland, sample plot, and photo point locations are shown in Figure 2.

**Wetland 1** (0.006 acre onsite) was located in the bottom of the swale south of the existing driveway and extended offsite upslope to the south. It was fed by a stormwater pipe located offsite to the south (shown in Photo Point 1) and drained northeast into a pipe at the driveway. This pipe directed flows east into a ditch on the east side of Linn Lane, which then drained north into a drainage in the Sahallie Illahee Park (assumed to be the tributary to Barlow Creek). The wetland was bound by steep, near-vertical slopes; the eastern one was reinforced with riprap. It may have historically been a natural channel that was largely piped and ditched during the development of the neighborhood. The wetland was assessed as a headwater slope HGM class and a seasonally flooded palustrine scrub-shrub (PSSC) Cowardin class. It was vegetated primarily by Himalayan blackberry (FAC), which had recently been mown to facilitate access for fieldwork, with some sedge (*Carex* sp; FACW/OBL) and lady fern (*Athyrium cyclosorum*; FAC).

Soil samples met the Corps hydric soil indicator for redox dark surface (F6). Soils were very dark grayish brown (10 YR 3/2) in matrix color with many yellow-red redoximorphic concentrations occurring as soft masses and pore linings. Angular rock fragments were mixed in with the soil. The soil was very moist and water was observed trickling from the stormwater pipe upslope of the wetland despite the drier-than-normal weather conditions. Corps wetland hydrology indicators observed within the wetland included primary indicators of saturation (A3) and oxidized rhizospheres (C3).

**Wetland 2** (0.04 acre onsite) was located in the bottom of the broad swale north of the existing driveway. It extended offsite downslope to the north, draining through a culvert and into a drainage in the Sahallie Illahee Park. It was assumed sustained by lateral subsurface flow and groundwater discharge. It was defined by the driveway and Linn Lane embankments to the east and south, and steep (>25%) side slopes to the west. The wetland may have historically been



connected to Wetland 1 prior to development of the site and surrounding neighborhood. The wetland was assessed as a headwater slope HGM class and a seasonally flooded palustrine emergent (PEMC) Cowardin class. It was vegetated primarily by mown turfgrasses such as tall fescue (*Schedonorus arundinaceus*; FAC) and velvetgrass (*Holcus lanatus*; FAC), along with willowherb (*Epilobium ciliatum*; FACW), Canada thistle (*Cirsium arvense*; FAC), coastal hedgenettle (*Stachys chamissonis*; FACW), and Himalayan blackberry. A red osier dogwood thicket (*Cornus sericea*; FACW) was present along the northern boundary of the site.

Soil samples met the Corps hydric soil indicator for redox dark surface. Soils were very dark grayish brown in matrix color with common yellow-red redoximorphic concentrations occurring as soft masses. The soil was moist compared to the very dry, crumbly characteristics of the soil on the swale side slopes, and secondary Corps wetland hydrology indicators were present, including geomorphic position (D2) and FAC-Neutral Test (D5). Soil saturation was present in the lower portion of the wetland offsite within the park.

### *Wetland Buffer*

Slopes adjacent to the wetlands were generally greater than 25% with a distinct top slope as shown in the topographical survey of the property prepared by Love Land Surveying, Inc (Appendix C) and Figure 2. According to Table 32-2 of the CDC, the required width of the Water Resource Area for a wetland within a ravine (Item B), *the width of the WRA extends from the water resource to the top of the slope (30-foot minimum), plus an additional 50 feet. The 50-foot distance may be reduced to 25 feet if a geotechnical study by a licensed engineer or similar accredited professional demonstrates that the slope is stable and not prone to erosion.* The applicant has provided a geotechnical study showing demonstrating slope stability (Appendix D) and the WRA is proposed to extend 25 feet from the break in slope for Wetland 2. For Wetland 1, the top of the steep slope/ravine is within ten or so feet of the wetland boundary, so a WRA width of 65 feet was applied. Total WRA area within the site totals 0.43 acre or 18,624 sq. ft. Together with the 0.05 acre of wetland, WRA covers nearly 70% of the 0.70-acre parcel.

Vegetation within the WRA consisted largely of mown turfgrasses, recently cleared Himalayan blackberry, and some ornamental shrubs and trees around the existing home. Red osier dogwood was present along the northern boundary of the property. The WRA also contains existing impervious developed areas, including the access road and parking/turnaround areas, as well as portions of the home. Overall, the wetland buffer is low-functioning and degraded, providing little protection to the water resource.

## **Proposed Project**

The applicant proposes the replacement of the existing home with a two-story home, including deck, improved parking area/turnaround, and stormwater facility (Site plan shown in Appendix B). It utilizes the exiting development where possible. The access drive will be widened from 9-12 ft. wide to 15 ft. wide. The rationale for widening the road beyond the minimum required 12 ft. is to allow pedestrian access as well as emergency vehicle access as the road is currently approximately 5-6 ft above grade where it crosses the wetland swales. The road will need to be wider than 12 ft. to allow emergency personnel to walk and carry equipment or assist people around the vehicle. The access drive will be supported by retaining walls on either side to

prevent slope failure of the steep embankments. The retaining walls will be placed within 10 feet of the wetland boundaries. A portion of the home and deck will overhang the WRA, supported by vertical columns. The deck will be at a height of 9.5-14 ft. above the surrounding grade, while the roof overhang will be 21-26 ft. above grade. At this height, sunlight and rainfall will be able to penetrate the area enough to support low-light vegetation, such as that which grows beneath a forest canopy. No impacts to the wetlands are proposed.

The applicant requests approval of reduction of the WRA under the Alternative Review Process per Section 32.080 based on the proposed mitigation plan which shall be, at minimum, qualitatively equal, in terms of maintaining the level of functions allowed by the WRA standards of CDC 32.060(D). Currently, the WRA is significantly degraded, vegetated primarily by nonnative turfgrasses and weedy forbs, along with invasive Himalayan blackberry and Canada thistle.

## **Approval Criteria**

### ***32.080 Approval Criteria (Alternate Review Process)***

*Applications reviewed under the alternate review process shall meet the following approval criteria:*

*A. The proposed WRA shall be, at minimum, qualitatively equal, in terms of maintaining the level of functions allowed by the WRA standards of CDC 32.060(D).*

As described further in this report (Table 1), the existing WRA, while very wide (100-150 feet from the delineated boundary of the water resources in some areas due to the steep grade of adjacent slopes), is low functioning, serving as residential yard dominated by mown nonnative turfgrass and weedy forbs along with invasive Himalayan blackberry and Canada thistle. It also contains existing development, including an access road and portions of the parking area and home which provide no protective function to the water resources, and may even adversely impact the function of the water resources by contributing untreated stormwater runoff and pollutants. The applicant proposes to reduce the WRA to 65 ft. in width and remove the existing development (access road, parking area, and residence) from it, for a proposed WRA buffer of 0.25-acre. A 65-foot width was chosen as an appropriate width because it corresponds with the base WRA width for a wetland in the City of West Linn. Other local metropolitan Portland districts, including Clean Water Service, City of Happy Valley, and Clackamas County regulate a base wetland buffer width of 50 feet, and while the basis for these different base widths is unknown, the applicant chooses to comply with the minimum City of West Linn standard. The slopes adjacent to the wetland have been demonstrated as stable according to a geotechnical study (Appendix D) and a WRA that extends 25 ft. beyond the top of slope, covering 0.43 acre of the 0.70-acre site (61%), in its current degraded condition, is unnecessary to protect the water resource. The proposed project will result in 2,216 sq. ft. of encroachment into the proposed 65-foot WRA, including the access road widening and roof/deck overhang along the western margin of the WRA. A stormwater facility is proposed to retain and treat stormwater runoff from the development and prevent discharge of untreated runoff into the wetland. The applicant proposes to mitigate for 2,216 sq. ft. of encroachments into the 65-foot WRA via enhancement of 2,216 sq. ft. within the remaining 0.20-acre WRA currently in degraded condition. The applicant also proposes to restore the 806 sq. ft. of roof/deck overhang that encroaches into the 65-foot WRA with native forest understory groundcover plants. The mitigation plan for the WRA will improve

hydrological, water quality, and habitat functions including stream flow moderation, sediment and pollution control, providing organic material sources, and wildlife habitat. Enhancing the WRA will also provide protection of the wetlands from the proposed development. Existing native vegetation along the northern site boundary (red osier dogwood thicket) will be preserved and maintained as is; the remaining WRA will be landscaped and maintained according to Section 32.040 (A). The proposed WRA shall be, at minimum, qualitatively equal in terms of maintaining the level of functions allowed by the WRA standards of CDC 32.060(D) and is anticipated to be superior with the addition of native plantings and appropriate stormwater management and treatment.

*B. If a WRA is already significantly degraded (e.g., native forest and ground cover have been removed or the site dominated by invasive plants, debris, or development), the approval authority may allow a reduced WRA in exchange for mitigation, if:*

- 1. The proposed reduction in WRA width, coupled with the proposed mitigation, would result in better performance of functions than the standard WRA without such mitigation. The approval authority shall make this determination based on the applicant's proposed mitigation plan and a comparative analysis of ecological functions under existing and enhanced conditions (see Table 32-4).*

As described in this report and demonstrated below in Table 1, the existing WRA is degraded, dominated by non-native and invasive species, including turfgrasses, Himalayan blackberry and Canada thistle. Stormwater runoff from steep slopes and development above is unmitigated. The proposed WRA will be enhanced by of removal of invasive species and planting of native trees, shrubs, and groundcover along the wetland boundaries to significantly improve ecological functions. The proposed WRA will result in higher functions than the larger WRA without mitigation. Additionally, 806 sq. ft. of area beneath the proposed home and deck overhang, while technically considered an encroachment according to Table 32-1 of the CDC, will be restored with native plantings and should provide further benefit to the WRA. The height of the proposed overhang above the surrounding grade will still allow sunlight and rainfall to access the area and thus can be planted with species adapted to lower-light conditions, such as those which grow under a forest canopy. Table 1 below presents existing and enhanced WRA ecological functions per Table 32-4.

Table 1. Ecological Functions Comparison per Table 32-4

<b>Ecological Functions</b>	<b>WRA existing conditions</b>	<b>WRA enhanced conditions</b>
Stream flow moderation and/or water storage	No dense or woody vegetation or fallen trees are present to slow velocity of stormwater. Both wetlands are moderately sloped toward the tributary to Barlow Creek north of the site, and Wetland 1 is piped into a ditch which routes surface flows directly into the	Planting of native woody vegetation and groundcover will slow stormwater runoff and increase infiltration and sequestration of pollutants, protecting the wetlands and moderating streamflow for the Barlow Creek tributary located

	tributary. Together with the very steep slopes above the wetlands, stormwater is quickly routed through the wetlands and into the tributary below with little opportunity for retention or infiltration.	immediately downslope of the site.
Sediment or pollution control	With steep slopes and only mown turfgrasses and weedy forbs as vegetation cover, the WRA is unable to sequester sediment or pollutants from reaching downstream.	Increased vegetation, including woody species, will increase the WRA's capacity and opportunity to filter nutrients and retain sediments.
Bank stabilization	Low stream flow moderation and/or water storage function (see above) can contribute to bank erosion and channel downcutting downstream.	Increased vegetation cover will moderate velocity of stormwater, increase retention and contribute to downstream bank stabilization.
Large wood recruitment for a fish bearing section of stream	The tributary is not a fish bearing stream, though wood recruitment potential would be improved.	No change.
Organic material sources	The mown turfgrass vegetation cover provides little organic matter for the wetland/drainage system.	Planting diverse native vegetation community including woody species will increase organic material sources throughout the WRA.
Shade (water temperature moderation) and microclimate	The water resource is not currently shaded. The WRA is vegetated by mown turfgrasses	Tree and shrub planting will provide shade sources adjacent to the wetland, cooling surface waters that drain into the tributary below.
Stream flow that sustains in-stream and adjacent habitats	The wetland is seasonally inundated/saturated	Seasonal saturation/inundation will be maintained. No hydrological impacts anticipated.
Other terrestrial habitat	Forested areas within 100-300 feet of the water resource are not contiguous. Areas immediately adjacent to the water resource have only nonnative and invasive herbaceous cover.	Mitigation of the WRA will augment existing forested natural area within 100-300 feet of the water resource (Sahallie Illahee Park).

2. *The mitigation project shall include all of the following components as applicable. It may also include other forms of mitigation (mitigation) deemed appropriate by the approval authority.*

- a. Removal of invasive vegetation.*
- b. Planting native, non-invasive plants (at minimum, consistent with CDC 32.100) that provide improved filtration of sediment, excess nutrients, and pollutants. The amount of mitigation (mitigation) shall meet or exceed the standards of CDC 32.090(C).*
- c. Providing permanent improvements to the site hydrology that would improve water resource functions.*
- d. Substantial improvements to the aquatic and/or terrestrial habitat of the WRA.*

The mitigation plan shall consist of removal of invasive species and planting of a diverse assemblage of native trees, shrubs, and groundcover species to improve hydrological and water quality functions including slowing runoff and filtration of sediment, excess nutrients, and pollutants. Terrestrial habitat of the onsite water resources will be improved by providing cover, nesting or burrowing sites, and food availability and type. Proposed total mitigation area, which includes both enhancement of existing degraded WRA and post-construction restoration of disturbed WRA is 3,022 sq. ft. which exceeds the standards of CDC 32.090(C).

*C. Identify and discuss site design and methods of development as they relate to WRA functions.*

Site design utilized two-story development and incorporated the existing development footprint to maximize the available development footprint while avoiding steep, hazardous slopes to the west and minimizing impacts to the proposed reduced WRA. Impacts to the reduced WRA will include widening of the access driveway from 9-12 ft. wide to 15 ft. wide to allow emergency vehicle as well as pedestrian access (personnel will be able to walk around the vehicle on the roadway which is approximately 5-6 ft above grade where it crosses the wetland swales) and turnaround, retaining walls to support the driveway embankment and prevent slope failure, and the roof and deck overhang. The overhang areas are well above the surrounding grade (the deck will be at a height of 9.5-14 ft. above the surrounding grade, while the roof overhang will be 21-26 ft. above grade) which will allow rain and sunlight to penetrate and support vegetation growth. This area will be restored with native forest understory plantings following construction. The WRA mitigation plan will protect the water resource from the development as well as improve hydrological, water quality, and wildlife habitat functions to both the onsite water resource and the water resource immediately downslope (tributary to Barlow Creek). The existing WRA is degraded, vegetated primarily with mown, nonnative turfgrasses and invasive species.

*D. Address the approval criteria of CDC 32.060, with the exception of CDC 32.060(D).*

Applicable approval criteria addressed below.

*No application for development on property containing a WRA shall be approved unless the approval authority finds that the proposed development is consistent with the following approval criteria, or can satisfy the criteria by conditions of approval:*

- A. *WRA protection/minimizing impacts.*
1. *Development shall be conducted in a manner that will avoid or, if avoidance is not possible, minimize adverse impact on WRAs.*
  2. *Mitigation and re-vegetation of disturbed WRAs shall be completed per CDC 32.090 and 32.100 respectively.*

Proposed development avoids impacts to the 65-foot WRA to the extent practicable. The access road widening is regarded as a necessity to allow appropriate emergency vehicle access and turnaround, with the associated retaining walls required to support the steep embankment which is a result of the constraining site topography. The home was placed as far west as site topography allowed (see geotechnical report included as Appendix D). Where the home does encroach into the WRA, its height above the surrounding grade will allow vegetation growth, preventing erosion or sedimentation of areas downslope. The applicant proposes to restore this area (806 sq. ft) with native forest understory groundcover plants that are well-adapted to low-light conditions. A stormwater facility will also be constructed to retain and treat stormwater runoff from the proposed project (currently, no stormwater facility is present) and prevent the discharge of untreated stormwater into the wetland. The applicant proposes mitigation of the WRA at a ratio of 1:1.4 between the wetland boundaries and the proposed project to provide the best protection of the wetland (3,022 sq. ft. of mitigation to 2,216 sq. ft. of impact). The mitigation plan meets the standards of CDC 32.090.

- B. *Storm water and storm water facilities.*
1. *Proposed developments shall be designed to maintain the existing WRAs and utilize them as the primary method of storm water conveyance through the project site unless:*
    - a. *The surface water management plan calls for alternate configurations (culverts, piping, etc.); or*
    - b. *Under CDC 32.070, the applicant demonstrates that the relocation of the water resource will not adversely impact the function of the WRA including, but not limited to, circumstances where the WRA is poorly defined or not clearly channelized. Re-vegetation, mitigation and/or mitigation of the re-aligned water resource shall be required as applicable.*
  2. *Public and private storm water detention, storm water treatment facilities and storm water outfall or energy dissipaters (e.g., rip rap) may encroach into the WRA if:*
    - a. *Accepted engineering practice requires it;*
    - b. *Encroachment on significant trees shall be avoided when possible, and any tree loss shall be consistent with the City's Tree Technical Manual and mitigated per CDC 32.090;*
    - c. *There shall be no direct outfall into the water resource, and any resulting outfall shall not have an erosive effect on the WRA or diminish the stability of slopes; and*
    - d. *There are no reasonable alternatives available.**A geotechnical report may be required to make the determination regarding slope stability.*

3. *Roadside storm water conveyance swales and ditches may be extended within rights-of-way located in a WRA. When possible, they shall be located along the side of the road furthest from the water resource. If the conveyance facility must be located along the side of the road closest to the water resource, it shall be located as close to the road/sidewalk as possible and include habitat friendly design features (treatment train, rain gardens, etc.).*
4. *Storm water detention and/or treatment facilities in the WRA shall be designed without permanent perimeter fencing and shall be landscaped with native vegetation.*
5. *Access to public storm water detention and/or treatment facilities shall be provided for maintenance purposes. Maintenance driveways shall be constructed to minimum width and use water permeable paving materials. Significant trees, including roots, shall not be disturbed to the degree possible. The encroachment and any tree loss shall be mitigated per CDC [32.090](#). There shall also be no adverse impacts upon the hydrologic conditions of the site.*

A stormwater management plan will be developed to meet City requirements.

- D. WRA width. Except for the exemptions in CDC [32.040](#), applications that are using the alternate review process of CDC [32.070](#), or as authorized by the approval authority consistent with the provisions of this chapter, all development is prohibited in the WRA as established in Table 32-2 below:*

Applicant is seeking to reduce the buffer width using the alternate review process of CDC 32.070.

- F. Roads, driveways and utilities.*
1. *New roads, driveways, or utilities shall avoid WRAs unless the applicant demonstrates that no other practical alternative exists. In that case, road design and construction techniques shall minimize impacts and disturbance to the WRA by the following methods:*
    - a. *New roads and utilities crossing riparian habitat areas or streams shall be aligned as close to perpendicular to the channel as possible.*
    - b. *Roads and driveways traversing WRAs shall be of the minimum width possible to comply with applicable road standards and protect public safety. The footprint of grading and site clearing to accommodate the road shall be minimized.*
    - c. *Road and utility crossings shall avoid, where possible:*
      - 1) *Salmonid spawning or rearing areas;*
      - 2) *Stands of mature conifer trees in riparian areas;*
      - 3) *Highly erodible soils;*
      - 4) *Landslide prone areas;*
      - 5) *Damage to, and fragmentation of, habitat; and*
      - 6) *Wetlands identified on the WRA Map.*

A 9-12-foot-wide access road currently traverses the WRA on an embankment that is 5-6 feet above grade. The applicant proposes to utilize the existing access road but widen it to 15 feet to allow emergency vehicle access, turnaround, and personnel to safely traverse the roadway. Retaining walls will be required to support the steep embankment. Impacts to the water resource will be avoided.

2. *Crossing of fish bearing streams and riparian corridors shall use bridges or arch-bottomless culverts or the equivalent that provides comparable fish protection, to allow passage of wildlife and fish and to retain the natural stream bed.*

No fish bearing streams are present onsite and no crossings are proposed. This criterion is not applicable.

3. *New utilities spanning fish bearing stream sections, riparian corridors, and wetlands shall be located on existing roads/bridges, elevated walkways, conduit, or other existing structures or installed underground via tunneling or boring at a depth that avoids tree roots and does not alter the hydrology sustaining the water resource, unless the applicant demonstrates that it is not physically possible or it is cost prohibitive. Bore pits associated with the crossings shall be restored upon project completion. Dry, intermittent streams may be crossed with open cuts during a time period approved by the City and any agency with jurisdiction.*

No new utilities shall span the WRA.

4. *No fill or excavation is allowed within the ordinary high water mark of a water resource, unless all necessary permits are obtained from the City, U.S. Army Corps of Engineers and Oregon Department of State Lands (DSL).*

No fill or excavation is proposed within the ordinary high water mark or within the boundaries of the wetlands.

5. *Crossings of fish bearing streams shall be aligned, whenever possible, to serve multiple properties and be designed to accommodate conduit for utility lines. The applicant shall, to the extent legally permissible, work with the City to provide for a street layout and crossing location that will minimize the need for additional stream crossings in the future to serve surrounding properties.*

No fish bearing streams are present onsite and no crossings are proposed.

### **32.090 MITIGATION PLAN**

*A. A mitigation plan shall only be required if development is proposed within a WRA (including development of a PDA). (Exempted activities of CDC 32.040 do not require mitigation unless specifically stated. Temporarily disturbed areas, including TDAs associated with exempted activities, do not require mitigation, just grade and soil restoration and re-vegetation.) The*



*mitigation plan shall satisfy all applicable provisions of CDC 32.100, Re-Vegetation Plan Requirements.*

*B. Mitigation shall take place in the following locations, according to the following priorities (subsections (B)(1) through (4) of this section):*

*1. On-site mitigation by restoring, creating, or enhancing WRAs.*

Mitigation is proposed onsite.

*C. Amount of mitigation.*

*1. The amount of mitigation shall be based on the square footage of the permanent disturbance area by the application. For every one square foot of non-PDA disturbed area, on-site mitigation shall require one square foot of WRA to be created, enhanced, or restored.*

*2. For every one square foot of PDA that is disturbed, on-site mitigation shall require one half a square foot of WRA vegetation to be created, enhanced, or restored.*

2,216 sq. ft. of permanent impacts to the 65-foot WRA are proposed. The applicant proposes enhancement mitigation of 2,216 sq. ft. of WRA adjacent to the wetland boundaries, as well as 806 sq. ft. of restoration mitigation beneath the encroaching roof/deck overhang for a total of 3,022 sq. ft. of mitigation to protect the water resource and downstream functions.

*E. A mitigation plan shall contain the following information:*

*1. A list of all responsible parties including, but not limited to, the owner, applicant, contractor, or other persons responsible for work on the development site.*

The applicant and owner are:

Kevin Janssen  
614 SE 52nd Avenue  
Portland, OR 97215

The applicant will provide contractor/designer and other responsible party contact information as it becomes available.

*2. A map showing where the specific adverse impacts will occur and where the mitigation activities will occur.*

Appendix B illustrates the proposed impacts to the 65-foot WRA. Figure 3 illustrates the proposed mitigation planting areas.

*3. A re-vegetation plan for the area(s) to be mitigated that meets the standards of CDC 32.100.*

See the response to CDC 32.100 below.

4. *An implementation schedule, including timeline for construction, mitigation, mitigation maintenance, monitoring, and reporting. All in-stream work in fish bearing streams shall be done in accordance with the Oregon Department of Fish and Wildlife.*

Mitigation shall occur after all approvals are met and in accordance with planting requirements outlined in 32.100. As per City of West Linn WRA protection requirements, 80% success is required for replanted areas. The mitigation planting site will be monitored and maintained for three years. If, after each year monitoring period, 80% survival has not been met, dead plants will be replaced up to the 80% success required. Monitoring reports shall be provided to document these activities. No work will be conducted in fish bearing streams and the in-stream work window is not applicable.

5. *Assurances shall be established to rectify any mitigation actions that are not successful within the first three years. This may include bonding or other surety.(Ord. 1623 § 1, 2014)*

The applicant can provide any necessary assurance based on coordination with City staff. We would propose that any bonding or surety be deferred based on the results of the ongoing monitoring, maintenance, and reporting requirements.

### **32.100 RE-VEGETATION PLAN REQUIREMENTS**

The mitigation planting plan will meet the mitigation requirements of CDC 32.090 and vegetative mitigation of CDC 32.080 including the following standards.

1. *All trees, shrubs and ground cover to be planted must be native plants selected from the Portland Plant List.*
2. *Plant size. Replacement trees must be at least one-half inch in caliper, measured at six inches above the ground level for field grown trees or above the soil line for container grown trees. Shrubs must be in at least a one-gallon container or the equivalent in ball and burlap and must be at least 12 inches in height.*
3. *Plant coverage.*
  - a. *Native trees and shrubs are required to be planted at a rate of five trees and 25 shrubs per every 500 square feet of disturbance area. Non-native sterile wheat grass may also be planted or seeded, in equal or lesser proportion to the native grasses or herbs.*
  - b. *Trees shall be planted between eight and 12 feet on center and shrubs shall be planted between four and five feet on center, or clustered in single species groups of no more than four plants, with each cluster planted between eight and 10 feet on center. When planting near existing trees, the dripline of the existing tree shall be the starting point for plant spacing measurements.*
4. *Plant diversity. Shrubs must consist of at least two different species. If 10 trees or more are planted, then no more than 50 percent of the trees may be of the same genus*
5. *Invasive vegetation. Invasive non-native or noxious vegetation must be removed within the mitigation area prior to planting.*
6. *Tree and shrub survival. A minimum survival rate of 80 percent of the trees and shrubs planted is expected by the third anniversary of the date that the mitigation planting is completed.*

7. *Monitoring and reporting. Monitoring of the mitigation site is the ongoing responsibility of the property owner. Plants that die must be replaced in kind.*
8. *To enhance survival of tree replacement and plantings, the following practices are required:*
  - a. *Mulching. Mulch new plantings a minimum of three inches in depth and 18 inches in diameter to retain moisture and discourage weed growth.*
  - b. *Irrigation. Water new plantings one inch per week between June 15th to October 15th, for the three years following planting.*
  - c. *Weed control. Remove, or control, non-native or noxious vegetation throughout maintenance period.*
  - d. *Planting season. Plant bare root trees between December 1st and February 28th, and potted plants between October 15th and April 30th.*
  - e. *Wildlife protection. Use plant sleeves or fencing to protect trees and shrubs against wildlife browsing and resulting damage to plants.*

### **WRA Mitigation Plan**

This WRA mitigation plan has been designed to meet the requirements of 32.100(A)1-8 as outlined above and described below. The applicant proposes enhancement mitigation of 2,216 sq. ft. the remaining 65-foot WRA along the boundaries of the wetland, in areas currently degraded and not vegetated by native species (red osier dogwood thicket is present along the northern boundary of the onsite WRA). The applicant also proposes to restore the 806 sq. ft. of roof/deck overhang that encroaches into the WRA with native forest understory groundcover plants. The plan is expected to improve functions of the WRA by removing invasive species and establishing a diverse assemblage of native trees and shrubs along the boundaries of the wetland and restoring the disturbed area of WRA beneath the home with native forest understory species. The functions expected to be enhanced include hydrological functions (slowing velocity of stormwater runoff), water quality functions (retention of sediment and nutrients), organic material recruitment, and riparian wildlife habitat quality.

### **Planting Plan**

The planting plan was developed according to 32.100 Revegetation requirements (Table 2). All plants were selected from the Portland Plant List. Plants selected for the planting area adjacent to the wetland boundaries (2,216 sq. ft.) are adapted to sun-part sun and seasonally wet-dry conditions. Plants selected for the planting area under the roof/deck overhang (806 sq. ft.) are groundcovers adapted to full shade, dry-moist conditions. The proposed quantities and sizing are according to the CDC requirements. 15 trees and 96 shrubs/woody groundcover plants will be installed in the WRA adjacent to the wetland boundaries. 30 shrubs and 68 groundcover plants will be installed in the WRA beneath the roof/deck overhang. All bare ground within the mitigation planting areas will be seeded with a native grass mix as shown below. Substitutions or additional plants are allowable, subject to price and availability, provided they are included on the native Portland Plant List, meet the stated type, spacing, and total quantities listed in the table below and are suited to sun and moisture conditions. The planting plan is subject to approval by the City.

Table 2. Planting Palette for WRA Mitigation Area (3,022 sq.ft.)

Species	Type	Minimum Size	Spacing	Quantity
<b>WRA Adjacent to Wetland Boundaries (2,216 sq. ft.)</b>				
Oregon ash <i>Fraxinus latifolia</i>	Tree	0.5” diam or 1 gal.	12’OC	6
Cascara <i>Rhamnus purshiana</i>	Tree	0.5” diam or 1 gal.	12’OC	9
Snowberry <i>Symphoricarpus albus</i>	Shrub	1 gal.	4-5’OC	24
Redosier dogwood <i>Cornus sericea</i>	Shrub	1 gal.	4-5’OC	24
Red flowering currant <i>Ribes sanguineum</i>	Shrub	1 gal.	4-5’OC	24
Kinnikinnick <i>Arctostaphylos uva-ursi</i>	Woody Ground cover	1 gal.	Clusters 10’ OC	24
*Sunmark Seeds native EC mix or equivalent	Ground cover	1 lb/1,000 sq. ft.		2.4 lbs
<b>WRA Beneath Roof/Deck Overhang (806 sq. ft.)</b>				
Salal <i>Gaultheria shallon</i>	Shrub	1 gal.	4-5’OC	15
Western swordfern <i>Polystichum munitum</i>	Ground cover	1 gal.	4-5’OC	15
Fringecup <i>Tellima grandiflora</i>	Ground cover	4”	2-3’OC	34
Inside-out flower <i>Vancouveria hexandra</i>	Ground cover	4”	2-3’OC	34
*Sunmark Seeds native EC mix or equivalent	Ground cover	1 lb/1,000 sq. ft.		0.8 lb

\*Seed mix includes California brome (*Bromus carinatus*), blue wildrye (*Elymus glaucus*), spike bentgrass (*Agrostis exarata*), native red fescue (*Festuca rubra rubra*), tufted hairgrass (*Deschampsia cespitosa*)

### Schedule and Maintenance Requirements


Bare root trees shall be planted between December 1st and February 28th, and potted plants shall be planted between October 15th and April 30<sup>th</sup>, following construction of the project.

Monitoring of the mitigation site is the ongoing responsibility of the property owner. Plants that die must be replaced in kind. In accordance with City requirements a minimum survival rate of 80 percent of the trees and shrubs planted is expected by the third anniversary of the date that the mitigation planting is completed.

To enhance survival of tree replacement and plantings, in accordance with Section 32.100 the following practices are required:

- Mulch new plantings a minimum of three inches in depth and 18 inches in diameter to retain moisture and discourage weed growth.
- Irrigation for new plantings shall be provided in the amount of one inch per week between June 15th to October 15th, for the three years following planting.
- Non-native or noxious vegetation shall be removed or controlled throughout maintenance period.
- Use plant sleeves or fencing to protect trees and shrubs against wildlife browsing and resulting damage to plants.
- Resources for plant substitutions are as follows:
  - Native plants from the Portland Plant List <https://www.portland.gov/bps/documents/portland-plant-list/download>
  - Portland Plant List Native Plants Condensed <https://backyardhabitats.org/wp-content/uploads/2021/01/Condensed-Portland-Plant-List-Plants-by-Condition.pdf>
  - Gardening with Oregon Native Plants West of the Cascades <https://extension.oregonstate.edu/catalog/pub/ec-1577-gardening-oregon-native-plants-west-cascades>

**FIGURE 1: LOCATION MAP**




Date: 10/5/2023

Data Source: ESRI, 2023; Clackamas County GIS Dept., 2023


Figure 1. Location Map

Linn Lane Project Site: S&A #3079



**FIGURE 2: EXISTING CONDITIONS**





Date: 11/8/2023

Data Source: ESRI, 2023; Clackamas County GIS Dept., 2023; DOGAMI, 2014

Figure 2: Existing Conditions

Linn Lane Project Site: S&A #3079

**FIGURE 3: PROPOSED WRA AND MITIGATION PLANTING AREAS**




Date: 11/9/2023

Data Source: ESRI, 2023; Clackamas County GIS Dept., 2023

Figure 3. Proposed WRA and Mitigation Planting Areas


Linn Lane Project Site: S&A #3079

**APPENDIX A. CITY OF WEST LINN WRA MAP**



# Water Resource Area (WRA) Map

**WATER RESOURCE AREA MAP DISCLAIMER**  
 The Water Resource Areas (WRA) map has interpretive value for general planning purposes only and is not satisfactory for making site-specific land use decisions. This map is to be used in conjunction with detailed written code, tables, and figures provided in Chapter 32 of the West Linn Community Development Code (CDC). The May 2014 WRA Map is intended to identify WRA water features (wetlands, streams, ephemeral streams, and riparian corridors). It is not intended to delineate the exact WRA boundaries or water feature alignment. That task will be carried out by staff in the course of site visits where the provisions of Table 32-2 in CDC Chapter 32 shall apply. Chapter 32 of the West Linn Community Development Code (CDC) is available at: <http://www.codepublishing.com/OR/WestLinn/CDC.html>. Any questions or clarifications regarding WRA's should be directed to the West Linn Planning Department. A copy of the WRA Map is available for public inspection in the Planning Director's office (Ord. 1623 § 1, 2014)



Map Developed by West Linn Planning Department and GIS

**MAP OVERLAYS:**  
 \*Streams, Pipe Segments, Other Open Ditches, and Significant Riparian Corridors  
 Map Source: "Significant Riparian Corridors West Linn Goal 5 Inventory, January 2007"  
 Map publication date: 1/2/2007.  
 Modified Streams and added Ephemeral Streams, April 2013, July 2013, September 2013

**\*\*Locally Significant Wetlands and Other Wetlands**  
 Map Source: "Local Wetland Inventory, West Linn Goal 5 Inventory, January 2005"  
 Map publication date: 6/5/2006.


**\*\*\*Taxlot Base Map provided by Clackamas County GIS, 2013**

**WETLANDS/GOAL 5 DISCLAIMER (DSL STANDARD):**  
 Information shown on this map is for planning purposes only and wetland information is subject to change. There may be unmapped wetlands subject to regulation and all wetland boundary mapping is approximate. In all cases, actual field conditions determine wetland boundaries. You are advised to contact the Oregon Division of State Lands and the U.S. Army Corps of Engineers with any regulatory questions.

This product is for informational purposes and may not have been prepared for, or be suitable for legal, engineering, or surveying purposes. Users of this information should review or consult the primary data and information sources to ascertain the usability of the information.

- Goal 5 Significant Riparian Corridors\***
- Significant Riparian Corridors
  - Streams
  - Ephemeral Stream
  - Piped Segments
  - Upper Stream Reach of Fish Inventory 2003/2004 Survey


- Goal 5 Wetland Inventory\*\***
- Locally Significant Wetlands, DSL 2005
  - Other Wetlands, DSL 2005
  - TA-05 Specific Wetland Identifier
  - Rivers & Ponds
  - West Linn City Limits
  - Taxlot Base Map\*\*\*



LOC: G:\PROJECTS\GIS\GOALS\_2006\SIGIPARIAN\SIGIPARIAN\_WETLANDS\_201406V6\_FINAL.MXD | KAH  
 VERSION 5 TO VERSION 6: REMOVED "PROPOSED" FROM MAP TITLE



**APPENDIX B. SITE PLAN**




PLOT PLAN

5494 LINN LN,  
WEST LINN, OR

SCALE: 1" = 20'

A RESIDENCE FOR: THE JANSSEN FAMILY

APPLICANT: ROBERT EASTON  
21520 LUPINE CT.  
WEST LINN, OR 97068  
(503) 866-8810



DISTURBANCE AREA (PERMANENT / PROPOSED)		1919 SQ. FT.
ROOF OVERLAP		237 SQ. FT.
RISE ZONE	REAR	20'
SETBACKS:	SIDE	15'
LOT AREA:		2938 SQ. FT.
ALLOWABLE COVERAGE:		10761 SQ. FT. (36%)
ACTUAL COVERAGE:		6180 SQ. FT. (21%)
ACTUAL FARE:		8399 SQ. FT. (28%)




12112 S NEW ERA RD  
OREGON CITY, OR 97045

(503)970-4257

General Notes and Disclaimers: These drawings have been prepared to meet generally accepted professional standards. However, local variations may require changes. Likewise, building code requirements vary with location and change from time to time. Before starting construction, the builder must review and be responsible for all details and dimensions, and ensure that these plans meet all current requirements in your area. It is also suggested that a local architect and/or engineer be retained to review and make any changes necessary to ensure that plans meet all requirements, and that you check with your local building department to see if a professional stamp is required on drawings filed for permit purposes. All applicable construction shall conform to the latest editions of either "Uniform Building Code" or the "BOCA Basic Building Code," or any other locally required code. Codes govern over drawings. Dimensions govern over scale. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

All ideas, arrangements, drawings, and plans set forth on this sheet are the original work product of, owned by, and are the property of Barclay Home Designs Inc. Use of this said work product is limited to a specified project of the purchaser, and for the construction of one building. Any use, reuse, or disclosure of said plans, reproductions, ideas, designs, and/or arrangements, other than by Barclay Home Designs Inc. is strictly prohibited by law without the written permission of Barclay Home Designs Inc. Contractors shall verify and be responsible for all dimensions and conditions on the job. This office must be notified of any variations and discrepancies of and from these drawings prior to work on the job.

JANSSEN





# GRADING PLAN

5494 LINN LN.  
WEST LINN, OR

SCALE: 1" = 20'

## A RESIDENCE FOR: THE JANSSEN FAMILY

APPLICANT: ROBERT EASTON  
21520 LUPINE CT.  
WEST LINN, OR 97068  
(503) 866-8810



TOTAL URA AREA: 13911 SQ. FT.	
DISTURBANCE AREA: 4179 SQ. FT.	
SETBACKS:	FRONT 70'
	REAR 20'
	SIDE 15'
LOT AREA:	
ALLOWABLE COVERAGE:	29318 SQ. FT. (25%)
ACTUAL COVERAGE:	10281 SQ. FT. (35%)
ALLOWABLE FAR:	13193 SQ. FT. (45%)
ACTUAL FAR:	6395 SQ. FT. (22%)



12112 S NEW ERA RD (503)970-4257  
OREGON CITY, OR 97045



**General Notes and Disclaimers:** These drawings have been prepared to meet generally accepted professional standards. However, local variations may require changes. Likewise, building code requirements vary with location and change from time to time. Before starting construction, the builder must review and be responsible for all details and dimensions, and ensure that these plans meet all current requirements in your area. It is also suggested that a local architect and/or engineer be retained to review and make any changes necessary to ensure that plans meet all requirements, and that you check with your local building department to see if a professional stamp is required on drawings filed for permit purposes. All applicable construction shall conform to the latest editions of either "Uniform Building Code" or the "BOCA Basic Building Code," or any other locally required code. Codes govern over drawings. Dimensions govern over scale. Verify all mechanical requirements before framing. Verify topographic and subsurface conditions, and adapt foundation plans accordingly.

All ideas, arrangements, drawings, and plans set forth on this sheet are the original work product of, owned by, and are the property of Barclay Home Designs Inc. Use of this said work product is limited to a specified project of the purchaser, and for the construction of one building. Any use, reuse, or disclosure of said plans, reproductions, ideas, designs, and/or arrangements, other than by Barclay Home Designs Inc. is strictly prohibited by law without the written permission of Barclay Home Designs Inc. Contractors shall verify and be responsible for all dimensions and conditions on the job. This office must be notified of any variations and discrepancies of and from these drawings prior to work on the job.

JANSSEN  
B




**APPENDIX C. SITE SURVEY**



SCALE: 1" = 20'

REGISTERED  
LAND SURVEYOR  
*Richard Love*  
OREGON  
RICHARD P. LOVE  
EXPIRES 12/31/2000

PROJECT: SITE PLAN AND TOPOGRAPHY MAP 2 IE E58D	
LOCATION: NW 1/4 OF SECTION 25, T.25S., R.1E., W.14 CITY OF WEST LINN, CLATSOP COUNTY, OREGON	
CLIENT: BOB EASTON	DATE: APRIL 4, 2008
JOB NUMBER: 06-4356	
LOVER LAND SURVEYS, INC. P.O. BOX 807 GLADSTONE, OR 97037 (503)-666-4915	



NOTES:  
CONTOUR INTERVALS ARE EVERY FOOT.  
THE VERTICAL DATUM IS BASED ON THE NATIONAL GEODETIC SURVEY DATUM OF 1988. THE POINT OF ADJUSTMENT IS LOCATED AT THE SOUTHWEST CORNER OF THE ROSSBORN BARGE ROAD. THE ELEVATION OF THIS POINT IS 143.40 FEET. THE ELEVATION OF THE POINT OF ADJUSTMENT IS 143.40 FEET. THE ELEVATION OF THE POINT OF ADJUSTMENT IS 143.40 FEET.  
THE TOTAL AREA OF THE SUBJECT TRACT IS 60,327 SQUARE FEET.  
THE TOTAL AREA WHICH HAS BETWEEN 0 AND 10% SLOPE IS 9,140 SQUARE FEET OR 31.10% OF THE TOTAL AREA.  
THE TOTAL AREA WHICH HAS BETWEEN 10 AND 20% SLOPE IS 6,277 SQUARE FEET OR 21.20% OF THE TOTAL AREA.  
THE TOTAL AREA WHICH HAS BETWEEN 20 AND 30% SLOPE IS 6,150 SQUARE FEET OR 21.07% OF THE TOTAL AREA.  
THE TOTAL AREA WHICH HAS MORE THAN 30% SLOPE IS 4,812 SQUARE FEET OR 16.30% OF THE TOTAL AREA.

**APPENDIX D. GEOTECHNICAL STUDY**



10110 SW Nimbus Avenue, Suite B-5  
Portland, Oregon 97223  
HGSIgeotech.com  
503.530.8076

March 3, 2023  
HGSI Project No. 23-3058

Jared Eck  
**Ledgewood Construction**  
PO Box 298  
Sherwood OR 97140

503.522.8700  
[jared@ledgewoodconstruction.net](mailto:jared@ledgewoodconstruction.net)

Via email with hard copies mailed on request

**Subject: Geotechnical Engineering Report and Slope Stability Evaluation  
Proposed Residential Development  
5494 Linn Lane  
West Linn, Oregon**

This report presents the results of a geotechnical engineering study conducted by Hardman Geotechnical Services Inc. (HGSI) for the proposed residential development at 5494 Linn Lane in West Linn, Oregon (Figure 1). The purpose of this study was to evaluate subsurface conditions and perform general reconnaissance at the site to provide geotechnical recommendations for future site development. This geotechnical study was performed in accordance with HGSI Proposal No. 23-770, dated January 27, 2023, and your subsequent authorization of our proposal and *General Conditions for Geotechnical Services*.

## **SITE DESCRIPTION AND PROPOSED DEVELOPMENT**

Available information indicates the property is approximately 0.67 acres and irregular in shape. The site is currently occupied by a single-family residence, reportedly constructed in 1955. The existing residence is single-story with attic and basement levels. The site slopes moderately to steeply down to the northeast.

It is to our understanding that the proposed construction will likely be in the general area of the existing home. We anticipate the new home will be of “daylight basement” construction to conform to existing topography. Although a grading plan was not received for this project, it is believed that moderate cuts and fills will be necessary due to site grades. Evaluation of slope stability for long term conditions as well as stability of temporary excavations needed to construct the home are addressed in this report.

## **REGIONAL GEOLOGY AND SEISMIC SETTING**

The subject site lies within the Portland Basin, a broad structural depression situated between the Coast Range on the west and the Cascade Range on the east. The Portland Basin is a northwest-southwest trending structural basin produced by broad regional down warping of the area. The Portland Basin is approximately 20 miles wide and 45 miles long and is filled with consolidated and unconsolidated sedimentary rocks of late Miocene, Pliocene and Pleistocene age.

March 3, 2023

HGSI Project No. 23-3058

Geologic maps indicate the subject site is underlain at an undetermined depth by Miocene age basalt of the Columbia River Basalt Group. The basalt underlying the subject site is typically gray to black, dense, fine-grained, low-olivine basalt; locally porphyritic; locally deeply weathered (Schlicker & Finlayson, 1979). Interflow zones between flows are typically vesicular, scoriaceous, and brecciated, and sometimes include sedimentary rocks. Schlicker & Finlayson (1979) designate the site area as having “Thin soils: Areas mapped as thin soils overlie hard bedrock at depths of 2 feet or less. Unit includes soil developed from basalt residuum, thin soil deposited on bedrock, and bare rock outcrop areas.”

At least three major seismic source zones capable of generating damaging earthquakes are known to exist in the region. These include the Portland Hills Fault Zone, Gales Creek-Newberg-Mt. Angel Structural Zone, and the Cascadia Subduction Zone. These potential earthquake source zones are included in the determination of seismic design values for structures, as presented in the *Seismic Design* section.

## **FIELD EXPLORATION**

### **Exploratory Hand Auger Borings**

On February 16, 2023 four hand auger borings, designated HA-1 to HA-4, were dug to depths of approximately 1.5 to 8 feet below ground surface (bgs) at the approximate locations shown on Figure 2. It should be noted that exploration locations were determined in the field by pacing or taping distances from apparent property corners and other site features. As such, the locations of the explorations should be considered approximate.

Explorations were conducted under the full-time observation of HGSI personnel. Soil samples were classified in the field and representative portions were placed in relatively air-tight plastic bags. These soil samples were then returned to the laboratory for further examination and laboratory testing. Pertinent information including soil sample depths, stratigraphy, soil engineering characteristics, and groundwater occurrence was recorded. Soils were classified in general accordance with the Unified Soil Classification System.

Summary hand auger boring logs are attached. The stratigraphic contacts shown on the individual logs represent the approximate boundaries between soil types. The actual transitions may be more gradual. The soil and groundwater conditions depicted are only for the specific dates and locations reported, and therefore, are not necessarily representative of other locations and times.

## **LABORATORY TESTING**

### **Moisture Content and Fines Content**

Moisture content determinations were made for selected samples, measured as the weight of water divided by the weight of dry soil, expressed as a percentage. Tests were performed for samples at HA-2 at a depth of 2 feet, HA-3 at depths of 3.5 and 8 feet, and HA-4 at a depth of 3 feet. Results of the moisture content testing, performed in general accordance with ASTM D2216 are present in Table 1 below.

In addition, fines content determinations were made for HA-2 at 2 feet, in accordance with ASTM C117-13. The soil sample was washed through a No. 200 sieve to determine the percentage of silt and clay (“fines”, defined as percentage passing the No. 200 sieve). It was determined that approximately 30% of the sample passed the No. 200 sieve indicating the soil sample is a silty sand (SM) material classified according to USCS. Test results are incorporated in the appropriate hand auger logs.

**Table 1. Moisture Content Test Results**

<b>Hand Auger</b>	<b>Sample Depth (Feet)</b>	<b>Moisture Content (%)</b>
HA-2	2.0	45.6
HA-3	3.5	29.4
HA-3	8.0	32.8
HA-4	3.0	35.6

## **SUBSURFACE CONDITIONS**

The following discussion is a summary of subsurface conditions encountered in our explorations. For more detailed information regarding subsurface conditions at specific exploration locations, refer to the attached exploration logs. Also, please note that subsurface conditions can vary between exploration locations, as discussed in the *Uncertainty and Limitations* section below.

### **Soil**

On-site soils consist of organic topsoil, native residual soil, and gravelly silts and clays interpreted as part of the Columbia River Basalt Group as described below.

***Organic Topsoil*** – At the surface of all hand augers, materials consisted of soft, brown topsoil. This layer was organic with thin roots and slight black mottling. The topsoil layer extended about 6 inches to 1-foot bgs in all hand auger locations.

***Native Residual Soil*** – Below topsoil in HA-2 through HA-4, our explorations encountered native residual soils. These soils were most likely formed as the result of heavy weathering of underlying basalt rock. This unit of residual soils was characterized by brown silt that tended to have higher moisture near the surface and increased in stiffness with depth. These characteristics along with the presence of mica and mottling were good indicators that the soils were native and may not have been disturbed other than surficial disturbance and weathering. This layer extended 2 to 3 feet bgs in the hand auger borings.

***Weathered Columbia River Basalt*** – Below the topsoil and native silt layers, material consisted of weathered Columbia River Basalt in all hand auger borings making excavation very difficult. This material consisted of silty sand and silty clay that was generally stiff to hard with gravels and basalt fragments. This layer extended from below the topsoil layer to 20 inches in HA-1 and 3 to 8 feet bgs in hand augers HA-2 through HA-4. Borings HA-1, HA-2 and HA-4 encountered refusal in this layer at depths of 1.6, 3.2 and 4.2 feet respectively; typically, on less weathered rock materials.

### **Groundwater**

Groundwater seepage was not encountered in the subsurface explorations conducted for this study, excavated to a maximum depth of 8.0 feet. Groundwater conditions may vary depending on the season, local subsurface conditions, changes in site utilization, and other factors. The groundwater conditions reported above are for the specific date and locations indicated, and therefore may not necessarily be indicative of other times and/or locations.

March 3, 2023

HGSI Project No. 23-3058

## **CONCLUSIONS AND RECOMMENDATIONS**

Results of this study indicate that the proposed development is geotechnically feasible, provided that the recommendations of this report are incorporated into the design and construction phases of the project. Included in this report is an evaluation of potential slope stability impacts to the proposed new structures. Recommendations are also presented below regarding site preparation and undocumented fill removal, engineered fill, wet weather earthwork, spread footing foundations, below-grade retaining walls, perimeter footing drains, seismic design, excavating conditions and utility trench backfill, and erosion control considerations.

### **Slope Stability and Landslide Hazard Evaluation**

For the purpose of evaluating slope stability, we reviewed published geologic and hazard mapping, reviewed regional site topography and LiDAR images, and performed a field reconnaissance. LiDAR, which stands for Light Detection and Ranging, is a remote sensing method that uses light in the form of a pulsed laser to measure ranges (variable distances) to the earth. This method can “see” through structures and tree cover to show the ground surface elevations without obstructions, a useful tool in imaging earth forms and identifying landslide topology.

Regional geologic mapping and the Oregon Department of Geology and Mineral Industries (DOGAMI) online landslide database (SLIDO, 2021) shows a large landslide complex that encompasses the site and dozens of other existing residences in the area (Figure 3a). The slide is mapped as a Rockslide Translational Landslide feature with “Moderate” (11-29%) confidence level. The slide feature is mapped as being pre-Historic (older than 150 years), and if present may have attained a state of equilibrium following the original land sliding. SLIDO indicates the depth of original sliding to be deep (estimated at 39 feet).

From site explorations and the geologic mapping, it appears that the site is in the oversteepened “headscarp” area of the ancient landslide. The body of the mapped ancient feature is northwest of the subject site (Figures 3a and 3b).

The DOGAMI Landslide Susceptibility mapping for Shallow and Deep Landslides was reviewed as part of this study. The area of the existing home and proposed facilities is mapped as having “High” susceptibility for shallow slides, less than 15 feet deep (Figure 3b). Steep slope areas above the homesite are mapped as having a “Moderate” susceptibility for shallow landsliding. The DOGAMI Susceptibility Mapping indicates the site and surrounding areas have “High” susceptibility for deep landslides, defined as extending greater than 15 feet below ground surface.

On the site itself, we did not observe evidence, either from surface reconnaissance or in the subsurface explorations, which would definitively indicate the presence of a landslide. Based on these considerations, we conclude an active landslide is most likely not present on or near the site. In either case, the presence of an ancient landslide or the lack thereof, is not indicative of a significant slope stability hazard to the site. In our opinion, a numeric slope stability analysis is not warranted.

A minimum footing-to-slope setback of 7 feet is recommended. The setback should be measured horizontally, from the face of the nearest slope to the outside edge of the footing. Where structures are located closer than the recommended setback distance, it may be necessary to deepen the footing to achieve the recommended setback. HGSI should observe foundation excavations prior to formwork and reinforcing steel placement, to verify footing-to-slope setbacks are adequate.

Storm water management systems (if any) should be constructed such that potential overflow is discharged in a controlled manner away from structures and slopes, and all systems should include an adequate factor of safety. During and following site development within sloped areas, surface runoff should be collected and

March 3, 2023

HGSI Project No. 23-3058

storm water should be discharged in a controlled manner. In no case should uncontrolled stormwater runoff be allowed to flow over slopes.

To our knowledge, the planned development does not involve any significant cuts or fills, other than the excavation needed for the planned development. Based on our observations and results of the slope stability evaluation, it is our opinion that no special design or construction provisions are needed to address slope issues on the site. Development of the site is not anticipated to have negatively impact slope stability of the site or adjacent properties. The project will be designed and constructed per current building codes, City of West Linn requirements, and the current standard-of-practice in geotechnical engineering. As such, it is our opinion that adequate slope stability factors of safety will be maintained for the design life of the proposed development, provided significant changes are not made to site topography or drainage conditions.

It should be noted that this evaluation is based on limited observation of surficial features, the subsurface explorations performed and review of available geologic literature. Deep subsurface explorations and quantification of slope stability factors of safety using numerical methods were beyond the scope of this study.

### **Site Preparation and Undocumented Fill Removal**

The areas of the site to be graded should first be cleared of vegetation and any loose debris; and debris from clearing should be removed from the site. We anticipate that the average depth of topsoil stripping will be about 12 inches over most of the site. The final depth of stripping removal may vary depending on local subsurface conditions and the contractor's methods and should be determined based on site observations after the initial stripping has been performed. Stripped organic soil and pavement sections should be stockpiled separately and only in designated areas or removed from the site and stripping operations should be observed and documented by HGSI. Existing subsurface structures (foundations, tile drains, old utility lines, septic leach fields, etc.) beneath areas of proposed structures and pavement should be removed and the excavations backfilled with engineered fill.

Undocumented fills were not encountered in any borings. There is potential for fills to be present on site in areas beyond our explorations. If encountered beneath proposed structures, pavements, or other settlement-sensitive improvements, undocumented fill should be removed down to firm inorganic native soils and the removal area backfilled with engineered fill. HGSI should observe removal excavations (if any) prior to fill placement to verify that over excavations are adequate and an appropriate bearing stratum is exposed.

In construction areas, once stripping has been verified, the area should be ripped or tilled to a depth of 12 inches, moisture conditioned, and compacted in-place prior to the placement of engineered fill. Exposed subgrade soils should be evaluated by HGSI. For large areas, this evaluation is normally performed by proof-rolling the exposed subgrade with a fully loaded scraper or dump truck. For smaller areas where access is restricted, the subgrade should be evaluated by probing the soil with a steel probe. Soft/loose soils identified during subgrade preparation should be compacted to a firm and unyielding condition or over-excavated and replaced with engineered fill, as described below. The depth of overexcavation, if required, should be evaluated by HGSI at the time of construction.

### **Engineered Fill**

In general, we anticipate that non-organic soils will be suitable for use as engineered fill in dry weather conditions, provided they are properly moisture conditioned for compaction. Imported fill material must be approved by the geotechnical engineer prior to being imported to the site. Oversize material greater than 6 inches in size should not be used within 3 feet of foundation footings, and material greater than 12 inches in diameter should not be used in engineered fill.



March 3, 2023

HGSI Project No. 23-3058

Engineered fill should be compacted in horizontal lifts not exceeding 8 inches using standard compaction equipment. We recommend that engineered fill be compacted to at least 90 percent of the maximum dry density determined by ASTM D1557 (Modified Proctor) or equivalent. On-site soils may be wet or dry of optimum; therefore, we anticipate that moisture conditioning of native soil will be necessary for compaction operations.

Proper test frequency and earthwork documentation usually requires daily observation and testing during stripping, rough grading, and placement of engineered fill. Field density testing should conform to ASTM D2922 and D3017, or D1556. Engineered fill should be periodically observed and tested by HGSI. Typically, one density test is performed for at least every 2 vertical feet of fill placed or every 50 yd<sup>3</sup>, whichever requires more testing.

### **Wet Weather Earthwork**

The on-site soils are moisture sensitive and may be difficult to handle or traverse with construction equipment during periods of wet weather. Earthwork is typically most economical when performed under dry weather conditions. Earthwork performed during the wet-weather season will probably require expensive measures such as cement treatment or imported granular material to compact fill to the recommended engineering specifications. If earthwork is to be performed or fill is to be placed in wet weather or under wet conditions when soil moisture content is difficult to control, HGSI should be contacted for additional recommendations.

Under wet weather, the construction area will unavoidably become wet, and the condition of exposed fill and native soils will degrade. To limit the impacts of wet weather on the finished building pad surface, consideration may be given to placement of a crushed aggregate pad. Where used, we recommend the working pad be constructed using 1½”-0 crushed aggregate and should have minimum thickness of at least 12 inches. This thickness is considered adequate to support light construction traffic but will not be sufficient to support heavy traffic such as loaded dump trucks or other heavy rubber-tired equipment.

### **Spread Footing Foundations**

Conventional isolated or continuous spread footings may be used to support the proposed structure, provided they are founded on competent native soils, or compacted engineered fill placed directly upon the competent native soils. We recommend a maximum allowable bearing pressure of 2,000 pounds per square foot (psf) for designing spread footings bearing on undisturbed native soils or engineered fill. The recommended maximum allowable bearing pressure may be increased by a factor of 1.33 for short term transient conditions such as wind and seismic loading. Exterior footings should be founded at least 18 inches below the lowest adjacent finished grade. Minimum footing widths should be determined by the project engineer/architect in accordance with applicable design codes.

A footing-to-slope setback of 7 feet is recommended. The setback should be measured from the bottom, outside edge of the footing horizontally to the face of the nearest slope. If needed, foundations can be deepened to achieve the recommended footing-to-slope setback.

Assuming construction is accomplished as recommended herein, and for the foundation loads anticipated, we estimate total settlement of spread foundations of less than about 1 inch and differential settlement between two adjacent load-bearing components supported on competent soil of less than about ½ inch. We anticipate that most of the estimated settlement will occur during construction, as loads are applied.

Wind, earthquakes, and unbalanced earth loads will subject the proposed structure to lateral forces. Lateral forces on a structure will be resisted by a combination of sliding resistance of its base or footing on the underlying soil and passive earth pressure against the buried portions of the structure. For use in design, a

March 3, 2023

HGSI Project No. 23-3058

coefficient of friction of 0.5 may be assumed along the interface between the base of the footing and subgrade soils. Passive earth pressure for buried portions of structures may be calculated using an equivalent fluid weight of 390 pounds per cubic foot (pcf), assuming footings are cast against dense, natural soils or engineered fill. The recommended coefficient of friction and passive earth pressure values do not include a safety factor. The upper 12 inches of soil should be neglected in passive pressure computations unless it is protected by pavement or slabs on grade.

Footing excavations should be trimmed neat and the bottom of the excavation should be carefully prepared. Loose, wet or otherwise softened soil should be removed from the footing excavation prior to placing reinforcing steel bars. HGSI should observe foundation excavations prior to placing crushed rock, to verify that adequate bearing soils have been reached. Due to the high moisture sensitivity of on-site soils, construction during wet weather may require overexcavation of footings and backfill with compacted, crushed aggregate.

### **Below-Grade Structural Retaining Walls**

Lateral earth pressures against below-grade retaining walls will depend upon the inclination of any adjacent slopes, type of backfill, degree of wall restraint, method of backfill placement, degree of backfill compaction, drainage provisions, and magnitude and location of any adjacent surcharge loads. At-rest soil pressure is exerted on a retaining wall when it is restrained against rotation. In contrast, active soil pressure will be exerted on a wall if its top is allowed to rotate or yield a distance of roughly 0.001 times its height or greater. If the subject retaining walls will be free to rotate at the top, they should be designed for an active earth pressure equivalent to that generated by a fluid weighing 35 pcf for level backfill against the wall. For restrained walls, an at-rest equivalent fluid pressure of 54 pcf should be used in design, again assuming level backfill against the wall. These values assume that the recommended drainage provisions are incorporated, and hydrostatic pressures are not allowed to develop against the wall.

During a seismic event, lateral earth pressures acting on below-grade structural walls will increase by an incremental amount that corresponds to the earthquake loading. Based on the Mononobe-Okabe equation and peak horizontal accelerations appropriate for the site location, seismic loading should be modeled using the active or at-rest earth pressures recommended above, plus an incremental rectangular-shaped seismic load of magnitude  $5H$ , where  $H$  is the total height of the wall.

We assume relatively level ground surface below the base of the walls. As such, we recommend passive earth pressure of 390 pcf for use in design, assuming wall footings are cast against competent native soils or engineered fill. If the ground surface slopes down and away from the base of any of the walls, a lower passive earth pressure should be used and HGSI should be contacted for additional recommendations.

A coefficient of friction of 0.5 may be assumed along the interface between the base of the wall footing and native materials. The recommended coefficient of friction and passive earth pressure values do not include a safety factor, and an appropriate safety factor should be included in design. The upper 12 inches of soil should be neglected in passive pressure computations unless it is protected by pavement or slabs on grade.

The above recommendations for lateral earth pressures assume that the backfill behind the subsurface walls will consist of properly compacted structural fill, and no adjacent surcharge loading. If the walls will be subjected to the influence of surcharge loading within a horizontal distance equal to or less than the height of the wall, the walls should be designed for the additional horizontal pressure. For uniform surcharge pressures, a uniformly distributed lateral pressure of 0.3 times the surcharge pressure should be added.

The recommended equivalent fluid densities assume a free-draining condition behind the walls so that hydrostatic pressures do not build up. This can be accomplished by placing a 12-inch-wide zone of crushed

drain rock containing less than 5 percent fines against the walls. A 3-inch minimum diameter perforated, plastic drain pipe should be installed at the base of the walls and connected to a sump to remove water from the crushed drain rock zone. The drain pipe should be wrapped in filter fabric (Mirafi 140N or other as approved by the geotechnical engineer) to minimize clogging. The above drainage measures are intended to remove water from behind the wall to prevent hydrostatic pressures from building up. Additional drainage measures may be specified by the project architect or structural engineer, for damp-proofing or other reasons.

HGSI should be contacted during construction to verify subgrade strength in wall keyway excavations, to verify that backslope soils are in accordance with our assumptions, and to take density tests on the wall backfill materials.

**Perimeter Footing Drains**

We recommend the outside edge of perimeter footings be provided with a drainage system consisting of 4-inch minimum diameter perforated PVC pipe embedded in a minimum of 1 ft<sup>3</sup> per lineal foot of clean, crushed drain rock. The drain pipe and surrounding drain rock should be wrapped in non-woven geotextile (Mirafi 140N, or approved equivalent) to minimize the potential for clogging and/or ground loss due to piping. Water collected from the footing drains should be directed into the local storm drain system or other suitable outlet. A minimum 0.5 percent fall should be maintained throughout the drain and non-perforated pipe outlet. The footing drains should include clean-outs to allow periodic maintenance and inspection.

Down spouts and roof drains should collect roof water in a system separate from the footing drains in order to reduce the potential for clogging. Roof drain water should be directed to an appropriate discharge point well away from structural foundations. Grades should be sloped downward and away from buildings to reduce the potential for ponded water near structures.

**Seismic Design**

We recommend Site Class C (Very Dense Soil and Soft Rock) be used for design per the International Building Code, which references ASCE 7-16. Design values determined for the site using the ASCE 7-16 Hazard Tool are summarized on Table 2, for Risk Category II. A copy of the Hazard Tool output is attached at the end of this report.

**Table 2. Recommended Earthquake Ground Motion Parameters (ASCE 7-16)**

<b>Parameter</b>	<b>Value</b>
Location (Lat, Long), degrees	45.3688, -122.6333
Mapped Spectral Acceleration Values (MCE, Site Class B):	
Short Period, S <sub>s</sub>	0.845 g
1.0 Sec Period, S <sub>1</sub>	0.379 g
Design Values for <b>Site Class C</b> (Very Dense Soil and Soft Rock):	
Peak Ground Acceleration PG <sub>A</sub> M	0.457
F <sub>a</sub>	1.2
F <sub>v</sub>	1.5
SD <sub>s</sub> = 2/3 x F <sub>a</sub> x S <sub>s</sub>	0.676 g
SD <sub>1</sub> = 2/3 x F <sub>v</sub> x S <sub>1</sub>	0.379 g

March 3, 2023

HGSI Project No. 23-3058

Soil liquefaction is a phenomenon wherein saturated soil deposits temporarily lose strength and behave as a liquid in response to earthquake shaking. Soil liquefaction is generally limited to loose, granular soils located below the water table. Stiff soil material along with gravels and rock were encountered in our subsurface explorations to the maximum depth of exploration, 8 feet. Static groundwater beneath the site is several hundred feet bgs. Therefore, soils under the project site are considered not susceptible to liquefaction. It is our opinion that special design or construction measures are not required to mitigate the effects of liquefaction, given the expected height of the planned building.

### **Excavating Conditions and Utility Trench Backfill**

We anticipate that on-site soils can be excavated using conventional heavy equipment such as trackhoes. Hand auger boring HA-1, HA-2 and HA-4 met refusal at 20 inches, 38 inches, and 50 inches bgs respectively, on gravels and basalt rock. It is likely that these boulders can be removed using large excavator equipment. The contractor should be prepared to excavate and dispose of oversize boulders where encountered.

Perched groundwater conditions often occur over fine-grained native deposits, particularly during the wet season. If encountered, the contractor should be prepared to implement an appropriate dewatering system for installation of the utilities. At this time, we anticipate that dewatering systems consisting of ditches, sumps and pumps would be adequate for control of groundwater where encountered during construction conducted during the dry season. Regardless of the dewatering system used, it should be installed and operated such that in-place soils are prevented from being removed along with the groundwater.

Vibrations created by traffic and construction equipment may cause some caving and raveling of excavation walls. In such an event, lateral support for the excavation walls should be provided by the contractor to prevent loss of ground support and possible distress to existing or previously constructed structural improvements.

Utility trench backfill should consist of  $\frac{3}{4}$ "-0 crushed rock, compacted to at least 90% of the maximum dry density obtained by Modified Proctor (ASTM D1557) or equivalent. Initial backfill lift thicknesses for a  $\frac{3}{4}$ "-0" crushed aggregate base may need to be as great as 4 feet to reduce the risk of flattening underlying flexible pipe. Subsequent lift thickness should not exceed 1 foot. If imported granular fill material is used, then the lifts for large vibrating plate-compaction equipment (e.g. hoe compactor attachments) may be up to 2 feet, provided that proper compaction is being achieved and each lift is tested. Use of large vibrating compaction equipment should be carefully monitored near existing structures and improvements due to the potential for vibration-induced damage.

Adequate density testing should be performed during construction to verify that the recommended relative compaction is achieved. Typically, one density test is taken for every 4 vertical feet of backfill on each 200-lineal-foot section of trench.

### **Erosion Control Considerations**

Results of our subsurface exploration did not indicate the presence of soils considered unusually susceptible to erosion. The primary erosion hazard will occur during construction in areas where vegetation has been removed, particularly during wet weather. Erosion during construction can be minimized by implementing the project erosion control plan, which should include judicious use of bio-bags, silt fences, or other appropriate technology. Where used, erosion control devices should be in place and remain in place throughout site preparation and construction.

Erosion and sedimentation of exposed soils can also be minimized by quickly re-vegetating exposed areas of soil, and by staging construction such that large areas of the project site are not denuded and exposed at the

same time. Areas of exposed soil requiring immediate and/or temporary protection against exposure should be covered with either mulch or erosion control netting/blankets.

### UNCERTAINTIES AND LIMITATIONS

We have prepared this report for the owner and his/her consultants for use in design of this project only. This report should not be construed as a warranty of the subsurface conditions. Experience has shown that soil and groundwater conditions can vary significantly over small distances. Inconsistent conditions can occur between explorations that may not be detected by a geotechnical study. If, during future site operations, subsurface conditions are encountered which vary appreciably from those described herein, HGSI should be notified for review of the recommendations of this report, and revision of such if necessary.

Sufficient geotechnical monitoring, testing and consultation should be provided during construction to confirm that the conditions encountered are consistent with those indicated by explorations. Recommendations for design changes will be provided should conditions revealed during construction differ from those anticipated, and to verify that the geotechnical aspects of construction comply with the contract plans and specifications.

Within the limitations of scope, schedule and budget, HGSI executed these services in accordance with generally accepted professional principles and practices in the field of geotechnical engineering at the time the report was prepared. No warranty, expressed or implied, is made. The scope of our work did not include environmental assessments or evaluations regarding the presence or absence of wetlands or hazardous or toxic substances in the soil, surface water, or groundwater at this site.




We appreciate this opportunity to be of service.

Sincerely,

**HARDMAN GEOTECHNICAL SERVICES INC.**


Ashlyn Kashima, E.I.T.  
Engineering Staff



RENEWS: 06/30/23

Scott L. Hardman, P.E., G.E.  
Geotechnical Engineer

- Attachments:
- References
  - Figure 1 – Vicinity Map
  - Figure 2 – Site Plan
  - Figure 3a – Bare Earth LiDAR and Landslides
  - Figure 3b – Landslide Susceptibility
  - Log of Hand Auger Borings (4 Sheets)
  - ASCE 7-16 Seismic Parameters (1 Sheet)



**REFERENCES**

Madin, I.P., 1990, Earthquake hazard geology maps of the Portland metropolitan area, Oregon: Oregon Department of Geology and Mineral Industries Open-File Report 0-90-2, scale 1:24,000, 22 p.

Oregon Department of Geology and Mineral Industries SLIDO, Version 4.4, updated October 29, 2021. <https://gis.dogami.oregon.gov/maps/slido/>


Schlicker, H.G. and Finlayson, C.T., 1979, Geology and Geologic Hazards of northwestern Clackamas County, Oregon: Oregon Department of Geology and Mineral Industries, Bulletin No. 99, 79 p., scale 1:24,000.

Snyder, D.T., 2008, Estimated Depth to Ground Water and Configuration of the Water Table in the Portland, Oregon Area: U.S. Geological Survey Scientific Investigations Report 2008-5059, 41 p., 3 plates.



**HARDMAN  
GEOTECHNICAL  
SERVICES INC**  
Practical, Cost-Effective  
Engineering Solutions

# VICINITY MAP




Project: 5494 Linn Lane West Linn, Oregon	Project No. 23-3058	FIGURE 1
--	---------------------	----------





**HARDMAN  
GEOTECHNICAL  
SERVICES INC.**  
Practical, Cost-Effective  
Engineering Solutions

# SITE MAP



## Legend

 Site Boundary

**HA-X**  
 Hand Auger Locations

Project: 5494 Linn Lane  
West Linn, Oregon


Project No. 23-3058

FIGURE 2






# BARE EARTH LiDAR & LANDSLIDES



<p>Project: 5494 Linn Lane West Linn, Oregon</p>	<p>Project No. 23-3058</p>	<p>FIGURE 3a</p>
--	----------------------------	------------------



# LANDSLIDE SUSCEPTIBILITY



Legend	Approximate Site Location
--------	---------------------------

Project: 5494 Linn Lane  
West Linn, Oregon

Project No. 23-3058

FIGURE 3b

# LOG OF HAND AUGER BORING

Project: 5494 Linn Lane  
West Linn, Oregon

Project No. 23-3058

Boring No. **HA - 1**

Depth (ft)	Pocket Penetrometer (tons/ft <sup>2</sup> )	Sample Interval	Sample Designation	Moisture Content (%)	Groundwater	Material Description
1						Moist, soft, brown, organic silt (OL), organic with thin roots [Topsoil] ----- Slightly moist, stiff/hard, brown with traces of orange and yellow, sandy silt mixture (ML) with bits of small gravel and weathered basalt fragments, scrapping from 10" to 1.5', 2" diameter black basalt rock at 1', soil color changed to a redish brown at 1.5 feet [Columbia River Basalt]
2						<i>Boring refusal on rock at 20 inches, no sample retained</i> <i>No groundwater or seepage encountered</i> <i>No caving of side walls</i>
3						
4						
5						
6						
7						
8						
9						
10						



**HARDMAN  
GEOTECHNIC,  
SERVICES INC**  
Practical, Cost-Effective  
Engineering Solutions

LEGEND



S-#



Soil Sample Depth  
Interval and Designation

Water Level at  
Time of Excavation

Date Bored: 2/16/2023

Logged By: AK

Surface Elevation:

# LOG OF HAND AUGER BORING

Project: 5494 Linn Lane  
West Linn, Oregon

Project No. 23-3058

Boring No. **HA - 2**

Depth (ft)	Pocket Penetrometer (tons/ft <sup>2</sup> )	Sample Interval	Sample Designation	Moisture Content (%)	Groundwater	Material Description
1						Moist, soft, brown, organic silt (OL), organic with thin roots, black mottling and orange staining at 9" [Topsoil]
2		☒	S-1	45.6		Slightly moist, slightly stiff, brown with traces of orange, sandy silt mixture (ML) with bits of small gravel and weathered basalt fragments, slightly micaceous [Native Residual Soil]
3						Slightly moist to moist, stiff/hard, brown with traces of orange, silty SAND (SM) with bits of small gravel, weathered soft basalt fragments and small sandstone [Columbia River Basalt] Sieve Wash: 30% of sample passed #200 sieve
4						<i>Boring refusal on rock at 38 inches, no sample retained No groundwater or seepage encountered No caving of sidewalls</i>
5						
6						
7						
8						
9						
10						



**HARDMAN  
GEOTECHNICAL  
SERVICES INC**  
Practical, Cost-Effective  
Engineering Solutions

LEGEND



S-#



Soil Sample Depth  
Interval and Designation

Water Level at  
Time of Excavation

Date Bored: 2/16/2023

Logged By: AK

Surface Elevation:


# LOG OF HAND AUGER BORING

Project: 5494 Linn Lane West Linn, Oregon	Project No. 23-3058	Boring No. <b>HA - 3</b>
--	---------------------	--------------------------

Depth (ft)	Pocket Penetrometer (tons/ft <sup>2</sup> )	Sample Interval	Sample Designation	Moisture Content (%)	Groundwater	Material Description
1						Moist, soft, brown, organic silt (OL), organic with thin roots, black mottling and orange staining at 9" [Topsoil]
2						Slightly moist, slightly stiff, brown, SILT (ML) with bits of small gravel and gray sandstone, slightly organic with roots, slightly micaceous, slight black mottles [Native Residual Soil]
3						Slightly moist, slightly stiff, orange/brown with red staining, silty SAND (SM) with bits of small gravel, slight black mottles, 2" rock at 2.5 feet [Columbia River Basalt]
4		☒	S-2	29.4		Slightly moist, stiff, brown with orange staining, silty CLAY with small gravels (CL), slight black mottles, purple and red staining at 5.5 feet [Columbia River Basalt]
5						
6						
7						
8		☒	S-3	32.8		
9						<i>Boring terminated at 8.0 feet</i> <i>No groundwater or seepage encountered</i> <i>No caving of sidewalls</i>
10						



LEGEND






Date Bored: 2/16/2023  
 Logged By: AK  
 Surface Elevation:

# LOG OF HAND AUGER BORING

Project: 5494 Linn Lane West Linn, Oregon	Project No. 23-3058	Boring No. <b>HA - 4</b>
--	---------------------	--------------------------

Depth (ft)	Pocket Penetrometer (tons/ft <sup>2</sup> )	Sample Interval	Sample Designation	Moisture Content (%)	Groundwater	Material Description
1						Moist, soft, brown, organic silt (OL), organic with thin roots, black mottling and orange staining at 9" [Topsoil]
2						Slightly moist, slightly stiff, brown, silt and clay mixture (ML) with bits of small gravel, slightly organic with roots, slightly micaceous, slight black mottles, scrapping on gravel and rock [Native Residual Soil]
3		☒	S-4	35.6		Slightly moist, slightly stiff to stiff, brown with orange staining, silty CLAY with small gravels (CL), slightly micaceous, scrapping on basalt [Columbia River Basalt]
4						
5						<i>Boring refusal on rock at 50 inches, no sample retained No groundwater or seepage encountered No caving of sidewalls</i>
6						
7						
8						
9						
10						

 <p><b>HARDMAN GEOTECHNICAL SERVICES INC</b> Practical, Cost-Effective Engineering Solutions</p>	<p style="text-align: center;">LEGEND</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  S-#         </div> <div style="text-align: center;">  </div> </div> <p style="font-size: small; text-align: center;">Soil Sample Depth Interval and Designation      Water Level at Time of Excavation</p>	<p>Date Bored: 2/16/2023</p> <p>Logged By: AK</p> <p>Surface Elevation:</p>
---	--	---

▲ This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

🔗 The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)


**ATC** Hazards by Location

**Search Information**


**Address:** 5494 Linn Ln, West Linn, OR 97068, USA  
**Coordinates:** 45.3688072, -122.633368  
**Elevation:** 558 ft  
**Timestamp:** 2023-02-20T21:48:00.928Z  
**Hazard Type:** Seismic  
**Reference Document:** ASCE7-16  
**Risk Category:** II  
**Site Class:** C



**MCER Horizontal Response Spectrum**



**Design Horizontal Response Spectrum**



**Basic Parameters**

Name	Value	Description
S <sub>S</sub>	0.845	MCE <sub>R</sub> ground motion (period=0.2s)
S <sub>1</sub>	0.379	MCE <sub>R</sub> ground motion (period=1.0s)
S <sub>MS</sub>	1.014	Site-modified spectral acceleration value
S <sub>M1</sub>	0.568	Site-modified spectral acceleration value
S <sub>DS</sub>	0.676	Numeric seismic design value at 0.2s SA
S <sub>D1</sub>	0.379	Numeric seismic design value at 1.0s SA

**Additional Information**

Name	Value	Description
SDC	D	Seismic design category
F <sub>a</sub>	1.2	Site amplification factor at 0.2s
F <sub>v</sub>	1.5	Site amplification factor at 1.0s
CR <sub>S</sub>	0.892	Coefficient of risk (0.2s)
CR <sub>1</sub>	0.867	Coefficient of risk (1.0s)
PGA	0.38	MCE <sub>G</sub> peak ground acceleration
F <sub>PGA</sub>	1.2	Site amplification factor at PGA
PGA <sub>M</sub>	0.457	Site modified peak ground acceleration
T <sub>L</sub>	16	Long-period transition period (s)
SsRT	0.845	Probabilistic risk-targeted ground motion (0.2s)
SsUH	0.948	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
S1RT	0.379	Probabilistic risk-targeted ground motion (1.0s)
S1UH	0.437	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
S1D	0.6	Factored deterministic acceleration value (1.0s)
PGAd	0.5	Factored deterministic acceleration value (PGA)

The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.

Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)

**Disclaimer**

Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

**APPENDIX E. SITE PHOTOGRAPHS**





Photo Point 1. From the driveway facing southwest toward Wetland 1. The stormwater pipe which discharges into the wetland is visible in the background (offsite).



Photo Point 1. From the driveway facing northeast toward Wetland 2 occupying the bottom of the steep-sided swale.



Photo Point 2. From the central portion of the site facing southeast toward the upper portion of Wetland 2 bound by the driveway and road embankments and steep slopes.



Photo Point 2. From the central portion of the site facing northeast toward the lower portion of Wetland 2 and redosier dogwood thicket at the site boundary.



Photo Point 2. From the central portion of the site facing northwest along the Wetland 2 side slope.



Photo Point 2. From the central portion of the site facing southwest toward the existing residence at the top of the slope.




Photo Point 3. From the northwestern site corner facing south along steep slope behind the existing residence.



Photo Point 3. From the northwestern site corner facing east toward the top of the slope.



Photo Point 3. From the northwestern site corner facing north

**APPENDIX F. WETLAND DETERMINATION FORMS**

**WETLAND DETERMINATION DATA FORM – Western Mountains, Valleys and Coast Region**

Project/Site: Linn Lane City/County: West Linn/Clackamas 7/10/2023  
 Applicant/Owner: Kevin Janssen State: OR Sampling Point: 1  
 Investigator(s): K Cartwright Section, Township, Range: T2S, R1E, Section 25BD  
 Landform (hillslope, terrace, etc.): hillslope Local relief (concave, convex, none): concave Slope (%): 3-5%  
 Subregion (LRR): Northwest Forests and Coast (LRR A) Lat: 45.368606 Long: -122.6331243 Datum:  
 Soil Map Unit Name: Cornelius silt loam NWI Classification: none  
 Are climatic / hydrologic conditions on the site typical for this time of year? Yes X No \_\_\_\_\_ (If no, explain in Remarks)  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" Present? Yes X No \_\_\_\_\_  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

**SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.**

Hydrophytic Vegetation Present? Yes <u>X</u> No _____ Hydric Soil Present? Yes <u>X</u> No _____ Wetland Hydrology Present? Yes <u>X</u> No _____	<b>Is the Sampled Area within a Wetland?</b> Yes <u>X</u> No _____
Remarks: Plot placed in swale bottom at upper end. Blackberry was recently mown to facilitate access	

**VEGETATION**

	Absolute % Cover	Dominant Species?	Indicator Status?	
<b>Tree Stratum</b> (Use scientific names.)				<b>Dominance Test worksheet:</b> Number of Dominant Species That Are OBL, FACW, or FAC: <u>3</u> (A) Total Number of Dominant Species Across All Strata: <u>3</u> (B) Percent of Dominant Species That Are OBL, FACW, or FAC: <u>100%</u> (A/B)
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
Total Cover: <u>0</u>				
<b>Shrub Stratum</b>				<b>Prevalence Index Worksheet:</b> Total % Cover of: _____ Multiply by: _____ OBL species _____ x1 = <u>0</u> FACW species _____ x2 = <u>0</u> FAC species _____ x3 = <u>0</u> FACU species _____ x4 = <u>0</u> UPL species _____ x5 = <u>0</u> Column Totals: <u>0</u> (A) <u>0</u> (B) Prevalence Index = B/A = _____
1. <u>Rubus armeniacus</u>	100	Y	☐FAC☐	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
Total Cover: <u>100</u>				
<b>Herb Stratum</b>				<b>Hydrophytic Vegetation Indicators:</b> _____ 1 - Rapid Test for Hydrophytic Vegetation <u>X</u> 2 - Dominance Test is >50% _____ 3 - Prevalence Index is ≤3.0 <sup>1</sup> _____ 4 - Morphological Adaptation <sup>1</sup> (Provide supporting data in Remarks or on a separate sheet) _____ 5 - Wetland Non-Vascular Plants <sup>1</sup> _____ Problematic Hydrophytic Vegetation <sup>1</sup> (Explain)
1. <u>Carex sp</u>	5	Y	FACW	
2. <u>Athyrium cyclosorum</u>	15	Y	☐FAC☐	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
Total Cover: <u>20</u>				
<b>Woody Vine Stratum</b>				<b>Hydrophytic Vegetation Present?</b> Yes <u>X</u> No _____
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
Total Cover: <u>0</u>				
% Bare Ground in Herb Stratum <u>80</u> % Cover of Biotic Crust <u>0</u>				

Remarks: Litter cover

**Profile Description: (Describe to the depth needed to document the indicator or confirm the absence of indicators.)**

Depth (inches)	Matrix		Redox Features				Texture	Remarks
	Color (moist)	%	Color (moist)	%	Type <sup>1</sup>	Loc <sup>2</sup>		
0-6	10 YR 3/2	90					SiL	10% rock fragments
6-16	10 YR 3/2	82	7.5 YR 4/6	10	C	M	SiL	5% rock fragments
			7.5 YR 4/6	3	C	PL		

<sup>1</sup>Type: C=Concentration, D=Depletion, RM=Reduced Matrix, CS=Covered or Coated Sand Grains. <sup>2</sup>Location: PL=Pore Lining, M=Matrix.

Hydric Soil Indicators: (Applicable to all LRRs, unless otherwise noted.)		Indicators for Problematic Hydric Soils <sup>3</sup> :	
<input type="checkbox"/> Histosol (A1)	<input type="checkbox"/> Sandy Redox (S5)	<input type="checkbox"/> 2 cm Muck (A10)	
<input type="checkbox"/> Histic Epipedon (A2)	<input type="checkbox"/> Stripped Matrix (S6)	<input type="checkbox"/> Red Parent Material (TF2)	
<input type="checkbox"/> Black Histic (A3)	<input type="checkbox"/> Loamy Mucky Mineral (F1) (except MLRA 1)	<input type="checkbox"/> Other (Explain in Remarks)	
<input type="checkbox"/> Hydrogen Sulfide (A4)	<input type="checkbox"/> Loamy Gleyed Matrix (F2)		
<input type="checkbox"/> Depleted Below Dark Surface (A11)	<input type="checkbox"/> Depleted Matrix (F3)		
<input type="checkbox"/> Thick Dark Surface (A12)	<input checked="" type="checkbox"/> Redox Dark Surface (F6)		<sup>3</sup> Indicators of hydrophytic vegetation and wetland hydrology must be present, unless disturbed or problematic.
<input type="checkbox"/> Sandy Muck Mineral (S1)	<input type="checkbox"/> Depleted Dark Surface (F7)		
<input type="checkbox"/> Sandy gleyed Matrix (S4)	<input type="checkbox"/> Redox Depressions (F8)		

<b>Restrictive Layer (if present):</b>	<b>Hydric Soil Present?</b>	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Type: _____		
Depth (inches): _____		

Remarks:

**HYDROLOGY**

Wetland Hydrology Indicators:		Secondary Indicators (2 or more required)
Primary Indicators (any one indicator is sufficient)		
<input type="checkbox"/> Surface Water (A1)	<input type="checkbox"/> Water-Stained Leaves (B9) (except MLRA 1, 2, 4A and 4B)	<input type="checkbox"/> Water-Stained Leaves (B9) (MLRA 1, 2, 4A and 4B)
<input type="checkbox"/> High Water Table (A2)	<input type="checkbox"/> Salt Crust (B11)	<input type="checkbox"/> Drainage Patterns (B10)
<input checked="" type="checkbox"/> Saturation (A3)	<input type="checkbox"/> Aquatic Invertebrates (B13)	<input type="checkbox"/> Dry-Season Water Table (C2)
<input type="checkbox"/> Water Marks (B1)	<input type="checkbox"/> Hydrogen Sulfide Odor (C1)	<input type="checkbox"/> Saturation Visible on Aerial Imagery (C9)
<input type="checkbox"/> Sediment Deposits (B2)	<input checked="" type="checkbox"/> Oxidized Rhizospheres along Living Roots (C3)	<input type="checkbox"/> Geomorphic Position (D2)
<input type="checkbox"/> Drift Deposits (B3)	<input type="checkbox"/> Presence of Reduced Iron (C4)	<input type="checkbox"/> Shallow Aquitard (D3)
<input type="checkbox"/> Algal Mat or Crust (B4)	<input type="checkbox"/> Recent Iron Reduction in Plowed Soils (C6)	<input type="checkbox"/> FAC-Neutral Test (D5)
<input type="checkbox"/> Iron Deposits (B5)	<input type="checkbox"/> Stunted or Stressed Plants (D1) (LRR A)	<input type="checkbox"/> Raised Ant Mounds (D6) (LRR A)
<input type="checkbox"/> Surface Soil Cracks (B6)	<input type="checkbox"/> Other (Explain in Remarks)	<input type="checkbox"/> Frost-Heave Hummocks (D7)
<input type="checkbox"/> Inundation Visible on Aerial Imagery (B7)		
<input type="checkbox"/> Sparsely Vegetated Concave Surface (B8)		

<b>Field Observations:</b>	<b>Wetland Hydrology Present?</b>	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Surface Water Present? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Depth (inches): _____		
Water table Present? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Depth (inches): _____		
Saturation Present? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Depth (inches): <u>6</u>		
(includes capillary fringe)		

Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:

Remarks:



# WETLAND DETERMINATION DATA FORM – Western Mountains, Valleys and Coast Region

Project/Site: Linn Lane City/County: West Linn/Clackamas 7/10/2023  
 Applicant/Owner: Kevin Janssen State: OR Sampling Point: 2  
 Investigator(s): K Cartwright Section, Township, Range: T2S, R1E, Section 25BD  
 Landform (hillslope, terrace, etc.): hillslope Local relief (concave, convex, none): none Slope (%): 3-5%  
 Subregion (LRR): Northwest Forests and Coast (LRR A) Lat: 45.368624 Long: -122.6331358 Datum:  
 Soil Map Unit Name: Cornelius silt loam NWI Classification: none  
 Are climatic / hydrologic conditions on the site typical for this time of year? Yes X No \_\_\_\_\_ (If no, explain in Remarks)  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" Present? Yes X No \_\_\_\_\_  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

## SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.

Hydrophytic Vegetation Present? Yes _____ No <u>X</u> Hydric Soil Present? Yes _____ No <u>X</u> Wetland Hydrology Present? Yes _____ No <u>X</u>	<b>Is the Sampled Area within a Wetland?</b> Yes _____ No <u>X</u>
Remarks: Plot placed several feet above swale bottom. Blackberry recently mown to facilitate access	

## VEGETATION

Tree Stratum (Use scientific names.)	Absolute % Cover	Dominant Species?	Indicator Status?	Dominance Test worksheet:
1. _____	_____	_____	_____	Number of Dominant Species That Are OBL, FACW, or FAC: <u>1</u> (A)  Total Number of Dominant Species Across All Strata: <u>2</u> (B)  Percent of Dominant Species That Are OBL, FACW, or FAC: <u>50%</u> (A/B)
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
Total Cover: <u>0</u>				<b>Prevalence Index Worksheet:</b> Total % Cover of: _____ Multiply by: _____ OBL species _____ x1 = <u>0</u> FACW species _____ x2 = <u>0</u> FAC species _____ x3 = <u>0</u> FACU species _____ x4 = <u>0</u> UPL species _____ x5 = <u>0</u> Column Totals: <u>0</u> (A) <u>0</u> (B) Prevalence Index = B/A = _____
<b>Shrub Stratum</b>				
1. <u>Rubus armeniacus</u>	<u>70</u>	<u>Y</u>	<input type="checkbox"/> FAC <input type="checkbox"/>	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
Total Cover: <u>70</u>				
<b>Herb Stratum</b>				
1. <u>Rubus ursinus</u>	<u>30</u>	<u>Y</u>	<input type="checkbox"/> FACU <input type="checkbox"/>	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
Total Cover: <u>30</u>				
<b>Woody Vine Stratum</b>				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
Total Cover: <u>0</u>				
% Bare Ground in Herb Stratum <u>70</u> % Cover of Biotic Crust <u>0</u>				

- Hydrophytic Vegetation Indicators:**
- \_\_\_\_\_ 1 - Rapid Test for Hydrophytic Vegetation
  - \_\_\_\_\_ 2 - Dominance Test is >50%
  - \_\_\_\_\_ 3 - Prevalence Index is ≤3.0<sup>1</sup>
  - \_\_\_\_\_ 4 - Morphological Adaptation<sup>1</sup> (Provide supporting data in Remarks or on a separate sheet)
  - \_\_\_\_\_ 5 - Wetland Non-Vascular Plants<sup>1</sup>
  - \_\_\_\_\_ Problematic Hydrophytic Vegetation<sup>1</sup> (Explain)

<sup>1</sup>Indicators of hydric soil and wetland hydrology must be present, unless disturbed or problematic.

**Hydrophytic Vegetation Present?** Yes \_\_\_\_\_ No X

Remarks: Litter cover

**Profile Description: (Describe to the depth needed to document the indicator or confirm the absence of indicators.)**

Depth (inches)	Matrix		Redox Features				Texture	Remarks
	Color (moist)	%	Color (moist)	%	Type <sup>1</sup>	Loc <sup>2</sup>		
0-16	10 YR 3/3	95	10 YR 3/4	5	C	M	SiL	

<sup>1</sup>Type: C=Concentration, D=Depletion, RM=Reduced Matrix, CS=Covered or Coated Sand Grains. <sup>2</sup>Location: PL=Pore Lining, M=Matrix.

Hydric Soil Indicators: (Applicable to all LRRs, unless otherwise noted.)		Indicators for Problematic Hydric Soils <sup>3</sup> :	
<input type="checkbox"/> Histosol (A1)	<input type="checkbox"/> Sandy Redox (S5)	<input type="checkbox"/> 2 cm Muck (A10)	
<input type="checkbox"/> Histic Epipedon (A2)	<input type="checkbox"/> Stripped Matrix (S6)	<input type="checkbox"/> Red Parent Material (TF2)	
<input type="checkbox"/> Black Histic (A3)	<input type="checkbox"/> Loamy Mucky Mineral (F1) (except MLRA 1)	<input type="checkbox"/> Other (Explain in Remarks)	
<input type="checkbox"/> Hydrogen Sulfide (A4)	<input type="checkbox"/> Loamy Gleyed Matrix (F2)		
<input type="checkbox"/> Depleted Below Dark Surface (A11)	<input type="checkbox"/> Depleted Matrix (F3)		
<input type="checkbox"/> Thick Dark Surface (A12)	<input type="checkbox"/> Redox Dark Surface (F6)		
<input type="checkbox"/> Sandy Muck Mineral (S1)	<input type="checkbox"/> Depleted Dark Surface (F7)		
<input type="checkbox"/> Sandy gleyed Matrix (S4)	<input type="checkbox"/> Redox Depressions (F8)		

<sup>3</sup>Indicators of hydrophytic vegetation and wetland hydrology must be present, unless disturbed or problematic.

<b>Restrictive Layer (if present):</b> Type: _____ Depth (inches): _____	<b>Hydric Soil Present?</b> Yes _____ No <u>X</u>
--	---

Remarks:

**HYDROLOGY**

Wetland Hydrology Indicators:		Secondary Indicators (2 or more required)
Primary Indicators (any one indicator is sufficient)		
<input type="checkbox"/> Surface Water (A1)	<input type="checkbox"/> Water-Stained Leaves (B9) (except MLRA 1, 2, 4A and 4B)	<input type="checkbox"/> Water-Stained Leaves (B9) (MLRA 1, 2, 4A and 4B)
<input type="checkbox"/> High Water Table (A2)	<input type="checkbox"/> Salt Crust (B11)	<input type="checkbox"/> Drainage Patterns (B10)
<input type="checkbox"/> Saturation (A3)	<input type="checkbox"/> Aquatic Invertebrates (B13)	<input type="checkbox"/> Dry-Season Water Table (C2)
<input type="checkbox"/> Water Marks (B1)	<input type="checkbox"/> Hydrogen Sulfide Odor (C1)	<input type="checkbox"/> Saturation Visible on Aerial Imagery (C9)
<input type="checkbox"/> Sediment Deposits (B2)	<input type="checkbox"/> Oxidized Rhizospheres along Living Roots (C3)	<input type="checkbox"/> Geomorphic Position (D2)
<input type="checkbox"/> Drift Deposits (B3)	<input type="checkbox"/> Presence of Reduced Iron (C4)	<input type="checkbox"/> Shallow Aquitard (D3)
<input type="checkbox"/> Algal Mat or Crust (B4)	<input type="checkbox"/> Recent Iron Reduction in Plowed Soils (C6)	<input type="checkbox"/> FAC-Neutral Test (D5)
<input type="checkbox"/> Iron Deposits (B5)	<input type="checkbox"/> Stunted or Stressed Plants (D1) (LRR A)	<input type="checkbox"/> Raised Ant Mounds (D6) (LRR A)
<input type="checkbox"/> Surface Soil Cracks (B6)	<input type="checkbox"/> Other (Explain in Remarks)	<input type="checkbox"/> Frost-Heave Hummocks (D7)
<input type="checkbox"/> Inundation Visible on Aerial Imagery (B7)		
<input type="checkbox"/> Sparsely Vegetated Concave Surface (B8)		

<b>Field Observations:</b> Surface Water Present?    Yes _____ No <u>X</u> Depth (inches): _____ Water table Present?      Yes _____ No <u>X</u> Depth (inches): _____ Saturation Present?        Yes _____ No <u>X</u> Depth (inches): _____ (includes capillary fringe)	<b>Wetland Hydrology Present?</b> Yes _____ No <u>X</u>
---	---

Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:

Remarks:

**WETLAND DETERMINATION DATA FORM – Western Mountains, Valleys and Coast Region**

Project/Site: Linn Lane City/County: West Linn/Clackamas 7/10/2023  
 Applicant/Owner: Kevin Janssen State: OR Sampling Point: 3  
 Investigator(s): K Cartwright Section, Township, Range: T2S, R1E, Section 25BD  
 Landform (hillslope, terrace, etc.): hillslope Local relief (concave, convex, none): none Slope (%): 3-5%  
 Subregion (LRR): Northwest Forests and Coast (LRR A) Lat: 45.368784 Long: -122.6330003 Datum:  
 Soil Map Unit Name: Cornelius silt loam NWI Classification: none  
 Are climatic / hydrologic conditions on the site typical for this time of year? Yes X No \_\_\_\_\_ (If no, explain in Remarks)  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" Present? Yes X No \_\_\_\_\_  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

**SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.**

Hydrophytic Vegetation Present? Yes <u>X</u> No _____ Hydric Soil Present? Yes _____ No <u>X</u> Wetland Hydrology Present? Yes _____ No <u>X</u>	<b>Is the Sampled Area within a Wetland?</b> Yes _____ No <u>X</u>
Remarks: Plot placed several feet above swale bottom.	

**VEGETATION**

Tree Stratum (Use scientific names.)	Absolute % Cover	Dominant Species?	Indicator Status?	Dominance Test worksheet:
1. _____	_____	_____	_____	Number of Dominant Species That Are OBL, FACW, or FAC: <u>2</u> (A)  Total Number of Dominant Species Across All Strata: <u>3</u> (B)  Percent of Dominant Species That Are OBL, FACW, or FAC: <u>67%</u> (A/B)
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
Total Cover: <u>0</u>				<b>Prevalence Index Worksheet:</b> Total % Cover of: _____ Multiply by: _____ OBL species _____ x1 = <u>0</u> FACW species _____ x2 = <u>0</u> FAC species _____ x3 = <u>0</u> FACU species _____ x4 = <u>0</u> UPL species _____ x5 = <u>0</u> Column Totals: <u>0</u> (A) <u>0</u> (B) Prevalence Index = B/A = _____
<b>Shrub Stratum</b>				
1. <u>Rubus armeniacus</u>	10	Y	<input type="checkbox"/> FAC <input type="checkbox"/>	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
Total Cover: <u>10</u>				
<b>Herb Stratum</b>				
1. <u>Rubus ursinus</u>	20	Y	<input type="checkbox"/> FACU <input type="checkbox"/>	
2. <u>Schedonorus arundinaceus</u>	50	Y	<input type="checkbox"/> FAC <input type="checkbox"/>	
3. <u>Cirsium arvense</u>	5		<input type="checkbox"/> FAC <input type="checkbox"/>	
4. <u>Geum macrophyllum</u>	5		<input type="checkbox"/> FAC <input type="checkbox"/>	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
Total Cover: <u>80</u>				
<b>Woody Vine Stratum</b>				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
Total Cover: <u>0</u>				
% Bare Ground in Herb Stratum <u>20</u> % Cover of Biotic Crust <u>0</u>				<b>Hydrophytic Vegetation Indicators:</b> _____ 1 - Rapid Test for Hydrophytic Vegetation <u>X</u> _____ 2 - Dominance Test is >50% _____ 3 - Prevalence Index is ≤3.0 <sup>1</sup> _____ 4 - Morphological Adaptation <sup>1</sup> (Provide supporting data in Remarks or on a separate sheet) _____ 5 - Wetland Non-Vascular Plants <sup>1</sup> _____ Problematic Hydrophytic Vegetation <sup>1</sup> (Explain)
<b>Hydrophytic Vegetation Present?</b> Yes <u>X</u> No _____				

Remarks: Litter cover

**Profile Description: (Describe to the depth needed to document the indicator or confirm the absence of indicators.)**

Depth (inches)	Matrix		Redox Features				Texture	Remarks
	Color (moist)	%	Color (moist)	%	Type <sup>1</sup>	Loc <sup>2</sup>		
0-16	10 YR 3/3	95					SiL	5% rock fragments

<sup>1</sup>Type: C=Concentration, D=Depletion, RM=Reduced Matrix, CS=Covered or Coated Sand Grains. <sup>2</sup>Location: PL=Pore Lining, M=Matrix.

Hydric Soil Indicators: (Applicable to all LRRs, unless otherwise noted.)		Indicators for Problematic Hydric Soils <sup>3</sup> :	
<input type="checkbox"/> Histosol (A1)	<input type="checkbox"/> Sandy Redox (S5)	<input type="checkbox"/> 2 cm Muck (A10)	
<input type="checkbox"/> Histic Epipedon (A2)	<input type="checkbox"/> Stripped Matrix (S6)	<input type="checkbox"/> Red Parent Material (TF2)	
<input type="checkbox"/> Black Histic (A3)	<input type="checkbox"/> Loamy Mucky Mineral (F1) (except MLRA 1)	<input type="checkbox"/> Other (Explain in Remarks)	
<input type="checkbox"/> Hydrogen Sulfide (A4)	<input type="checkbox"/> Loamy Gleyed Matrix (F2)		
<input type="checkbox"/> Depleted Below Dark Surface (A11)	<input type="checkbox"/> Depleted Matrix (F3)		
<input type="checkbox"/> Thick Dark Surface (A12)	<input type="checkbox"/> Redox Dark Surface (F6)		
<input type="checkbox"/> Sandy Muck Mineral (S1)	<input type="checkbox"/> Depleted Dark Surface (F7)		
<input type="checkbox"/> Sandy gleyed Matrix (S4)	<input type="checkbox"/> Redox Depressions (F8)		

<sup>3</sup>Indicators of hydrophytic vegetation and wetland hydrology must be present, unless disturbed or problematic.

<b>Restrictive Layer (if present):</b> Type: _____ Depth (inches): _____	<b>Hydric Soil Present?</b> Yes _____ No <u>X</u>
--	---

Remarks:

**HYDROLOGY**

Wetland Hydrology Indicators:		Secondary Indicators (2 or more required)
<u>Primary Indicators (any one indicator is sufficient)</u>		
<input type="checkbox"/> Surface Water (A1)	<input type="checkbox"/> Water-Stained Leaves (B9) (except MLRA 1, 2, 4A and 4B)	<input type="checkbox"/> Water-Stained Leaves (B9) (MLRA 1, 2, 4A and 4B)
<input type="checkbox"/> High Water Table (A2)	<input type="checkbox"/> Salt Crust (B11)	<input type="checkbox"/> Drainage Patterns (B10)
<input type="checkbox"/> Saturation (A3)	<input type="checkbox"/> Aquatic Invertebrates (B13)	<input type="checkbox"/> Dry-Season Water Table (C2)
<input type="checkbox"/> Water Marks (B1)	<input type="checkbox"/> Hydrogen Sulfide Odor (C1)	<input type="checkbox"/> Saturation Visible on Aerial Imagery (C9)
<input type="checkbox"/> Sediment Deposits (B2)	<input type="checkbox"/> Oxidized Rhizospheres along Living Roots (C3)	<input type="checkbox"/> Geomorphic Position (D2)
<input type="checkbox"/> Drift Deposits (B3)	<input type="checkbox"/> Presence of Reduced Iron (C4)	<input type="checkbox"/> Shallow Aquitard (D3)
<input type="checkbox"/> Algal Mat or Crust (B4)	<input type="checkbox"/> Recent Iron Reduction in Plowed Soils (C6)	<input type="checkbox"/> FAC-Neutral Test (D5)
<input type="checkbox"/> Iron Deposits (B5)	<input type="checkbox"/> Stunted or Stressed Plants (D1) (LRR A)	<input type="checkbox"/> Raised Ant Mounds (D6) (LRR A)
<input type="checkbox"/> Surface Soil Cracks (B6)	<input type="checkbox"/> Other (Explain in Remarks)	<input type="checkbox"/> Frost-Heave Hummocks (D7)
<input type="checkbox"/> Inundation Visible on Aerial Imagery (B7)		
<input type="checkbox"/> Sparsely Vegetated Concave Surface (B8)		

<b>Field Observations:</b> Surface Water Present?    Yes _____ No <u>X</u> Depth (inches): _____ Water table Present?      Yes _____ No <u>X</u> Depth (inches): _____ Saturation Present?        Yes _____ No <u>X</u> Depth (inches): _____ (includes capillary fringe)	<b>Wetland Hydrology Present?</b> Yes _____ No <u>X</u>
---	---

Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:

Remarks:

**WETLAND DETERMINATION DATA FORM – Western Mountains, Valleys and Coast Region**

Project/Site: Linn Lane City/County: West Linn/Clackamas 7/10/2023  
 Applicant/Owner: Kevin Janssen State: OR Sampling Point: 4  
 Investigator(s): K Cartwright Section, Township, Range: T2S, R1E, Section 25BD  
 Landform (hillslope, terrace, etc.): hillslope Local relief (concave, convex, none): concave Slope (%): 3-5%  
 Subregion (LRR): Northwest Forests and Coast (LRR A) Lat: 45.368767 Long: -122.6329599 Datum:  
 Soil Map Unit Name: Cornelius silt loam NWI Classification: none  
 Are climatic / hydrologic conditions on the site typical for this time of year? Yes X No \_\_\_\_\_ (If no, explain in Remarks)  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" Present? Yes X No \_\_\_\_\_  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

**SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.**

Hydrophytic Vegetation Present? Yes <u>X</u> No _____ Hydric Soil Present? Yes <u>X</u> No _____ Wetland Hydrology Present? Yes <u>X</u> No _____	<b>Is the Sampled Area within a Wetland?</b> Yes <u>X</u> No _____
Remarks: Plot placed in swale bottom at upper end.	

**VEGETATION**

Tree Stratum (Use scientific names.)	Absolute % Cover	Dominant Species?	Indicator Status?	Dominance Test worksheet:
1. _____	_____	_____	_____	Number of Dominant Species That Are OBL, FACW, or FAC: <u>1</u> (A)  Total Number of Dominant Species Across All Strata: <u>1</u> (B)  Percent of Dominant Species That Are OBL, FACW, or FAC: <u>100%</u> (A/B)
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
Total Cover: <u>0</u>				<b>Prevalence Index Worksheet:</b> Total % Cover of: _____ Multiply by: _____ OBL species _____ x1 = <u>0</u> FACW species _____ x2 = <u>0</u> FAC species _____ x3 = <u>0</u> FACU species _____ x4 = <u>0</u> UPL species _____ x5 = <u>0</u> Column Totals: <u>0</u> (A) <u>0</u> (B) Prevalence Index = B/A = _____
<b>Shrub Stratum</b>				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
Total Cover: <u>0</u>				
<b>Herb Stratum</b>				
1. <i>Schedonorus arundinaceus</i>	50	Y	☐FAC☐	
2. <i>Geum macrophyllum</i>	10		☐FAC☐	
3. <i>Epilobium ciliatum</i>	15		☐FACW☐	
4. <i>Cirsium arvense</i>	10		☐FAC☐	
5. <i>Stachys chamissonis</i>	10		☐FACW☐	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
Total Cover: <u>95</u>				
<b>Woody Vine Stratum</b>				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
Total Cover: <u>0</u>				
% Bare Ground in Herb Stratum <u>5</u> % Cover of Biotic Crust <u>0</u>				

**Hydrophytic Vegetation Indicators:**

1 - Rapid Test for Hydrophytic Vegetation  
X 2 - Dominance Test is >50%  
 3 - Prevalence Index is ≤3.0<sup>1</sup>  
 4 - Morphological Adaptation<sup>1</sup> (Provide supporting data in Remarks or on a separate sheet)  
 5 - Wetland Non-Vascular Plants<sup>1</sup>  
 Problematic Hydrophytic Vegetation<sup>1</sup> (Explain)

<sup>1</sup>Indicators of hydric soil and wetland hydrology must be present, unless disturbed or problematic.

**Hydrophytic Vegetation Present?** Yes X No \_\_\_\_\_

Remarks: Litter cover

**Profile Description: (Describe to the depth needed to document the indicator or confirm the absence of indicators.)**

Depth (inches)	Matrix		Redox Features				Texture	Remarks
	Color (moist)	%	Color (moist)	%	Type <sup>1</sup>	Loc <sup>2</sup>		
0-6	10 YR 3/2	100					SiL	
6-16	10 YR 3/2	95	7.5 YR 4/4	5	C	M	SiL	

<sup>1</sup>Type: C=Concentration, D=Depletion, RM=Reduced Matrix, CS=Covered or Coated Sand Grains. <sup>2</sup>Location: PL=Pore Lining, M=Matrix.

<b>Hydric Soil Indicators: (Applicable to all LRRs, unless otherwise noted.)</b>		<b>Indicators for Problematic Hydric Soils<sup>3</sup>:</b>	
<input type="checkbox"/> Histosol (A1)	<input type="checkbox"/> Sandy Redox (S5)	<input type="checkbox"/> 2 cm Muck (A10)	
<input type="checkbox"/> Histic Epipedon (A2)	<input type="checkbox"/> Stripped Matrix (S6)	<input type="checkbox"/> Red Parent Material (TF2)	
<input type="checkbox"/> Black Histic (A3)	<input type="checkbox"/> Loamy Mucky Mineral (F1) (except MLRA 1)	<input type="checkbox"/> Other (Explain in Remarks)	
<input type="checkbox"/> Hydrogen Sulfide (A4)	<input type="checkbox"/> Loamy Gleyed Matrix (F2)		
<input type="checkbox"/> Depleted Below Dark Surface (A11)	<input type="checkbox"/> Depleted Matrix (F3)		
<input type="checkbox"/> Thick Dark Surface (A12)	<input checked="" type="checkbox"/> Redox Dark Surface (F6)		<sup>3</sup> Indicators of hydrophytic vegetation and wetland hydrology must be present, unless disturbed or problematic.
<input type="checkbox"/> Sandy Muck Mineral (S1)	<input type="checkbox"/> Depleted Dark Surface (F7)		
<input type="checkbox"/> Sandy gleyed Matrix (S4)	<input type="checkbox"/> Redox Depressions (F8)		

<b>Restrictive Layer (if present):</b>	<b>Hydric Soil Present?</b>	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Type: _____		
Depth (inches): _____		

Remarks:

**HYDROLOGY**

<b>Wetland Hydrology Indicators:</b>		
<u>Primary Indicators (any one indicator is sufficient)</u>		<u>Secondary Indicators (2 or more required)</u>
<input type="checkbox"/> Surface Water (A1)	<input type="checkbox"/> Water-Stained Leaves (B9) (except MLRA 1, 2, 4A and 4B)	<input type="checkbox"/> Water-Stained Leaves (B9) (MLRA 1, 2, 4A and 4B)
<input type="checkbox"/> High Water Table (A2)	<input type="checkbox"/> Salt Crust (B11)	<input type="checkbox"/> Drainage Patterns (B10)
<input type="checkbox"/> Saturation (A3)	<input type="checkbox"/> Aquatic Invertebrates (B13)	<input type="checkbox"/> Dry-Season Water Table (C2)
<input type="checkbox"/> Water Marks (B1)	<input type="checkbox"/> Hydrogen Sulfide Odor (C1)	<input type="checkbox"/> Saturation Visible on Aerial Imagery (C9)
<input type="checkbox"/> Sediment Deposits (B2)	<input type="checkbox"/> Oxidized Rhizospheres along Living Roots (C3)	<input checked="" type="checkbox"/> Geomorphic Position (D2)
<input type="checkbox"/> Drift Deposits (B3)	<input type="checkbox"/> Presence of Reduced Iron (C4)	<input type="checkbox"/> Shallow Aquitard (D3)
<input type="checkbox"/> Algal Mat or Crust (B4)	<input type="checkbox"/> Recent Iron Reduction in Plowed Soils (C6)	<input checked="" type="checkbox"/> FAC-Neutral Test (D5)
<input type="checkbox"/> Iron Deposits (B5)	<input type="checkbox"/> Stunted or Stressed Plants (D1) (LRR A)	<input type="checkbox"/> Raised Ant Mounds (D6) (LRR A)
<input type="checkbox"/> Surface Soil Cracks (B6)	<input type="checkbox"/> Other (Explain in Remarks)	<input type="checkbox"/> Frost-Heave Hummocks (D7)
<input type="checkbox"/> Inundation Visible on Aerial Imagery (B7)		
<input type="checkbox"/> Sparsely Vegetated Concave Surface (B8)		

<b>Field Observations:</b>	<b>Wetland Hydrology Present?</b>	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Surface Water Present? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Depth (inches): _____		
Water table Present? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Depth (inches): _____		
Saturation Present? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Depth (inches): _____		
(includes capillary fringe)		

Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:

Remarks:

**WETLAND DETERMINATION DATA FORM – Western Mountains, Valleys and Coast Region**

Project/Site: Linn Lane City/County: West Linn/Clackamas 7/10/2023  
 Applicant/Owner: Kevin Janssen State: OR Sampling Point: 5  
 Investigator(s): K Cartwright Section, Township, Range: T2S, R1E, Section 25BD  
 Landform (hillslope, terrace, etc.): hillslope Local relief (concave, convex, none): none Slope (%): 3-5%  
 Subregion (LRR): Northwest Forests and Coast (LRR A) Lat: 45.368715 Long: -122.6329361 Datum:  
 Soil Map Unit Name: Cornelius silt loam NWI Classification: none  
 Are climatic / hydrologic conditions on the site typical for this time of year? Yes X No \_\_\_\_\_ (If no, explain in Remarks)  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ significantly disturbed? Are "Normal Circumstances" Present? Yes X No \_\_\_\_\_  
 Are Vegetation \_\_\_\_\_, Soil \_\_\_\_\_, or Hydrology \_\_\_\_\_ naturally problematic? (If needed, explain any answers in Remarks.)

**SUMMARY OF FINDINGS – Attach site map showing sampling point locations, transects, important features, etc.**

Hydrophytic Vegetation Present? Yes <u>X</u> No _____ Hydric Soil Present? Yes _____ No <u>X</u> Wetland Hydrology Present? Yes _____ No <u>X</u>	<b>Is the Sampled Area within a Wetland?</b> Yes _____ No <u>X</u>
Remarks: Plot placed several feet above swale bottom.	

**VEGETATION**

Tree Stratum (Use scientific names.)	Absolute % Cover	Dominant Species?	Indicator Status?	Dominance Test worksheet:
1. _____	_____	_____	_____	Number of Dominant Species That Are OBL, FACW, or FAC: <u>3</u> (A)  Total Number of Dominant Species Across All Strata: <u>4</u> (B)  Percent of Dominant Species That Are OBL, FACW, or FAC: <u>75%</u> (A/B)
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
Total Cover: <u>0</u>				<b>Prevalence Index Worksheet:</b> Total % Cover of: _____ Multiply by: _____ OBL species _____ x1 = <u>0</u> FACW species _____ x2 = <u>0</u> FAC species _____ x3 = <u>0</u> FACU species _____ x4 = <u>0</u> UPL species _____ x5 = <u>0</u> Column Totals: <u>0</u> (A) <u>0</u> (B) Prevalence Index = B/A = _____
<b>Shrub Stratum</b>				
1. <u>Rubus armeniacus</u>	<u>30</u>	<u>Y</u>	<input type="checkbox"/> FAC <input type="checkbox"/>	
2. _____	_____	_____	_____	
3. _____	_____	_____	_____	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
Total Cover: <u>30</u>				
<b>Herb Stratum</b>				
1. <u>Rubus ursinus</u>	<u>20</u>	<u>Y</u>	<input type="checkbox"/> FACU <input type="checkbox"/>	
2. <u>Schedonorus arundinaceus</u>	<u>20</u>	<u>Y</u>	<input type="checkbox"/> FAC <input type="checkbox"/>	
3. <u>Cirsium arvense</u>	<u>40</u>	<u>Y</u>	<input type="checkbox"/> FAC <input type="checkbox"/>	
4. _____	_____	_____	_____	
5. _____	_____	_____	_____	
6. _____	_____	_____	_____	
7. _____	_____	_____	_____	
8. _____	_____	_____	_____	
9. _____	_____	_____	_____	
10. _____	_____	_____	_____	
11. _____	_____	_____	_____	
Total Cover: <u>80</u>				
<b>Woody Vine Stratum</b>				
1. _____	_____	_____	_____	
2. _____	_____	_____	_____	
Total Cover: <u>0</u>				
% Bare Ground in Herb Stratum <u>20</u> % Cover of Biotic Crust <u>0</u>				

**Hydrophytic Vegetation Indicators:**

\_\_\_\_\_ 1 - Rapid Test for Hydrophytic Vegetation  
X 2 - Dominance Test is >50%  
 \_\_\_\_\_ 3 - Prevalence Index is ≤3.0<sup>1</sup>  
 \_\_\_\_\_ 4 - Morphological Adaptation<sup>1</sup> (Provide supporting data in Remarks or on a separate sheet)  
 \_\_\_\_\_ 5 - Wetland Non-Vascular Plants<sup>1</sup>  
 \_\_\_\_\_ Problematic Hydrophytic Vegetation<sup>1</sup> (Explain)

<sup>1</sup>Indicators of hydric soil and wetland hydrology must be present, unless disturbed or problematic.

**Hydrophytic Vegetation Present?** Yes X No \_\_\_\_\_

Remarks: Litter cover

**Profile Description: (Describe to the depth needed to document the indicator or confirm the absence of indicators.)**

Depth (inches)	Matrix		Redox Features				Texture	Remarks
	Color (moist)	%	Color (moist)	%	Type <sup>1</sup>	Loc <sup>2</sup>		
0-16	10 YR 3/3	100					SiL	

<sup>1</sup>Type: C=Concentration, D=Depletion, RM=Reduced Matrix, CS=Covered or Coated Sand Grains. <sup>2</sup>Location: PL=Pore Lining, M=Matrix.

Hydric Soil Indicators: (Applicable to all LRRs, unless otherwise noted.)		Indicators for Problematic Hydric Soils <sup>3</sup> :	
<input type="checkbox"/> Histosol (A1)	<input type="checkbox"/> Sandy Redox (S5)	<input type="checkbox"/> 2 cm Muck (A10)	
<input type="checkbox"/> Histic Epipedon (A2)	<input type="checkbox"/> Stripped Matrix (S6)	<input type="checkbox"/> Red Parent Material (TF2)	
<input type="checkbox"/> Black Histic (A3)	<input type="checkbox"/> Loamy Mucky Mineral (F1) (except MLRA 1)	<input type="checkbox"/> Other (Explain in Remarks)	
<input type="checkbox"/> Hydrogen Sulfide (A4)	<input type="checkbox"/> Loamy Gleyed Matrix (F2)		
<input type="checkbox"/> Depleted Below Dark Surface (A11)	<input type="checkbox"/> Depleted Matrix (F3)		
<input type="checkbox"/> Thick Dark Surface (A12)	<input type="checkbox"/> Redox Dark Surface (F6)		
<input type="checkbox"/> Sandy Muck Mineral (S1)	<input type="checkbox"/> Depleted Dark Surface (F7)		
<input type="checkbox"/> Sandy gleyed Matrix (S4)	<input type="checkbox"/> Redox Depressions (F8)		

<sup>3</sup>Indicators of hydrophytic vegetation and wetland hydrology must be present, unless disturbed or problematic.

<b>Restrictive Layer (if present):</b> Type: _____ Depth (inches): _____	<b>Hydric Soil Present?</b> Yes _____ No <u>X</u>
--	---

Remarks:

**HYDROLOGY**

Wetland Hydrology Indicators:		Secondary Indicators (2 or more required)
Primary Indicators (any one indicator is sufficient)		
<input type="checkbox"/> Surface Water (A1)	<input type="checkbox"/> Water-Stained Leaves (B9) (except MLRA 1, 2, 4A and 4B)	<input type="checkbox"/> Water-Stained Leaves (B9) (MLRA 1, 2, 4A and 4B)
<input type="checkbox"/> High Water Table (A2)	<input type="checkbox"/> Salt Crust (B11)	<input type="checkbox"/> Drainage Patterns (B10)
<input type="checkbox"/> Saturation (A3)	<input type="checkbox"/> Aquatic Invertebrates (B13)	<input type="checkbox"/> Dry-Season Water Table (C2)
<input type="checkbox"/> Water Marks (B1)	<input type="checkbox"/> Hydrogen Sulfide Odor (C1)	<input type="checkbox"/> Saturation Visible on Aerial Imagery (C9)
<input type="checkbox"/> Sediment Deposits (B2)	<input type="checkbox"/> Oxidized Rhizospheres along Living Roots (C3)	<input type="checkbox"/> Geomorphic Position (D2)
<input type="checkbox"/> Drift Deposits (B3)	<input type="checkbox"/> Presence of Reduced Iron (C4)	<input type="checkbox"/> Shallow Aquitard (D3)
<input type="checkbox"/> Algal Mat or Crust (B4)	<input type="checkbox"/> Recent Iron Reduction in Plowed Soils (C6)	<input type="checkbox"/> FAC-Neutral Test (D5)
<input type="checkbox"/> Iron Deposits (B5)	<input type="checkbox"/> Stunted or Stressed Plants (D1) (LRR A)	<input type="checkbox"/> Raised Ant Mounds (D6) (LRR A)
<input type="checkbox"/> Surface Soil Cracks (B6)	<input type="checkbox"/> Other (Explain in Remarks)	<input type="checkbox"/> Frost-Heave Hummocks (D7)
<input type="checkbox"/> Inundation Visible on Aerial Imagery (B7)		
<input type="checkbox"/> Sparsely Vegetated Concave Surface (B8)		

<b>Field Observations:</b> Surface Water Present?    Yes _____ No <u>X</u> Depth (inches): _____ Water table Present?      Yes _____ No <u>X</u> Depth (inches): _____ Saturation Present?        Yes _____ No <u>X</u> Depth (inches): _____ (includes capillary fringe)	<b>Wetland Hydrology Present?</b> Yes _____ No <u>X</u>
---	---

Describe Recorded Data (stream gauge, monitoring well, aerial photos, previous inspections), if available:

Remarks:



# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

July 2<sup>nd</sup>, 2024

---

5494 LINN LN  
WEST LINN, OR 97068

---

## Stormwater Management Report (SWMR)

*PREPARED FOR:*

Kevin Janssen

[khjanssen@yahoo.com](mailto:khjanssen@yahoo.com)

541-515-0653

*PREPARED BY:*

White Pelican Consulting, LLC

Deborah Beck P.E.

PO BOX #33946

Portland, OR 97292

(503) 847-9455

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## TABLE OF CONTENTS

---

ENGINEERS CERTIFICATION .....	1
PROJECT SUMMARY.....	2
SITE LOCATION AND DESCRIPTION.....	2
SOILS .....	2
SLOPES .....	2
PROPOSED CONDITIONS AND STORMWATER FACILITIES .....	3
DESIGN HYDROLOGY AND SIZING .....	4
DESIGN DETAILS .....	6
OPERATIONS AND MAINTENANCE (O&M).....	10
ENGINEERING CONCLUSIONS.....	12
APPENDIX A: NATURAL RESOURCE ASSESSMENT AND GEOTECH REPORT .....	13
APPENDIX B: HYDROCAD MODELING OUTPUT .....	16

---

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## ENGINEERS CERTIFICATION

---

I hereby certify that this Stormwater Management Report for 5494 Linn Ln, West Linn, OR 97068, has been prepared by me or under my supervision and meets the minimum standards of the City of West Linn and normal standards of engineering practice. I hereby acknowledge and agree that the jurisdiction does not and will not assume liability for the sufficiency, suitability, or performance of drainage facilities designed by me.



EXPIRES: 12/31/2025

White Pelican Consulting, LLC

Deborah A. Beck, P.E.

Principle Engineer

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## PROJECT SUMMARY

---

This project proposes to manage stormwater resulting from new construction at 5494 Linn Ln, West Linn, OR 97068 with two StormTech chamber systems. The roof runoff will be directed to a lined MC-7200 StormTech chamber system with sumped catch basin inlet and orifice constricted outlet. The driveway runoff will be directed to a lined SC-310 StormTech chamber system with sumped down-turn elbow style catch basin inlet and an orifice constricted outlet. The two StormTech systems will provide pollution reduction and flow control before releasing the overflow to existing stormwater pipe located east of the site. The new construction includes a new single-family residence (roof coverage ~7,163 sq. ft) and driveway (~1,662 sq. ft.).

## SITE LOCATION AND DESCRIPTION

---

5494 Linn Ln, West Linn, OR 97068 (site), tax lot ID 21E25BD00500, is entirely located within Clackamas County and is zoned R10. R10 is single-dwelling zone which allows 1 dwelling unit per 10,000 ft<sup>2</sup>. The site is in the Johnson Creek Watershed (source Metro Maps). The site is 0.67 acres (~29,185 sq. ft.) with an existing single-family residence and driveway.

Two wetlands totaling 0.05 acre were identified onsite during a Natural Resource Assessment conducted by Schott & Associates Inc. Wetland 1 (0.006-acre onsite) is at the bottom of the swale south of the existing driveway and Wetland 2 (0.04 acre onsite) is at the bottom of the broad swale north of the existing driveway.

The Landslide Susceptibility mapping was performed by the Hardman Geotechnical Services, Inc and showed the existing home and proposed facilities are mapped as having “High” susceptibility for shallow slides less than 15 ft deep.

## SOILS

---

The soils on the site are listed as Cornelius silt loam, 8 to 15 percent slopes (23C), Wetted Drainage Class “Moderately Well Drained” and are rated Hydrologic soil group C (NRCS Soil Web).

## SLOPES

---

Slopes on the site surrounding where the new residence is to be located are generally >20%. Due to the steep slopes combined with the landslide susceptibility ratings of the site, infiltration of collected stormwater is not recommended.

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223




FIGURE 1. SLOPES AS SHOWN IN METRO MAPS, LIGHT ORANGE >10%, PINK >25%.

## *Groundwater*

Hardman Geotechnical Services Inc. (HGS) prepared a Geotech Report of the site and as part of their analysis took soil borings down to 8 ft. HGS did not encounter groundwater in the soil borings.

## EXISTING STORMWATER CONDITIONS

Existing impervious areas include a single-family residence and asphalt driveway servicing the residence. The existing house has gutter and downspouts that drain to ground and discharge at an unknown location. The existing driveway drains to grade.

## PROPOSED CONDITIONS AND STORMWATER FACILITIES

Proposed construction includes a demolition of the existing house, construction of a new single-family house and replacing and enlarging the existing driveway. The new impervious areas and associated square footage are in Table 1 below. Due to the site consisting mostly of slopes >20% and being rated as a landslide concern, lined orifice-controlled systems were chosen to manage the stormwater resulting from the new impervious areas. The roof runoff will be directed to a lined MC-7200 StormTech chamber system with sumped catch basin inlet and orifice constricted outlet. The driveway runoff will be directed to a lined SC-310 StormTech chamber system with sumped down-turn elbow style catch basin inlet and an orifice constricted outlet. Combined, the two StormTech systems will provide pollution reduction and flow control before releasing the overflow to existing stormwater pipe located east of the site. Should the StormTech chamber systems be overwhelmed by a very large storm, the stormwater will flow out of the nyloplast basin grates and downslope to the nearby wetland and to the tributary to Barlow Creek running through Shallie Illahee Park.

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

TABLE 1: NEW IMPERVIOUS AREAS

Areas	Sq. Ft.
New Residence Roof	7,163
Improved driveway - uncovered areas	1,662
Total New Impervious	8,825

## DESIGN HYDROLOGY AND SIZING

---

### *Areas used in Model*

The areas used in the modeling for sizing the stormwater facilities are listed in Table 1 above.

### *New Impervious Area Runoff*

Design hydrology for on-site stormwater runoff from the proposed new construction and infiltration of the runoff was calculated using HydroCAD 10.20 modeling software. HydroCAD 10 uses the Santa Barbara Urban Hydrograph (SBUH) Method.

The city of West Linn requires systems performing flow-control to be sized for 10-yr storm events. The 2-yr, 10-yr and 25-yr events of expected flows both pre-development and post-development were modeled. The peak flow rates determined are listed in Table 2 and Table 3.

The two StormTech chamber systems are expected to fully capture and detain the runoff resulting from the 10-yr and 25-yr storm events while slowly releasing the captured flows at rates below the determined pre-development flow. Figure 2 shows the hydrographs of the 10-yr storm for each system. The HydroCAD® Modeling Output is in Appendix C.

TABLE 2: MODELED PRE-DEVELOPMENT PEAK FLOW RATES

Peak cfs of Pre-Dev Rain Event			
Area	2-yr	10-yr	25-yr
House	0.026	0.056	0.072
Driveway	0.006	0.013	0.017
Total	0.032	0.069	0.089

TABLE 3: MODELED POST-DEVELOPMENT FLOW RATES

Peak cfs of Post-Dev Rain Event			
Area	2-yr	10-yr	25-yr
House - StormTech MC-7200	0.011	0.013	0.015
Driveway- StormTech SC-310	0.007	0.009	0.010
Total	0.018	0.022	0.025

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223





FIGURE 2: HYDROGRAPH OF 10-YR STORM IN THE MC-7200 STORMTECH THREE-CHAMBER SYSTEM (TOP) AND THE SC-310 STORMTECH TWO-CHAMBER SYSTEM BOTTOM.



**GENERAL NOTES:**

CONTRACTOR IS RESPONSIBLE FOR VERIFICATION OF ALL UTILITIES PRIOR TO CONSTRUCTION AND SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY CONFLICTS WITH THESE PLANS UPON DISCOVERY.

THE CONTRACTOR SHALL PREVENT SEDIMENT LADEN WATER FROM LEAVING THE SITE. ALL ADJACENT DOWNSTREAM STORM DRAIN INLETS SHALL BE PROTECTED FROM SILTATION.

THE CONTRACTOR SHALL NOT ALLOW ANY WASH WATER OR DEBRIS TO ENTER NEW PIPES OR CHANNELS DURING CONSTRUCTION.

THE CONTRACTOR SHALL AT ALL TIMES PROVIDE AND MAINTAIN AMPLE MEANS AND DEVICES TO REMOVE AND DISPOSE OF ALL WATER ENTERING THE TRENCH EXCAVATION DURING THE PROCESS OF LAYING THE PIPE.

INSTALL CONTINUOUS INSULATED COPPER TRACER WIRE OR MAGNETIC TAPE AS REQUIRED BY THE OREGON PLUMBING SPECIALTY CODE.

UNLESS OTHERWISE NOTED, ALL STORM DRAIN PIPES ARE TO HAVE A MINIMUM 1% DOWNSLOPE TO THE NEAREST STORMWATER FACILITY. STORM DRAIN PIPES ARE TO BE PVC SCHEDULE 40, ABS SCHEDULE 40, OR CAST IRON AND FOLLOW OREGON PLUMBING SPECIALTY CODE.

ALL STORM WATER PIPE CONNECTIONS TO CATCH BASINS, MANHOLES, PLANTERS AND OTHER RELATED STRUCTURES SHALL BE WATER TIGHT AS PER OREGON PLUMBING SPECIALTY CODE.

STORMWATER FACILITIES, STRUCTURES, AND PIPING SHOWN ARE INTENDED TO BE FOR SCHEMATIC PURPOSES ONLY. THE CONTRACTOR SHALL ADJUST THE ALIGNMENT AND GRADE OF THE STORMWATER SYSTEM AS NECESSARY TO ACCOMMODATE THE NEW CONSTRUCTION AND TOPOGRAPHY, WHILE MAINTAINING MINIMUM SLOPE REQUIREMENTS.

ALL COMPONENTS OF THE PRIVATE STORMWATER SYSTEM SHALL BE CONSTRUCTED PER OREGON PLUMBING SPECIALTY CODE REQUIREMENTS.


- CONSTRUCTION NOTES:**
- DIRECT DOWNSPOUTS FROM ROOF TO STORM DRAIN PIPE DISCHARGING TO MC-7200 STORMTECH SYSTEM, USE 4 INCH STORM DRAIN LINE. 4 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - STORM PIPE COLLECTING ROOF RUNOFF AND DISCHARGING TO NYLOPLAST BASIN (OR EQUIVALENT) ATTACHED TO MC-7200 STORMTECH SYSTEM. MIN 4 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - INSTALL 3 MC-7200 STORMTECH CHAMBERS INSIDE LINED ROCK GALLERY. INSTALL PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAILS. USE CONCEPTUAL ELEVATIONS AS NOTED IN DETAILS. MC-7200 CHAMBER SYSTEM IS FOR ROOF DRAINAGE ONLY.
  - CONCRETE OUTLET STRUCTURE. 48 INCH DIAMETER MANHOLE. DISCHARGE MC-7200 SYSTEM DRAIN PIPE TO OUTLET. INSTALL A GATE VALVE WITH 0.5 INCH ORIFICE DRILLED IN THE PLATE ON THE OUTLET PIPE MAKING SURE GATE VALVE IS ACCESSIBLE FROM INSIDE MANHOLE, OR INSTALL ORIFICE PLATE WITH 0.5 INCH OPENING OVER OUTLET PIPE. WATERPROOF INLET AND OUTLET PIPE OPENINGS.
  - GATE VALVE OR ORIFICE PLATE WITH 0.5 INCH ORIFICE DRILLED IN PLATE. AFTER INSTALL, GATE VALVE IS TO BE FULLY SHUT TO ALLOW PROPER FUNCTION OF THE ORIFICE.
  - 6 INCH SOLID DRAIN PIPE DISCHARGING TO EXISTING STORM DRAINAGE PIPE.
  - SLOPE DRIVEWAY TO DRAIN TO OPEN GRATE ON SUMPED NYLOPLAST BASIN ATTACHED TO SC-310 STORMTECH SYSTEM.
  - INSTALL 2 SC-310 STORMTECH CHAMBERS INSIDE LINED ROCK GALLERY AT LOW POINT OF DRIVEWAY. INSTALL PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAILS. USE CONCEPTUAL ELEVATIONS AS NOTED IN DETAILS.
  - 3 INCH DRAIN PIPE DRAINING LINED SC-310 ROCK GALLERY. CONNECT TO GATE VALVE INSIDE 12 INCH NYLOPLAST DRAIN BASIN. CONNECT TO 6 INCH DRAIN PIPE DISCHARGING TO EXISTING STORM DRAINAGE PIPE.
  - MIN 12 INCH DIAMETER NYLOPLAST BASIN OR EQUIVALENT. RUN DRAIN PIPE FROM SC-310 ROCK GALLERY TO BASIN, INSTALL GATE VALVE WITH 0.5 INCH ORIFICE DRILLED IN PLATE. AFTER INSTALL, GATE VALVE IS TO BE FULLY SHUT TO ALLOW PROPER FUNCTION OF THE ORIFICE.
  - 6 INCH SOLID DRAIN PIPE DISCHARGING TO EXISTING 12 INCH STORM DRAIN PIPE NEAR WALKING BRIDGE. FIELD LOCATE APPROPRIATE CONNECTION POINT TO MAINTAIN 1% DOWNSLOPE. 6 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - 18 INCH DIAMETER STORMTECH NYLOPLAST BASIN OR EQUIVALENT. MINIMUM 18 INCH SUMP. INSTALL DOWN-TURN ELBOW ON OUTLET PIPE. MAY TOP WITH REDUCER TO DECREASE DIAMETER OF GRATE.



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.


**WHITE PELICAN CONSULTING**  
 PORTLAND, OREGON  
 503-847-9455  
 www.whitepelicanconsulting.com  
 email: dbeck@whitepelicanconsulting.com

**JANSEN RESIDENCE**  
 5494 LINN LANE  
 WEST LINN, OREGON 97008  
 STORMWATER MANAGEMENT  
 SITE PLAN




DATE	
7/2/24	
SCALE	PROJ. NO.
1"=10'	
DRAWN BY	CHECKED BY
TRT	DAB

**SW1**




PROPOSED LAYOUT: HOUSE		CONCEPTUAL ELEVATIONS		PART TYPE		ITEM ON LAYOUT	DESCRIPTION	INVERT	MAX FLOW
3	MC-7200	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT UNPAVED):	12.75'	A	12" TOP PARTIAL CUT END CAP PART# MC7200EPP12T / TYP OF ALL 12" TOP CONNECTIONS	35.69'			
4	STORMTECH MC-7200 END CAPS	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	8.25'	B	24" BOTTOM PARTIAL CUT END CAP PART# MC7200EPP24B / TYP OF ALL 24" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS	2.26'			
5	STONE ABOVE (IN)	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC):	7.75'	C	12" BOTTOM PARTIAL CUT END CAP PART# MC7200EPP12B / TYP OF ALL 12" BOTTOM CONNECTIONS	1.55'			
9	STONE BELOW (IN)	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	5.75'	D	INSTALL FLAMP ON 24" ACCESS PIPE / PART# MCLFLAMP				
40	STONE VOID	TOP OF STONE:	5.75'	E	12" x 12" TOP MANIFOLD INVERT:				
1559	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED) (COVER STONE INCLUDED) (BASE STONE INCLUDED)	TOP OF MC-7200 CHAMBER:	3.75'	F	CONCRETE STRUCTURE (DESIGN BY ENGINEER / PROVIDED BY OTHERS)	35.69'			
425	SYSTEM AREA (SF)	12" x 12" TOP MANIFOLD INVERT:	0.84'	G	CONCRETE STRUCTURE (DESIGN BY ENGINEER / PROVIDED BY OTHERS)				
88.9	SYSTEM PERIMETER (ft)	12" BOTTOM CONNECTION INVERT:	0.74'	H	ADS N-12 DUAL WALL PERFORATED HDPE UNDERDRAIN		2.5 CFS IN		
137	THERMOPLASTIC LINER (SY) (20% OVERAGE)	BOTTOM OF MC-7200 CHAMBER:	0.00'	I	4" SEE DETAIL		2.0 CFS OUT		



- ISOLATOR ROW PLUS (SEE DETAIL)
- PLACE MINIMUM 17.5' OF ADS PLUS 15' WOVEN GEOTEXTILE OVER BEDDING STONE AND UNDERNEATH CHAMBER FEET FOR SCOUR PROTECTION AT ALL CHAMBER INLET ROWS
- THERMOPLASTIC LINER (SEE TECH NOTE #6.50 PROVIDED BY OTHERS / DESIGN BY OTHERS)


**NOTES**

- MINIMUM SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #6.32 FOR MANIFOLD SIZING GUIDANCE.
- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE INSITU SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- ADS DOES NOT DESIGN OR PROVIDE MEMBRANE LINER SYSTEMS FOR CISTERNS (RAINWATER HARVESTING). TO MINIMIZE THE LEAKAGE POTENTIAL OF LINER SYSTEMS, THE MEMBRANE LINER SYSTEM SHOULD BE DESIGNED BY A KNOWLEDGEABLE GEOTEXTILE PROFESSIONAL AND INSTALLED BY A QUALIFIED CONTRACTOR.
- NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.



5 UNDERDRAIN DETAIL

SPACE INTENTIONALLY LEFT BLANK



2 MC-7200 TECHNICAL SPECIFICATION

**NOMINAL CHAMBER SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)	100.0" X 60.0" X 79.1" (2540 mm X 1524 mm X 2010 mm)
CHAMBER STORAGE	175.9 CUBIC FEET (4.98 m³)
MINIMUM INSTALLED STORAGE*	267.3 CUBIC FEET (7.56 m³)
WEIGHT (NOMINAL)	205 lbs. (92.9 kg)

**NOMINAL END CAP SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)	90.0" X 61.0" X 32.8" (2286 mm X 1549 mm X 833 mm)
END CAP STORAGE	39.5 CUBIC FEET (1.12 m³)
MINIMUM INSTALLED STORAGE*	115.3 CUBIC FEET (3.26 m³)
WEIGHT (NOMINAL)	90 lbs. (40.8 kg)


\*ASSUMES 12" (305 mm) STONE ABOVE, 9" (229 mm) STONE FOUNDATION AND BETWEEN CHAMBERS, 12" (305 mm) STONE PERIMETER IN FRONT OF END CAPS AND 40% STONE POROSITY.

PARTIAL CUT HOLES AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B" PARTIAL CUT HOLES AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T" END CAPS WITH A PREFABRICATED WELDED STUB END WITH "Y"


PART #	STUB	B	C
MC7200EPP06T	6" (150 mm)	42.54" (1081 mm)	---
MC7200EPP06B	---	---	0.86" (22 mm)
MC7200EPP08T	8" (200 mm)	40.50" (1029 mm)	---
MC7200EPP08B	---	---	1.01" (26 mm)
MC7200EPP10T	10" (250 mm)	38.37" (975 mm)	---
MC7200EPP10B	---	---	1.33" (34 mm)
MC7200EPP12T	12" (300 mm)	35.69" (907 mm)	---
MC7200EPP12B	---	---	1.55" (39 mm)
MC7200EPP15T	15" (375 mm)	32.72" (831 mm)	---
MC7200EPP15B	---	---	1.70" (43 mm)
MC7200EPP18T	18" (450 mm)	29.36" (746 mm)	---
MC7200EPP18B	---	---	1.97" (50 mm)
MC7200EPP18TW	18" (450 mm)	29.36" (746 mm)	---
MC7200EPP18TB	---	---	1.97" (50 mm)
MC7200EPP24TW	24" (600 mm)	23.05" (585 mm)	---
MC7200EPP24TB	---	---	2.26" (57 mm)
MC7200EPP24BW	30" (750 mm)	---	2.56" (65 mm)
MC7200EPP26BW	36" (900 mm)	---	3.25" (83 mm)
MC7200EPP42BW	42" (1050 mm)	---	3.55" (90 mm)

NOTE: ALL DIMENSIONS ARE NOMINAL

CUSTOM PREFABRICATED INVERTS ARE AVAILABLE UPON REQUEST. INVENTORIED MANIFOLDS INCLUDE 12-24" (300-600 mm) SIZE ON SIZE AND 15-48" (375-1200 mm) ECCENTRIC MANIFOLDS. CUSTOM INVERT LOCATIONS ON THE MC-7200 END CAP CUT IN THE FIELD ARE NOT RECOMMENDED FOR PIPE SIZES GREATER THAN 10" (250 mm). THE INVERT LOCATION IN COLUMN 'B' ARE THE HIGHEST POSSIBLE FOR THE PIPE SIZE.



3 MC-7200 ISOLATOR ROW PLUS DETAIL




6 MC-SERIES END CAP INSERTION DETAIL

ACCEPTABLE FILL MATERIALS: STORMTECH MC-7200 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT	
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	ANY SOIL/ROCK MATERIALS, NATIVE SOILS, OR PER ENGINEER'S PLANS. CHECK PLANS FOR PAVEMENT SUBGRADE REQUIREMENTS.	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 24" (600 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE.	AASHTO M145 <sup>1</sup> A-1, A-2.4, A-3 OR AASHTO M43 <sup>3</sup> 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 24" (600 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 12" (300 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS.
B	EMBEDMENT STONE: FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETE <sup>2</sup>	AASHTO M43 <sup>3</sup> 3, 357, 4, 467, 5, 56, 57	NO COMPACTION REQUIRED.
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETE <sup>2</sup>	AASHTO M43 <sup>3</sup> 3, 357, 4, 467, 5, 56, 57	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>

PLEASE NOTE:

- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
- STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 9" (230 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
- WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR BRACING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.
- ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.
- WHERE RECYCLED CONCRETE AGGREGATE IS USED IN LAYERS 'A' OR 'B' THE MATERIAL SHOULD ALSO MEET THE ACCEPTABILITY CRITERIA OUTLINED IN TECHNICAL NOTE 6.20 "RECYCLED CONCRETE STRUCTURAL BACKFILL".




1 MC-7200 CROSS SECTION DETAIL



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.

WHITE PELICAN CONSULTING  
PORTLAND, OREGON  
503-847-9455  
www.whitepelicanconsulting.com  
email: dbeck@whitepelicanconsulting.com



JANSEN RESIDENCE  
5494 LINN AVENUE  
WEST LINN, OREGON 97068  
STORMWATER MANAGEMENT  
DETAILS



DATE	5/24/24
SCALE	NTS
PROJ. NO.	
DRAWN BY	TRT
CHECKED BY	DBJ

SW2

PROPOSED LAYOUT: DRIVEWAY		CONCEPTUAL ELEVATIONS		PART TYPE		ITEM ON LAYOUT		DESCRIPTION		*INVERT ABOVE BASE OF CHAMBER	
2	SC-310	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT UNPAVED):	9.83	PREFABRICATED EZ END CAP	A	12" BOTTOM PREFABRICATED EZ END CAP, PART#: SC310ECEZ / TYP OF ALL 12" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS				0.90'	
2	STORMTECH SC-310 CHAMBERS	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	3.83	FLAMP	B	INSTALL FLAMP ON 12" ACCESS PIPE, PART#: SC31012RAMP					
4	STORMTECH SC-310 END CAPS	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC):	3.33	MANIFOLD	C	8" x 8" TOP MANIFOLD, MOLDED FITTINGS				3.60'	
6	STONE ABOVE (in)	MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):		NYLOPLAST (INLET W/ISO PLUS ROW)	D	18" DIAMETER (24.00" SUMP MIN)					0.9 CFS IN
6	STONE BELOW (in)	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):		NYLOPLAST (OUTLET)	E	12" DIAMETER (DESIGN BY ENGINEER)					0.7 CFS OUT
40	STONE VOID	TOP OF STONE:		UNDERDRAIN	F	4" ADS-N-12 DUAL WALL PERFORATED HDPE UNDERDRAIN					
129	INSTALLED SYSTEM VOLUME (CF)	TOP OF SC-310 CHAMBER:									
	(PERIMETER STONE INCLUDED)	12" ISOLATOR ROW PLUS INVERT:	0.58								
	(COVER STONE INCLUDED)	12" BOTTOM CONNECTION INVERT:	0.58								
120	SYSTEM AREA (SF)	12" BOTTOM CONNECTION INVERT:	0.58								
44.8	SYSTEM PERIMETER (ft)	BOTTOM OF SC-310 CHAMBER:	0.50								
		BOTTOM OF SC-310 CHAMBER:	0.50								
		UNDERDRAIN INVERT:	0.00								
30	THERMOPLASTIC LINER (3% 20% OVERAGE)	BOTTOM OF STONE:	0.00								




**NOTES**

- TRAFFIC LOAD TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #632 FOR MANIFOLD SIZING GUIDANCE DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE INSTALLED SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- ADS DOES NOT DESIGN OR PROVIDE MEMBRANE LINER SYSTEMS FOR CISTERNS (RAINWATER HARVESTING), TO MINIMIZE THE LEAKAGE POTENTIAL OF LINER SYSTEMS, THE MEMBRANE LINER SYSTEM SHOULD BE DESIGNED BY A KNOWLEDGEABLE GEOTEXTILE PROFESSIONAL AND INSTALLED BY A QUALIFIED CONTRACTOR.
- **NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.

4

**UNDERDRAIN DETAIL**



SPACE INTENTIONALLY LEFT BLANK

2

**SC-310 TECHNICAL SPECIFICATION**

SC-310 TECHNICAL SPECIFICATION

NTS

**NOMINAL CHAMBER SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)	34.0\"/>
CHAMBER STORAGE	14.7 CUBIC FEET (0.42 m <sup>3</sup> )
MINIMUM INSTALLED STORAGE*	31.0 CUBIC FEET (0.88 m <sup>3</sup> )
WEIGHT	35.0 lbs. (16.8 kg)

\*ASSUMES 6\"/>

PRE-FAB STUB AT BOTTOM OF END CAP WITH FLAMP END WITH "BR"  
 PRE-FAB STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 PRE-FAB STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"  
 PRE-CORED END CAPS END WITH "PC"

PART #	STUB	A	B	C
SC310EPE06T / SC310EPE06TPC	6\"/>			
SC310EPE08T / SC310EPE08TPC	8\"/>			
SC310EPE10T / SC310EPE10TPC	10\"/>			
SC310EPE12T / SC310EPE12TPC	12\"/>			

ALL STUBS, EXCEPT FOR THE SC310ECEZ ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2894.

\*FOR THE SC310ECEZ THE 12\"/>

BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL.

**3 SC-310 ISOLATOR ROW PLUS DETAIL**

**INSPECTION & MAINTENANCE**

STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT

A. INSPECTION PORTS (IF PRESENT)

- REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
- REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
- USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
- LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
- IF SEDIMENT IS AT, OR ABOVE, 3\"/>

B. ALL ISOLATOR PLUS ROWS

- REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
- USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
  - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
  - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
  - IF SEDIMENT IS AT, OR ABOVE, 3\"/>

STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JET/VAC PROCESS

- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45\"/>

STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.

STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

**NOTES**

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION, ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.

1

**SC-310 CROSS SECTION DETAIL**



**NOTES:**


- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2922 (POLYETHYLENE) OR ASTM F2418 (POLYPROPYLENE), "STANDARD SPECIFICATION FOR CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-310 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 400 LBS/FT<sup>2</sup>. THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418, AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.

**WHITE PELICAN CONSULTING**  
 PORTLAND, OREGON  
 503-847-9455  
 www.whitepelicanconsulting.com  
 email: dbeck@whitepelicanconsulting.com

**JANSEN RESIDENCE**  
 5494 LINE AVENUE  
 WEST LINN, OREGON 97008  
 STORMWATER MANAGEMENT  
 DETAILS



DATE	5/24/24
SCALE	NTS
DRAWN BY	TRT
CHECKED BY	DB

**SW3**


SPACE INTENTIONALLY LEFT BLANK



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.



**WHITE PELICAN CONSULTING**  
 PORTLAND, OREGON  
 503-847-9455  
 www.whitepelicanconsulting.com  
 email: dbect@whitepelicanconsulting.com

JANSEN RESIDENCE  
 5494 LINE AVENUE  
 WEST LINN, OREGON 97068  
 STORMWATER MANAGEMENT  
 DETAILS




DATE	5/31/24
SCALE	NTS
PROJ. NO.	
DRAWN BY	TRT
CHECKED BY	DB

**SW4**




<b>Oldcastle Precast</b>	<b>48" MANHOLE</b>	<b>48" MANHOLE</b>
PO Box 323, Wilsonville, Oregon 97070-0323 Tel: (503) 682-2844 Fax: (503) 682-2657	File Name: 020-48MH Issue Date: 2017 oldcastleprecast.com/wilsonville	

MANHOLE  
 DETAIL  
 NTS



DRAIN BASIN  
 DETAIL  
 NTS



- NOTES**
- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
  - 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
  - DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
  - DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS & HANCOCK DUAL WALL) & SDR 35 PVC
  - FOR COMPLETE DESIGN AND PRODUCT INFORMATION: WWW.NYLOPLAST-US.COM
  - TO ORDER CALL: 800-821-6710

A	PART #	GRATE/SOLID COVER OPTIONS
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY STANDARD LIGHT DUTY SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY STANDARD LIGHT DUTY SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20 STANDARD AASHTO H-20 SOLID AASHTO H-20

REDUCER  
 DETAIL  
 NTS

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## OPERATIONS AND MAINTENANCE (O&M)

---

### StormTech Chamber System

#### **INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- A. INSPECTION PORTS (IF PRESENT)
    - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
    - A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - B. ALL ISOLATOR PLUS ROWS
    - B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45" (1.1 m) OR MORE IS PREFERRED
  - B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
  - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

#### **NOTES**

1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## Nyloplast or Catch Basin

Maintenance Component	Spring	Summer	Fall	Winter	24-hr Precip > 1"
Replace or repair inlets if they are cracked or broken. Reseal inlet pipes if they are not watertight.		X	X		
Remove sediment from catchbasin.	X		X		X
Remove leaf litter/debris from gutters.	X		X		
Check trench drains leading to the facility and remove any soil or debris.	X	X	X	X	X
Remove inspection portal lid and check for spalling or cracking of walls and for root intrusions. Repair as necessary.		X	X		
Remove inspection portal lid and check sediment depth. Have professionally cleaned when depth of sediment or debris is 6" or greater.		X	X		
Remove Inspection portal lid and contact City stormwater engineers (503.635.0270) if ponding occurs for more than 48 hours.	X		X	X	X

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## ENGINEERING CONCLUSIONS

---

Stormwater runoff from the post-development impervious areas will be directed to two separate lined StormTech chamber systems each with a 0.5 inch orifice limiting the rate of drainage from the systems to below pre-development levels. These stormwater facilities will meet both pollution reduction and flow control requirements as specified by the City of West Linn.

The proposed installation of the two lined StormTech chamber systems as described in this report are expected to meet the site's needs for stormwater management of impervious areas on the site.

# White Pelican Consulting, LLC

Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## APPENDIX A: NATURAL RESOURCE ASSESSMENT AND GEOTECH REPORT

---

*Submitted as separate document due to large file size.*

# White Pelican Consulting, LLC


Environmental Engineering & Data Analysis

WBE, DBE, ESB Oregon Certified # 12223

## APPENDIX B: HYDROCAD MODELING OUTPUT



---





Pre-Dev House Roof

Pre-Dev Driveway



**Summary for Subcatchment 13S: Pre-Dev House Roof**

Runoff = 0.026 cfs @ 7.99 hrs, Volume= 500 cf, Depth= 0.84"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
Type IA 24-hr 2-yr Rainfall=2.50"

Area (sf)	CN	Description
* 7,163	79	
7,163	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Subcatchment 16S: Pre-Dev Driveway**

Runoff = 0.006 cfs @ 7.99 hrs, Volume= 116 cf, Depth= 0.84"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
Type IA 24-hr 2-yr Rainfall=2.50"

Area (sf)	CN	Description
* 1,662	79	
1,662	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Subcatchment 13S: Pre-Dev House Roof**

Runoff = 0.056 cfs @ 7.98 hrs, Volume= 912 cf, Depth= 1.53"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
Type IA 24-hr 10-yr Rainfall=3.45"

	Area (sf)	CN	Description
*	7,163	79	
	7,163	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Subcatchment 16S: Pre-Dev Driveway**

Runoff = 0.013 cfs @ 7.98 hrs, Volume= 212 cf, Depth= 1.53"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
Type IA 24-hr 10-yr Rainfall=3.45"

	Area (sf)	CN	Description
*	1,662	79	
	1,662	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Subcatchment 13S: Pre-Dev House Roof**

Runoff = 0.072 cfs @ 7.98 hrs, Volume= 1,124 cf, Depth= 1.88"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
 Type IA 24-hr 25-yr Rainfall=3.90"

Area (sf)	CN	Description
* 7,163	79	
7,163	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**Summary for Subcatchment 16S: Pre-Dev Driveway**

Runoff = 0.017 cfs @ 7.98 hrs, Volume= 261 cf, Depth= 1.88"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
 Type IA 24-hr 25-yr Rainfall=3.90"

Area (sf)	CN	Description
* 1,662	79	
1,662	79	100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					<b>Direct Entry,</b>

**5494 Linn Ln West Linn**

Prepared by White Pelican Consulting

HydroCAD® 10.20-5a s/n 12722 © 2023 HydroCAD Software Solutions LLC

*Multi-Event Tables*

Printed 5/30/2024

Page 5

**Events for Subcatchment 13S: Pre-Dev House Roof**

Event	Rainfall (inches)	Runoff (cfs)	Volume (cubic-feet)	Depth (inches)
2-yr	2.50	0.026	500	0.84
10-yr	3.45	0.056	912	1.53
25-yr	<b>3.90</b>	<b>0.072</b>	<b>1,124</b>	<b>1.88</b>

**5494 Linn Ln West Linn**

Prepared by White Pelican Consulting

HydroCAD® 10.20-5a s/n 12722 © 2023 HydroCAD Software Solutions LLC


*Multi-Event Tables*

Printed 5/30/2024



Page 6

**Events for Subcatchment 16S: Pre-Dev Driveway**


Event	Rainfall (inches)	Runoff (cfs)	Volume (cubic-feet)	Depth (inches)
2-yr	2.50	0.006	116	0.84
10-yr	3.45	0.013	212	1.53
25-yr	<b>3.90</b>	<b>0.017</b>	<b>261</b>	<b>1.88</b>



House Roof





Driveway



MC-7200 StormTech (3)  
House

SC310 StormTech (2)



### Summary for Subcatchment 3S: House Roof

Runoff = 0.133 cfs @ 7.90 hrs, Volume= 1,920 cf, Depth= 3.22"

Routed to Pond 5P : MC-7200 StormTech (3) House


Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
 Type IA 24-hr 10-yr Rainfall=3.45"

Area (sf)	CN	Description
* 7,163	98	Roof
7,163	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

### Subcatchment 3S: House Roof

Hydrograph





### Summary for Subcatchment 15S: Driveway

Runoff = 0.031 cfs @ 7.90 hrs, Volume= 446 cf, Depth= 3.22"  
 Routed to Pond 1P : SC310 StormTech (2)


Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
 Type IA 24-hr 10-yr Rainfall=3.45"

Area (sf)	CN	Description
* 1,662	98	Roof
1,662	98	100.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.0					Direct Entry,

### Subcatchment 15S: Driveway

Hydrograph



**Summary for Pond 1P: SC310 StormTech (2)**

Inflow Area = 1,662 sf, 100.00% Impervious, Inflow Depth = 3.22" for 10-yr event  
 Inflow = 0.031 cfs @ 7.90 hrs, Volume= 446 cf  
 Outflow = 0.009 cfs @ 9.18 hrs, Volume= 446 cf, Atten= 72%, Lag= 76.9 min  
 Primary = 0.009 cfs @ 9.18 hrs, Volume= 446 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.05 hrs / 2  
 Peak Elev= 548.40' @ 9.18 hrs Surf.Area= 120 sf Storage= 100 cf

Plug-Flow detention time= 131.8 min calculated for 446 cf (100% of inflow)  
 Center-of-Mass det. time= 131.5 min ( 795.9 - 664.4 )


Volume	Invert	Avail.Storage	Storage Description
#1	546.67'	100 cf	<b>8.77'W x 13.63'L x 2.33'H Prismatic</b> 279 cf Overall - 29 cf Embedded = 249 cf x 40.0% Voids
#2	547.17'	29 cf	<b>ADS_StormTech SC-310 +Cap</b> x 2 Inside #1 Effective Size= 28.9"W x 16.0"H => 2.07 sf x 7.12'L = 14.7 cf Overall Size= 34.0"W x 16.0"H x 7.56'L with 0.44' Overlap 2 Chambers in 2 Rows
		129 cf	Total Available Storage

Device	Routing	Invert	Outlet Devices
#1	Primary	546.67'	<b>0.5" Vert. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads

**Primary OutFlow** Max=0.009 cfs @ 9.18 hrs HW=548.40' (Free Discharge)  
 ↑1=Orifice/Grate (Orifice Controls 0.009 cfs @ 6.29 fps)

### Pond 1P: SC310 StormTech (2)

Hydrograph



**Summary for Pond 5P: MC-7200 StormTech (3) House**

Inflow Area = 7,163 sf, 100.00% Impervious, Inflow Depth = 3.22" for 10-yr event  
 Inflow = 0.133 cfs @ 7.90 hrs, Volume= 1,920 cf  
 Outflow = 0.013 cfs @ 21.03 hrs, Volume= 1,920 cf, Atten= 90%, Lag= 788.1 min  
 Primary = 0.013 cfs @ 21.03 hrs, Volume= 1,920 cf

Routing by Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.05 hrs  
 Peak Elev= 547.42' @ 21.03 hrs Surf.Area= 429 sf Storage= 1,064 cf

Plug-Flow detention time= 992.6 min calculated for 1,920 cf (100% of inflow)  
 Center-of-Mass det. time= 992.5 min ( 1,657.0 - 664.4 )

Volume	Invert	Avail.Storage	Storage Description
#1	543.25'	884 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc) 2,896 cf Overall - 686 cf Embedded = 2,210 cf x 40.0% Voids
#2	544.00'	686 cf	<b>ADS_StormTech MC-7200 +Cap</b> x 3 Inside #1 Effective Size= 91.2"W x 60.0"H => 26.68 sf x 6.59'L = 175.9 cf Overall Size= 100.0"W x 60.0"H x 6.95'L with 0.36' Overlap 3 Chambers in 2 Rows Cap Storage= 39.5 cf x 2 x 2 rows = 158.0 cf
		1,570 cf	Total Available Storage


Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
543.25	429	0	0
550.00	429	2,896	2,896


Device	Routing	Invert	Outlet Devices
#1	Primary	543.25'	<b>0.5" Vert. Orifice/Grate</b> C= 0.600 Limited to weir flow at low heads

**Primary OutFlow** Max=0.013 cfs @ 21.03 hrs HW=547.42' (Free Discharge)  
 ←1=Orifice/Grate (Orifice Controls 0.013 cfs @ 9.81 fps)

### Pond 5P: MC-7200 StormTech (3) House

Hydrograph





**GENERAL NOTES:**

CONTRACTOR IS RESPONSIBLE FOR VERIFICATION OF ALL UTILITIES PRIOR TO CONSTRUCTION AND SHALL NOTIFY ENGINEER IMMEDIATELY OF ANY CONFLICTS WITH THESE PLANS UPON DISCOVERY.

THE CONTRACTOR SHALL PREVENT SEDIMENT LADEN WATER FROM LEAVING THE SITE. ALL ADJACENT DOWNSTREAM STORM DRAIN INLETS SHALL BE PROTECTED FROM SILTATION.

THE CONTRACTOR SHALL NOT ALLOW ANY WASH WATER OR DEBRIS TO ENTER NEW PIPES OR CHANNELS DURING CONSTRUCTION.

THE CONTRACTOR SHALL AT ALL TIMES PROVIDE AND MAINTAIN AMPLE MEANS AND DEVICES TO REMOVE AND DISPOSE OF ALL WATER ENTERING THE TRENCH EXCAVATION DURING THE PROCESS OF LAYING THE PIPE.

INSTALL CONTINUOUS INSULATED COPPER TRACER WIRE OR MAGNETIC TAPE AS REQUIRED BY THE OREGON PLUMBING SPECIALTY CODE.

UNLESS OTHERWISE NOTED, ALL STORM DRAIN PIPES ARE TO HAVE A MINIMUM 1% DOWNSLOPE TO THE NEAREST STORMWATER FACILITY. STORM DRAIN PIPES ARE TO BE PVC SCHEDULE 40, ABS SCHEDULE 40, OR CAST IRON AND FOLLOW OREGON PLUMBING SPECIALTY CODE.

ALL STORM WATER PIPE CONNECTIONS TO CATCH BASINS, MANHOLES, PLANTERS AND OTHER RELATED STRUCTURES SHALL BE WATER TIGHT AS PER OREGON PLUMBING SPECIALTY CODE.

STORMWATER FACILITIES, STRUCTURES, AND PIPING SHOWN ARE INTENDED TO BE FOR SCHEMATIC PURPOSES ONLY. THE CONTRACTOR SHALL ADJUST THE ALIGNMENT AND GRADE OF THE STORMWATER SYSTEM AS NECESSARY TO ACCOMMODATE THE NEW CONSTRUCTION AND TOPOGRAPHY, WHILE MAINTAINING MINIMUM SLOPE REQUIREMENTS.

ALL COMPONENTS OF THE PRIVATE STORMWATER SYSTEM SHALL BE CONSTRUCTED PER OREGON PLUMBING SPECIALTY CODE REQUIREMENTS.


- CONSTRUCTION NOTES:**
- DIRECT DOWNSPOUTS FROM ROOF TO STORM DRAIN PIPE DISCHARGING TO MC-7200 STORMTECH SYSTEM, USE 4 INCH STORM DRAIN LINE. 4 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - STORM PIPE COLLECTING ROOF RUNOFF AND DISCHARGING TO NYLOPLAST BASIN (OR EQUIVALENT) ATTACHED TO MC-7200 STORMTECH SYSTEM. MIN 4 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - INSTALL 3 MC-7200 STORMTECH CHAMBERS INSIDE LINED ROCK GALLERY. INSTALL PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAILS. USE CONCEPTUAL ELEVATIONS AS NOTED IN DETAILS. MC-7200 CHAMBER SYSTEM IS FOR ROOF DRAINAGE ONLY.
  - CONCRETE OUTLET STRUCTURE. 48 INCH DIAMETER MANHOLE. DISCHARGE MC-7200 SYSTEM DRAIN PIPE TO OUTLET. INSTALL A GATE VALVE WITH 0.5 INCH ORIFICE DRILLED IN THE PLATE ON THE OUTLET PIPE MAKING SURE GATE VALVE IS ACCESSIBLE FROM INSIDE MANHOLE, OR INSTALL ORIFICE PLATE WITH 0.5 INCH OPENING OVER OUTLET PIPE. WATERPROOF INLET AND OUTLET PIPE OPENINGS.
  - GATE VALVE OR ORIFICE PLATE WITH 0.5 INCH ORIFICE DRILLED IN PLATE. AFTER INSTALL, GATE VALVE IS TO BE FULLY SHUT TO ALLOW PROPER FUNCTION OF THE ORIFICE.
  - 6 INCH SOLID DRAIN PIPE DISCHARGING TO EXISTING STORM DRAINAGE PIPE.
  - SLOPE DRIVEWAY TO DRAIN TO OPEN GRATE ON SUMPED NYLOPLAST BASIN ATTACHED TO SC-310 STORMTECH SYSTEM.
  - INSTALL 2 SC-310 STORMTECH CHAMBERS INSIDE LINED ROCK GALLERY AT LOW POINT OF DRIVEWAY. INSTALL PER MANUFACTURER'S INSTALLATION INSTRUCTIONS. SEE DETAILS. USE CONCEPTUAL ELEVATIONS AS NOTED IN DETAILS.
  - 3 INCH DRAIN PIPE DRAINING LINED SC-310 ROCK GALLERY. CONNECT TO GATE VALVE INSIDE 12 INCH NYLOPLAST DRAIN BASIN. CONNECT TO 6 INCH DRAIN PIPE DISCHARGING TO EXISTING STORM DRAINAGE PIPE.
  - MIN 12 INCH DIAMETER NYLOPLAST BASIN OR EQUIVALENT. RUN DRAIN PIPE FROM SC-310 ROCK GALLERY TO BASIN, INSTALL GATE VALVE WITH 0.5 INCH ORIFICE DRILLED IN PLATE. AFTER INSTALL, GATE VALVE IS TO BE FULLY SHUT TO ALLOW PROPER FUNCTION OF THE ORIFICE.
  - 6 INCH SOLID DRAIN PIPE DISCHARGING TO EXISTING 12 INCH STORM DRAIN PIPE NEAR WALKING BRIDGE. FIELD LOCATE APPROPRIATE CONNECTION POINT TO MAINTAIN 1% DOWNSLOPE. 6 INCH CONVEYANCE PIPE MUST BE CAST IRON, ABS SCHEDULE 40, OR PVC SCHEDULE 40 AND HAVE MINIMUM 1% GRADE AND FOLLOW OREGON PLUMBING SPECIALTY CODE.
  - 18 INCH DIAMETER STORMTECH NYLOPLAST BASIN OR EQUIVALENT. MINIMUM 18 INCH SUMP. INSTALL DOWN-TURN ELBOW ON OUTLET PIPE. MAY TOP WITH REDUCER TO DECREASE DIAMETER OF GRATE.



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.

**WHITE PELICAN CONSULTING**  
 PORTLAND, OREGON  
 503-847-9455  
 www.whitepelicanconsulting.com  
 email: dbeck@whitepelicanconsulting.com










**JANSEN RESIDENCE**  
 5494 LINN LANE  
 WEST LINN, OREGON 97008  
 STORMWATER MANAGEMENT  
 SITE PLAN



DATE	
7/2/24	
SCALE	PROJ. NO.
1"=10'	
DRAWN BY	CHECKED BY
TRT	DAB

**SW1**

PROPOSED LAYOUT: HOUSE		CONCEPTUAL ELEVATIONS		PART TYPE		ITEM ON LAYOUT		DESCRIPTION		INVERT	MAX FLOW
3	MC-7200	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT UNPAVED)	12.75	A	12" TOP PARTIAL CUT END CAP PART# MC7200EPP12T / TYP OF ALL 12" TOP CONNECTIONS	35.69'					
4	STORMTECH MC-7200 CHAMBERS	MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC)	8.25	B	24" BOTTOM PARTIAL CUT END CAP PART# MC7200EPP24B / TYP OF ALL 24" BOTTOM CONNECTIONS AND ISOLATOR PLUS ROWS	2.26'					
9	STONE ABOVE (IN)	MINIMUM ALLOWABLE GRADE (UNPAVED NO TRAFFIC)	7.75	C	12" BOTTOM PARTIAL CUT END CAP PART# MC7200EPP12B / TYP OF ALL 12" BOTTOM CONNECTIONS	1.55'					
9	STONE BELOW (IN)	MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT)	5.75	D	FLAMP						
40	STONE VOID	TOP OF STONE	5.75	E	MANIFOLD						
1559	INSTALLED SYSTEM VOLUME (CF)	TOP OF MC-7200 CHAMBER	3.72	F	CONCRETE STRUCTURE						
	(PERIMETER STONE INCLUDED)	12" x 12" TOP MANIFOLD INVERT	0.54	G	CONCRETE STRUCTURE						
	(COVER STONE INCLUDED)	24" ISOLATOR ROW PLUS INVERT	0.88	H	ADS N-12 DUAL WALL PERFORATED HDPE UNDERDRAIN						
425	SYSTEM AREA (SF)	12" BOTTOM CONNECTION INVERT	0.74	I	INSPECTION PORT						
88.9	SYSTEM PERIMETER (ft)	BOTTOM OF MC-7200 CHAMBER	0.00								
	UNDERDRAIN INVERT										
	THERMOPLASTIC LINER (3%)	BOTTOM OF STONE	0.00								
	(20% OVERAGE)										



**NOTES**

- DRAINAGE SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #6.32 FOR MANIFOLD SIZING GUIDANCE.
- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE IN-SITU SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- ADS DOES NOT DESIGN OR PROVIDE MEMBRANE LINER SYSTEMS FOR CISTERNS (RAINWATER HARVESTING). TO MINIMIZE THE LEAKAGE POTENTIAL OF LINER SYSTEMS, THE MEMBRANE LINER SYSTEM SHOULD BE DESIGNED BY A KNOWLEDGEABLE GEOTEXTILE PROFESSIONAL AND INSTALLED BY A QUALIFIED CONTRACTOR.
- **NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.

**ISOLATOR ROW PLUS** (SEE DETAIL)

PLACE MINIMUM 12" OF ADS PLUS 15% WOVEN GEOTEXTILE OVER BEDDING STONE AND UNDERNEATH CHAMBER FEET FOR SCOUR PROTECTION AT ALL CHAMBER INLET ROWS















































THERMOPLASTIC LINER (SEE TECH NOTE #6.50 PROVIDED BY OTHERS / DESIGN BY OTHERS)

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- A. INSPECTION PORTS (IF PRESENT)
    - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
    - A.3. USING A FLASHLIGHT AND STADIUM, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - B. ALL ISOLATOR PLUS ROWS
    - B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
  - B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
  - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS. RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

**NOTES**

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACUUMING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



**NOMINAL CHAMBER SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)

CHAMBER STORAGE

MINIMUM INSTALLED STORAGE\*

WEIGHT (NOMINAL)

100'0" X 60'0" X 78'11" (2540 mm X 1524 mm X 2010 mm)

175.9 CUBIC FEET (4.98 m³)

267.3 CUBIC FEET (7.56 m³)

205 lbs. (92.9 kg)

**NOMINAL END CAP SPECIFICATIONS**

SIZE (W X H X INSTALLED LENGTH)

END CAP STORAGE

MINIMUM INSTALLED STORAGE\*

WEIGHT (NOMINAL)

90'0" X 61'0" X 32'8" (2286 mm X 1549 mm X 833 mm)

39.5 CUBIC FEET (1.12 m³)

115.3 CUBIC FEET (3.26 m³)

90 lbs. (40.8 kg)

\*ASSUMES 12" (305 mm) STONE ABOVE, 9" (229 mm) STONE FOUNDATION AND BETWEEN CHAMBERS, 12" (305 mm) STONE PERIMETER IN FRONT OF END CAPS AND 40% STONE POROSITY.



PARTIAL CUT HOLES AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"

PARTIAL CUT HOLES AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

END CAPS WITH A PREFABRICATED WELDED STUB END WITH "Y"

PART #	STUB	B	C
MC7200EPP06T	6" (150 mm)	42.54" (1081 mm)	
MC7200EPP06B			0.86" (22 mm)
MC7200EPP08T	8" (200 mm)	40.50" (1029 mm)	
MC7200EPP08B			1.01" (26 mm)
MC7200EPP10T	10" (250 mm)	38.37" (975 mm)	
MC7200EPP10B			1.33" (34 mm)
MC7200EPP12T	12" (300 mm)	35.69" (907 mm)	
MC7200EPP12B			1.55" (39 mm)
MC7200EPP15			

PROPOSED LAYOUT: DRIVEWAY	CONCEPTUAL ELEVATIONS	PART TYPE	ITEM ON LAYOUT	DESCRIPTION	INVERT	MAX FLOW
SC-310	MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):					9.83
2	STORMTECH SC-310 CHAMBERS					3.83
4	STORMTECH SC-310 END CAPS					3.33
6	STONE ABOVE (IN)					3.33
6	STONE BELOW (IN)					3.33
40	STONE VOID					3.33
129	INSTALLED SYSTEM VOLUME (CF) (PERIMETER STONE INCLUDED) (COVER STONE INCLUDED) (BASE STONE INCLUDED)					0.9 CFS IN
120	SYSTEM AREA (SF)					0.7 CFS OUT
44.8	SYSTEM PERIMETER (ft)					
30	THERMOPLASTIC LINER (3% (20% OVERAGE))					




**NOTES**

- DRAINFIELD SIZE TO BE DETERMINED BY SITE DESIGN ENGINEER. SEE TECH NOTE #6.32 FOR MANIFOLD SIZING GUIDANCE DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.
- THIS CHAMBER SYSTEM WAS DESIGNED WITHOUT SITE-SPECIFIC INFORMATION ON SOIL CONDITIONS OR BEARING CAPACITY. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR DETERMINING THE SUITABILITY OF THE SOIL AND PROVIDING THE BEARING CAPACITY OF THE INSTALLED SOILS. THE BASE STONE DEPTH MAY BE INCREASED OR DECREASED ONCE THIS INFORMATION IS PROVIDED.
- ADS DOES NOT DESIGN OR PROVIDE MEMBRANE LINER SYSTEMS FOR CISTERNS (RAINWATER HARVESTING). TO MINIMIZE THE LEAKAGE POTENTIAL OF LINER SYSTEMS, THE MEMBRANE LINER SYSTEM SHOULD BE DESIGNED BY A KNOWLEDGEABLE GEOTEXTILE PROFESSIONAL AND INSTALLED BY A QUALIFIED CONTRACTOR.
- **NOT FOR CONSTRUCTION:** THIS LAYOUT IS FOR DIMENSIONAL PURPOSES ONLY TO PROVE CONCEPT & THE REQUIRED STORAGE VOLUME CAN BE ACHIEVED ON SITE.

4



**UNDERDRAIN DETAIL**



NUMBER AND SIZE OF UNDERDRAINS PER SITE DESIGN ENGINEER  
4" (100 mm) TYP FOR SC-310 & SC-100LP SYSTEMS  
6" (150 mm) TYP FOR SC-740, SC-800, DC-780, MC-3500, MC-4500 & MC-7200 SYSTEMS


SPACE INTENTIONALLY LEFT BLANK

**SC-310 TECHNICAL SPECIFICATION**



NOMINAL CHAMBER SPECIFICATIONS	34.0" X 16.0" X 85.4" (864 mm X 406 mm X 2169 mm)
SIZE (W X H X INSTALLED LENGTH)	14.7 CUBIC FEET (0.42 m³)
CHAMBER STORAGE	31.0 CUBIC FEET (0.88 m³)
MINIMUM INSTALLED STORAGE*	35.0 lbs. (16.8 kg)

\*ASSUMES 6" (152 mm) ABOVE, BELOW, AND BETWEEN CHAMBERS



PART #	STUB	A	B	C
SC310EPE06T / SC310EPE06TPC	6" (150 mm)	9.6" (244 mm)	5.8" (147 mm)	---
SC310EPE08T / SC310EPE08TPC	8" (200 mm)	11.9" (302 mm)	3.5" (89 mm)	0.6" (15 mm)
SC310EPE10T / SC310EPE10TPC	10" (250 mm)	12.7" (323 mm)	1.4" (36 mm)	0.7" (18 mm)
SC310EPE12T / SC310EPE12TPC	12" (300 mm)	13.5" (343 mm)	---	0.9" (23 mm)

ALL STUBS, EXCEPT FOR THE SC310ECEZ ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2894.

\*FOR THE SC310ECEZ THE 12" (300 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 0.25" (6 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL.


2

**SC-310 TECHNICAL SPECIFICATION**

**ACCEPTABLE FILL MATERIALS: STORMTECH SC-310 CHAMBER SYSTEMS**

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	<b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	ANY SOIL/ROCK MATERIALS, NATIVE SOILS, OR PER ENGINEER'S PLANS. CHECK PLANS FOR PAVEMENT SUBGRADE REQUIREMENTS.	N/A
C	<b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE. MOST PAVEMENT SUBBASE MATERIALS CAN BE USED IN LIEU OF THIS LAYER.	AASHTO M145' A-1, A-2.4, A-3 OR AASHTO M43' 3, 3S7, 4, 4E7, 5, 5E, 57, 6, 67, 69, 7, 78, 8, 89, 9, 10
B	<b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETES	AASHTO M43' 3, 3S7, 4, 4E7, 5, 5E, 57
A	<b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	CLEAN, CRUSHED, ANGULAR STONE OR RECYCLED CONCRETES	AASHTO M43' 3, 3S7, 4, 4E7, 5, 5E, 57

- PLEASE NOTE:
1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
  2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
  3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAVING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.
  4. ONCE LAYER 'C' IS PLACED, ANY SOIL MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.
  5. WHERE RECYCLED CONCRETE AGGREGATE IS USED IN LAYERS 'A' OR 'B' THE MATERIAL SHOULD ALSO MEET THE ACCEPTABILITY CRITERIA OUTLINED IN TECHNICAL NOTE 6.20 "RECYCLED CONCRETE STRUCTURAL BACKFILL".



**NOTES:**

1. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2922 (POLYETHYLENE) OR ASTM F2418 (POLYPROPYLENE), "STANDARD SPECIFICATION FOR CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
2. SC-310 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
3. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
4. PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
5. REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT SHALL BE GREATER THAN OR EQUAL TO 400 LBS/FT². THE ASC IS DEFINED IN SECTION 6.2.8 OF ASTM F2418. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.

1

**SC-310 CROSS SECTION DETAIL**

**SC-310 ISOLATOR ROW PLUS DETAIL**

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- A.1. INSPECTION PORTS (IF PRESENT)
  - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
  - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
  - A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
  - A.4. LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
  - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- B. ALL ISOLATOR PLUS ROWS
- B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
  - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
    - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
    - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - iii) IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JET/VAC PROCESS
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
  - B. APPLY MULTIPLE PASSES OF JET/VAC UNTIL BACKFLUSH WATER IS CLEAN
  - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

**NOTES**

1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.


SPACE INTENTIONALLY LEFT BLANK



WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.

**WHITE PELICAN CONSULTING**  
PORTLAND, OREGON  
503-847-9455  
www.whitepelicanconsulting.com  
email: dbeck@whitepelicanconsulting.com

**JANSEN RESIDENCE**  
5494 LINE AVENUE  
WEST LINN, OREGON 97008  
STORMWATER MANAGEMENT DETAILS



DATE	5/24/24
SCALE	NTS
DRAWN BY	TRT
CHECKED BY	DB

**SW3**






WHITE PELICAN CONSULTING IS NOT LIABLE FOR THE ACCURACY OF THE TOPOGRAPHY INFORMATION. IT IS THE SOLE RESPONSIBILITY OF THE BUILDER TO VERIFY ALL SITE CONDITIONS, INCLUDING ANY FILL PLACED ON THE SITE, AND INFORM OWNERS OF ANY POTENTIAL FIELD MODIFICATIONS.



**WHITE PELICAN CONSULTING**  
 PORTLAND, OREGON  
 503-847-9455  
 www.whitepelicanconsulting.com  
 email: dbeck@whitepelicanconsulting.com

JANSEN RESIDENCE  
 5494 LINE AVENUE  
 WEST LINN, OREGON 97068  
 STORMWATER MANAGEMENT  
 DETAILS




DATE	5/31/24
SCALE	NTS
PROJ. NO.	
DRAWN BY	TRT
CHECKED BY	DB

**SW4**




<b>Oldcastle Precast</b>	<b>48" MANHOLE</b>	<b>48" MANHOLE</b>
PO Box 323, Wilsonville, Oregon 97070-0323 Tel: (503) 682-2844 Fax: (503) 682-2657	File Name: 020-48MH Issue Date: 2017 oldcastleprecast.com/wilsonville	

MANHOLE  
 DETAIL  
 NTS ①



DRAIN BASIN  
 DETAIL  
 NTS ②



- NOTES**
- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
  - 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
  - DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
  - DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE ADS & HANCOCK DUAL WALL, & SDR 35 PVC
  - FOR COMPLETE DESIGN AND PRODUCT INFORMATION: WWW.NYLOPLAST-US.COM
  - TO ORDER CALL: 800-821-6710

A	PART #	GRATE/SOLID COVER OPTIONS
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY STANDARD LIGHT DUTY SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY STANDARD LIGHT DUTY SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10 STANDARD AASHTO H-20 SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20 STANDARD AASHTO H-20 SOLID AASHTO H-20

REDUCER  
 DETAIL  
 NTS ③

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH NYLOPLAST HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN. REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM NYLOPLAST. ©2018 NYLOPLAST

DRAWN BY: CJA  
 DATE: 2-6-23  
 MATERIAL: NYLOPLAST  
 PROJECT NO. NAME:  

REVISED BY: JJC  
 DATE: 7-16-13  
 DWG SIZE: A SCALE: 1:25 SHEET: 1 OF 1  
 DWG NO.: 7001-110-104 REV: E

3130 VERONA AVE  
 BUFORD, GA 30518  
 PHN (770) 932-2440  
 FAX (770) 932-2400  
 www.nyloplast-us.com

TITLE: DRAIN BASIN WITH REDUCER OPTIONS

**EXHIBIT PD-2 – COMPLETENESS LETTER**



CITY OF  
**West Linn**

July 29, 2024

Kevin Janssen,  
614 SE 52<sup>nd</sup> Ave  
Portland OR 97215

Subject: WAP-24-01 Water Resource Area Permit for the replacement of an existing single-family residence at 5494 Linn Lane

Dear Mr. Janssen:

Your application was accepted for review February 20, 2024, and deemed complete as of July 8, 2024 following submission of a revised application package. The city has up to 120 days to exhaust all local review; that period ends November 5, 2024.

Please be aware that determination of a complete application does not guarantee a recommendation of approval from staff for your proposal as submitted – it signals that staff believes you have provided the necessary information for the Planning Director to render a decision on your proposal.

A 21-day public notice will be prepared and mailed. This notice will identify the earliest potential decision date by the Planning Director.

Please contact me at 503-742-6058, or by email at [jfloyd@westlinnoregon.gov](mailto:jfloyd@westlinnoregon.gov) if you have any questions or comments.

Sincerely,

A handwritten signature in blue ink, appearing to read 'John Floyd', with a stylized flourish extending from the end.

John Floyd  
Senior Planner

**EXHIBIT PD-3 – PUBLIC COMMENTS**

## Comments on City of West Linn Notice of Upcoming Planning Manager Decision

### **Citation:**

#### **CDC 32.050**

G. Construction management plan. The applicant shall submit a construction management plan which includes the following:

1. The location of proposed TDAs (site ingress/egress for construction equipment, areas for storage of material, construction activity areas, grading and trenching, etc.) that will subsequently be restored to original grade and replanted with native vegetation, shall be identified, mapped and enclosed with fencing per subsection (G)(3) of this section.
2. Appropriate erosion control measures consistent with Clackamas County Erosion Prevention and Sediment Control Planning and Design Manual, rev. 2008, and a tentative schedule of work.

### **Comments:**

In general, the application seemed to be very comprehensive in addressing the CDC requirements for requesting a WRA waiver, except in one crucial area.

The applicant states in his response to the letter from the City that the required Construction Management Plan is contained in Sheet A Plot Plan. This Plan does not address the items required in CDC 32.050 paragraph 1 concerning TDAs nor appropriate erosion control measures in paragraph 2.

The proposed site is at the north end of Linn Lane, a dead-end, very narrow (1.5 lanes) street. Construction vehicles will cause much disruption of local traffic, especially if construction vehicles are allowed to park on the street. There is no mention on the plan of where construction vehicles will park. In addition, the street asphalt is already severely cracked in multiple places. Heavy construction vehicles will place a severe strain on the already degraded condition. What is the mitigation for this effect.

The site is extremely steep with little area for storage of construction materials and, especially, where dirt disrupted from grading and construction will be stored without impacting the WRA.

As a resident of Linn Lane, the City has not adequately put conditions on how Construction Management will be performed in order to protect the integrity of the street and the access of residents to and from their homes.

August 20, 2024

City of West Linn, Planning Manager; [ifloyd@westlinnoregon.com](mailto:ifloyd@westlinnoregon.com)

As requested in your mailing of July 31, 2024, please allow this communication to act as our letter of Comments for Consideration.

In accordance with chapter 32 of the CDC we have concerns regarding the proposed reshaping of our little portion of this community. The terrain in our area is on the side of a hill with significant sloping and run off. The vegetation, trees and surrounding environment have evolved over many, many years; as have the very large trees on our property. We don't know the full impact of these proposed changes and alterations. The inhabitants, vegetation and trees have adapted to the sediments, drainage, erosion, wind patterns, ice and rain storms, shade and light, etc. These stable and established patterns will now be subject to substantial revision. We are very concerned about our existing hillside and the causally cascading impacts any reshaping might bring.

We are confident that you will not allow for any unnecessary disturbance of our property or our quality of life.

Steve and Lorna Lathram

5184 Linn Ln, West Linn, 97068


**EXHIBIT PD-4 – AGENCY COMMENTS**



## Response Page

Department of State Lands (DSL) WN# \*

WN2024-0517

### Responsible Jurisdiction

**Staff Contact**

John Floyd

**Jurisdiction Type**

City

**Municipality**

West Linn

**Local case file #**

WAP-24-01

**County**

Clackamas

### Activity Location

Township	Range	Section	QQ section	Tax Lot(s)
02S	01E	25	BD	500

Street Address

5494 Linn Ln

Address Line 2

City

West Linn

Postal / Zip Code

97068

State / Province / Region

OR

Country

Clackamas

**Latitude**

45.368806

**Longitude**

-122.633139

### Wetland/Waterway/Other Water Features

There are/may be wetlands, waterways or other water features on the property that are subject to the State Removal-Fill Law based upon a review of wetland maps, the county soil survey and other available information.

Local Wetlands Inventory shows wetland, waterway or other water features on the property

### Your Activity

A state permit will not be required for the proposed project because, based on the submitted site plan, the project avoids impacts to jurisdictional wetlands, waterways, or other waters.

### Applicable Oregon Removal-Fill Permit Requirement(s)



- A state permit is required for 50 cubic yards or more of fill removal or other ground alteration in wetlands, below ordinary high water of waterways, within other waters of the state, or below highest measured tide.

## DSL Review



### Wetland Ecologist Comments

Wetlands as depicted in WD2023-0462 appear to be avoided. Therefore, no state permit is needed.

**This is a preliminary jurisdictional determination and is advisory only.**

This report is for the State Removal-Fill law only. City or County permits may be required for the proposed activity.

### Contact Information

For information on permitting, use of a state-owned water, wetland determination or delineation report requirements please contact the respective DSL Aquatic Resource, Proprietary or Jurisdiction Coordinator for the site county.

#### Response Date

8/28/2024

#### Response by:

Matthew Unitis

#### Response Phone:

503-910-1559



# Wetland Land Use Notification

## OREGON DEPARTMENT OF STATE LANDS

775 Summer Street NE, Suite 100, Salem, OR 97301-1279

Phone: (503) 986-5200

This form is to be completed by planning department staff for mapped wetlands and waterways.

\* Required Field (?) Tool Tips

## Activity Location



**Township** \* (?)

02S

**Range** \* (?)

01E

**Section** \* (?)

25

**Quarter-quarter Section** (?)

BD

**Tax Lot(s)** \*

500

You can enter multiple tax lot numbers within this field. i.e. 100, 200, 300, etc.

To add additional tax map and lot information, please click the "add" button below.

## Address

Street Address

5494 Linn Ln

Address Line 2

City

West Linn

Postal / Zip Code

97068

State

OR

Country

USA

**County** \*

Clackamas

**Adjacent Waterbody**

Barlow Cr

**Geolocation** \*

45.2207, 122.3759

## Proposed Activity



Prior to submitting, please ensure proposed activity will involve physical alterations to the land and/or new construction or expansion of footprint of existing structures.

**Local Case File #** \* (?)

WAP-24-01

**Zoning**

Residential, R-10

**Describe any Earthwork/Ground Disturbance** \*

Substantial grading upslope from wetlands

## Proposed

- Building Permit (new structures)
- Grading Permit
- Site Plan Approval
- Other (please describe)  
Water Resource Area Permit
- Conditional use Permit
- Planned Unit Development
- Subdivision

## Applicant's Project Description and Planner's Comments: \*

Demolition of the existing SFD and replacement with a larger SFD and expansion of the driveway located between two wetlands from 9 feet to 15 feet. Reduction of a highly degraded water resource area (wetland buffer) from through the alternative review process. The two wetlands total 0.05 acres in size and the water resource area would be reduced from 100-150 feet to 65 feet with mitigation planting.

## Required attachments with site marked: Tax map and legible, scaled site plan map. (?)

03\_2s1e25bd.pdf 2.09MB

## Additional Attachments

WAP-24-02 Applicant Resubmittal 07.08.24.pdf 26.43MB

## Applicant

### First Name \*

Kevin

### Last Name \*

Janssen

### Applicant Organization Name

(if applicable)

### Mailing Address \*

Street Address

614 SE 52nd Ave

Address Line 2

City

Portland

Postal / Zip Code

97215

State

OR

Country

USA

### Phone (?)

503-515-0653

### Email (?)

khjanssen@yahoo.com

### Is the Property Owner name and address the same as the Applicant? \*

No  Yes

## Property Owner

### First Name \*

Robert

### Last Name \*

Easton

### Property Owner Organization Name

(if applicable)

### Mailing Address (If different than Applicant Address)

Street Address

21520 Lupine Ct

Address Line 2

City

West Linn

Postal / Zip Code

97068

State

OR

Country

USA

**Phone** (?)

503-866-8810

**Email** (?)

bobeaston@comcast.net

### Responsible Jurisdiction



\*

City of  County of

**Municipality**\*

West Linn

**Date**\*

7/28/2024

### Staff Contact

**First Name**\*

John

**Last Name**\*

Floyd

**Phone**\* (?)

503-742-6058

**Email**\*

jfloyd@westlinnoregon.gov

**EXHIBIT PD-5 – AFFADAVIT AND NOTICE PACKET**

**CITY OF WEST LINN  
NOTICE OF UPCOMING PLANNING MANAGER DECISION  
FILE NO. WAP-24-01**

The West Linn Planning Manager is considering Water Resource Area Permit (Alternative Review Process) at 5494 Linn Lane. The applicant is requesting approval for the demolition of the existing single-family residence and the construction of a new single-family dwelling on a property containing two wetlands. Included in the proposal is the proposed reduction and enhancement of the Water Resource Area (Buffer) through the alternative review process.

The Planning Manager will decide the application based on criteria in Chapters 11, 32, 48, 96, and 99 of the Community Development Code (CDC). The CDC approval criteria are available for review on the City website <http://www.westlinnoregon.gov/cdc> or at City Hall and the City Library.

The application is posted on the City's website, <https://westlinnoregon.gov/projects>. The application, all documents or evidence relied upon by the applicant and applicable criteria are available for inspection at City Hall at no cost. Copies may be obtained at reasonable cost.

A public hearing will not be held for this decision. **Anyone wishing to submit comments for consideration must submit all material before 4:00 p.m. on August 20, 2024 to [jfloyd@westlinnoregon.com](mailto:jfloyd@westlinnoregon.com) or mail them to City Hall. All comments must be received by the deadline.**

**It is important to submit all testimony in response to this notice.** All comments submitted for consideration of this application should relate specifically to the applicable criteria. Failure to raise an issue in a hearing, in person, or by letter, or failure to provide sufficient specificity to afford the decision-maker an opportunity to respond to the issue, precludes appeal to the Oregon Land Use Board of Appeals based on that issue (CDC Section 99.090).

The final decision will be posted on the website and available at City Hall. Persons with party status may appeal the decision by submitting an appeal application to the Planning Department within 14 days of mailing the notice of the final decision pursuant to CDC [99.240](#).

For additional information, please contact John Floyd, Senior Planner, City Hall, 22500 Salamo Rd., West Linn, OR 97068, 503-742-6058.

Scan this QR Code to go to Project Web Page:



Mailed July 31, 2024



**AFFIDAVIT OF NOTICE  
PLANNING MANAGER DECISION**

We, the undersigned, certify that, in the interest of the party (parties) initiating a proposed land use, the following took place on the dates indicated below:

**PROJECT**

File No.: **WAP-24-01**                                  Applicant’s Name:        **Kevin Janssen**  
Development Address: **5494 Linn Lane**  
Planning Manager Decision no earlier than **August 20, 2024**

**MAILED NOTICE**

Notice of Upcoming Planning Manager Decision was mailed at least 14days before the decision, per Section 99.080 of the CDC to:

Kevin Janssen, applicant representative	7/31/24	<i>Lynn Schroder</i>
Robert Easton, property owner	7/31/24	<i>Lynn Schroder</i>
Property owners within 500ft of the site perimeter	7/31/24	<i>Lynn Schroder</i>
Rosemont Summit Neighborhood Association	7/31/24	<i>Lynn Schroder</i>
Oregon Dept of Fish & Wildlife	7/31/24	<i>Lynn Schroder</i>
US Army Corps of Engineers	7/31/24	<i>Lynn Schroder</i>

**EMAILED NOTICE**

Notice of Upcoming Planning Manager Decision was emailed at least 14 days before the decision to:

Rosemonth Summit Neighborhood Association	7/29/24	<i>Lynn Schroder</i>
Kevin Janssen, applicant	7/29/24	<i>Lynn Schroder</i>
Bob Easton, property owner	7/29/24	<i>Lynn Schroder</i>
Oregon Division of State Lands, Jevra Brown	7/29/24	<i>Lynn Schroder</i>

**WEBSITE**

Notice of Upcoming Planning Manager Decision was posted on the City’s website at least 14 days before the decision.

7/29/24	<i>Lynn Schroder</i>
---------	----------------------

**SIGN**

A sign for Upcoming Planning Manager Decision was posted on the property at least 10 days before the decision, per Section 99.080 of the CDC.


07/30/24	<i>John Floyd</i>
----------	-------------------

**FINAL DECISION**

Notice of Final Decision was mailed to the applicant, all parties with standing, and posted on the City’s website, per Section 99.040 of the CDC.

10/3/24	Lynn Schroder
---------	---------------

WAP-24-01 - Notified Properties within 500 feet of 5494 Linn Lane







**NOTICE OF UPCOMING  
PLANNING MANAGER DECISION**

**PROJECT # WAP-24-01  
MAIL: 07.31.24 TIDINGS: N/A**

**CITIZEN CONTACT INFORMATION**

To lessen the bulk of agenda packets and land use application notice, and to address the concerns of some City residents about testimony contact information and online application packets containing their names and addresses as a reflection of the mailing notice area, this sheet substitutes for the photocopy of the testimony forms and/or mailing labels. A copy is available upon request.