

NOTE:

1. ALL WALL THICKNESS ON THIS PAGE ARE 8" UNLESS OTHERWISE NOTED.

STEEL NOTES:

- A. CODES SPECIFICATIONS: STEEL CONSTRUCTION SHALL CONFORM TO THE SPECIFICATIONS AND STANDARDS AS CONTAINED IN THE CURRENT EDITION OF THE AISC MANUAL OF STEEL CONSTRUCTION.
- B. MATERIAL: STRUCTURAL SHAPES, BARS, PLATES, AND SHEETS INDICATED ON THE DRAWINGS SHALL BE STEEL MEETING ASTM A36 SPECIFICATIONS. BOLTS SHALL CONFORM TO ASTM A307.
- C. WELDING: WELDING SHALL CONFORM TO AWS D1.1 CODE FOR ARC AND GAS WELDING IN BUILDING CONSTRUCTION. ELECTRODE SHALL BE E70XX LOW HYDROGEN GROUP. WELDING SHALL BE CONDUCTED BY WELDERS CERTIFIED BY THE AWS. ALL WELDS SHALL BE MIN 3/16" FILLET UNLESS OTHERWISE NOTED.
- D. HOT DIP GALVANIZING: UNLESS OTHERWISE NOTED, ALL STEEL FABRICATIONS SHALL BE HOT DIP GALVANIZED AFTER FABRICATION.

TITION: STANDARD INLET AND OUTLET HEADWALL STRUCTURE (FOR OUTLETS OF 36" DIA.

WL-DET1350

C WORKS DEPARTMENT - STANDARD DRAWINGS 22500 Salamo Road, West Linn OR 97068

All material and workmanship shall be in accordance with the City of West Linn Standard Construction

this Standard Drawing, while designed in accordance with generally accepted engineering orinciples and practices, is the sole responsibility of the user and should not be used without consulting a Registered

File CAD_FILE_NAME