



- NOTE:
1. UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER, STREETS SHALL BE PAVED TO FINAL GRADE USING 2 OR MORE LIFTS. FINAL LIFT SHALL BE PLACED ONLY AFTER ACCEPTANCE OF THE FIRST LIFT AT A TIME AS DIRECTED OR APPROVED BY THE CITY ENGINEER. A PLAIN CONCRETE PAVEMENT ALTERNATIVE CROSS-SECTION, CONSISTING OF 7 INCH PCC ON COMPACTED SUBGRADE, IS ALLOWED WITH APPROVAL OF CITY ENGINEER.
 2. ROAD BASE SHALL BE PREPARED 1 FOOT BEHIND CURB.
 3. STANDARD CURB PER ODOT RD700. H=16", E=4"
 4. 4" OF PORTLAND CEMENT CONCRETE OVER 2" OF 3/4"-0" AGGREGATE BASE.
 5. LANDSCAPE BUFFER SHALL BE COVERED WITH 6" OF QUALITY TOPSOIL.

Standard Drawing No. WL-RD011	Title: STANDARD STREET CROSS-SECTION COLLECTOR	 City of West Linn PUBLIC WORKS DEPARTMENT - STANDARD DRAWINGS 22500 Salamo Road, West Linn OR 97068 Phone: 503-722-5500 www.westlinnoregon.gov	NOTE: All material and workmanship shall be in accordance with the City of West Linn Standard Construction Specifications.	The selection and use of this Standard Drawing, while designed in accordance with generally accepted engineering principles and practices, is the sole responsibility of the user and should not be used without consulting a Registered Professional Engineer. File WL-RD011.dwg
Effective Date: 02/22/19	Approved  City Engineer			